

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:

0850150024

Status:

Active

Overview:


[din_41612](#)

Description:

2.54mm (.100") Pitch DIN 41612 Header, 4-Row C-Pin, Press-Fit Style R Reverse, 0.6µm (24µ") Selective Gold (Au), 128 Circuits, Lead free

Documents:	
3D Model	Product Specification PS-85013-0002 (PDF)
Drawing (PDF)	RoHS Certificate of Compliance (PDF)

Agency Certification	
CSA	LR19980
UL	E29179
General	
Product Family	Backplane Connectors
Series	85015
Application	Backplane
Comments	"R" at Style Represents Vertical Male DIN Connectors
Component Type	PCB Header
Overview	din_41612
Product Name	IEC 603-2/DIN 41612
Style	R
Physical	
Circuits (Loaded)	128
Circuits (maximum)	128
Circuits Detail	Rows A, B, C & D
Color - Resin	Gray
Durability (mating cycles max)	400
First Mate / Last Break	No
Flammability	94V-0
Guide to Mating Part	No
Keying to Mating Part	Yes
Material - Metal	Phosphor Bronze
Material - Plating Mating	Gold
Material - Plating Termination	Tin
Material - Resin	Polyester
Number of Columns	32
Number of Pairs	Open Pin Field
Number of Rows	4
Orientation	Vertical
PC Tail Length (in)	0.520 In
PC Tail Length (mm)	13.20 mm
PCB Locator	No
PCB Retention	Yes
PCB Thickness Recommended (in)	0.063 In, 0.157 In
PCB Thickness Recommended (mm)	1.60 mm, 4.00 mm
Packaging Type	Carton
Pitch - Mating Interface (in)	0.100 In
Pitch - Mating Interface (mm)	2.54 mm
Pitch - Term. Interface (in)	0.100 In
Pitch - Term. Interface (mm)	2.54 mm
Polarized to PCB	Yes
Stackable	No
Surface Mount Compatible (SMC)	No



EU RoHS

ELV and RoHS Compliant

REACH SVHC

Not Reviewed

Halogen-Free

Status

Not Reviewed

China RoHS



Need more information on product environmental compliance?

Email productcompliance@molex.com

For a multiple part number RoHS Certificate of Compliance, [click here](#)

Please visit the [Contact Us](#) section for any non-product compliance questions.

Search Parts in this Series

[85015Series](#)

Mates With

[85042](#) DIN 41612 Receptacle . [85052](#) DIN 41612 Header

Use With

[85089-1081](#) Press-in Tool

Temperature Range - Operating

Termination Interface: Style

-55°C to +125°C

Through Hole - Compliant Pin

Electrical

Current - Maximum per Contact

Data Rate

Voltage - Maximum

1A

622.0 Mbps

250V AC (RMS)

Material Info

Reference - Drawing Numbers

Product Specification

Sales Drawing

PS-85013-0002

SDA-85015-0024

This document was generated on 05/17/2010

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

