

Model 7115
XLR D Square Flanged Panel Receptacle

Use for your audio applications to protect contacts and absorb vibrations.

Features

- 3-pin audio receptacle with sturdy all metal one piece design
- Solder cup terminations
- Front mountable
- Female receptacles have latch lock mechanism

Materials

- Housing is diecast zinc alloy with tarnish resistant black nickel-plating.
- Ground tab is made of steel

Ordering Information

Model: 7115



Model 7115 D Series Square Flanged Panel Receptacle Solder Cups 3 Pin (F), Black

Specifications

Number of contacts	3
Contact resistance	< 5 mΩ
Dielectric strength	1500 V dc
Wire Size (AWG)	14 AWG / 2.5 mm ²

USA: Sales: 800-490-2361

Technical Support: technicalsupport@pomonatest.com

Fax: 425-446-5844

Europe: 31-(0) 40 2675 150 **International:** 425-446-5500

Where to Buy: www.pomonaelectronics.com

All dimensions are in inches. Tolerances (except noted): .xx = ±.02" (.51 mm), .xxx = ± .005" (.127 mm). All specifications are to the latest revisions. Specifications are subject to change without notice. Registered trademarks are the property of their respective companies.

Last Update: 10/08/07
D1103997, Rev. 004

Copyright 2007

Page 1 of 1