

### PLASTIC SILICON RECTIFIER

VOLTAGE RANGE: 50 --- 1000 V

CURRENT: 6.0 A


#### FEATURES

- ◇ Low cost
- ◇ Diffused junction
- ◇ Low leakage
- ◇ Low forward voltage drop
- ◇ High current capability
- ◇ Easily cleaned with Freon, Alcohol, Isopropanol and similar solvents
- ◇ The plastic material carries U/L recognition 94V-0

#### MECHANICAL DATA

- ◇ Case: JEDEC R-6, molded plastic
- ◇ Terminals: Axial lead, solderable per MIL-STD-202, Method 208
- ◇ Polarity: Color band denotes cathode
- ◇ Weight: 0.072 ounces, 2.04 grams
- ◇ Mounting position: Any

#### R - 6



#### MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature unless otherwise specified.

Single phase, half wave, 60 Hz, resistive or inductive load. For capacitive load, derate by 20%.

|                                                                                                                   |                 | 6A05            | 6A1 | 6A2 | 6A4 | 6A6 | 6A8 | 6A10 | UNITS              |
|-------------------------------------------------------------------------------------------------------------------|-----------------|-----------------|-----|-----|-----|-----|-----|------|--------------------|
| Maximum recurrent peak reverse voltage                                                                            | $V_{RRM}$       | 50              | 100 | 200 | 400 | 600 | 800 | 1000 | V                  |
| Maximum RMS voltage                                                                                               | $V_{RMS}$       | 35              | 70  | 140 | 280 | 420 | 560 | 700  | V                  |
| Maximum DC blocking voltage                                                                                       | $V_{DC}$        | 50              | 100 | 200 | 400 | 600 | 800 | 1000 | V                  |
| Maximum average forward rectified current<br>9.5mm lead length, @ $T_A=75^\circ\text{C}$                          | $I_{F(AV)}$     | 6.0             |     |     |     |     |     |      | A                  |
| Peak forward surge current<br>8.3ms single half-sine-wave<br>superimposed on rated load @ $T_J=125^\circ\text{C}$ | $I_{FSM}$       | 400.0           |     |     |     |     |     |      | A                  |
| Maximum instantaneous forward voltage<br>@ 6.0 A                                                                  | $V_F$           | 1.0             |     |     |     |     |     |      | V                  |
| Maximum reverse current @ $T_A=25^\circ\text{C}$<br>at rated DC blocking voltage @ $T_A=100^\circ\text{C}$        | $I_R$           | 10.0<br>100.0   |     |     |     |     |     |      | $\mu\text{A}$      |
| Typical junction capacitance (Note1)                                                                              | $C_J$           | 120             |     |     |     |     |     |      | pF                 |
| Typical thermal resistance (Note2)                                                                                | $R_{\theta JA}$ | 10              |     |     |     |     |     |      | $^\circ\text{C/W}$ |
| Operating junction temperature range                                                                              | $T_J$           | - 55 ---- + 150 |     |     |     |     |     |      | $^\circ\text{C}$   |
| Storage temperature range                                                                                         | $T_{STG}$       | - 55 ---- + 150 |     |     |     |     |     |      | $^\circ\text{C}$   |


NOTE: 1. Measured at 1.0MHz and applied reverse voltage of 4.0V DC.

2. Thermal resistance from junction to ambient.

www.galaxycn.com

FIG.1 – FORWARD DERATING CURVE


AVERAGE FORWARD RECTIFIED CURRENT  
AMPERES



AMBIENT TEMPERATURE, °C

FIG.2 – TYPICAL FORWARD CHARACTERISTICS


INSTANTANEOUS FORWARD CURRENT  
AMPERES



INSTANTANEOUS FORWARD VOLTAGE, VOLTS

FIG.3 –MAXIMUM NON-REPETITIVE FORWARD  
SURGE CURRENT


PEAK FORWARD SURGE CURRENT  
AMPERES



NUMBER OF CYCLES AT 60Hz

FIG.4 – TYPICAL JUNCTION CAPACITANCE

CAPACITANCE, pF



REVERSE VOLTAGE, VOLTS