

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: [0039299042](#)
Status: **Active**
Overview: [minifit_jr](#)
Description: 4.20mm (.165") Pitch Mini-Fit Jr.™ Header, Dual Row, Vertical, with Snap-in Plastic Peg PCB Lock, 4 Circuits, PA Polyamide Nylon 6/6 94V-2, Tin (Sn) Plating, with Drain Holes

Documents:	
3D Model	Product Specification PS-5556-001 (PDF)
Drawing (PDF)	RoHS Certificate of Compliance (PDF)

Agency Certification


CSA	LR19980
TUV	R72081037
UL	E29179

General

Product Family	PCB Headers
Series	5566
Application	Wire-to-Board
Comments	Current = 13A max. per circuit when header is mated to a receptacle loaded with 45750 Mini-Fit Plus HCS™ Crimp Terminal Crimped to to 16 AWG wire. . See Molex product specification PS-45750-001 for additional current de-rating information.. High Temperature, Square Pin, Solder Type
Overview	minifit_jr
Product Name	Mini-Fit Jr.™

Physical

Breakaway	No
Circuits (Loaded)	4
Circuits (maximum)	4
Color - Resin	Natural
Durability (mating cycles max)	30
First Mate / Last Break	No
Flammability	94V-2
Glow-Wire Compliant	No
Guide to Mating Part	No
Keying to Mating Part	None
Lock to Mating Part	Yes
Material - Metal	Brass
Material - Plating Mating	Tin
Material - Plating Termination	Tin
Material - Resin	Nylon
Number of Rows	2
Orientation	Vertical
PC Tail Length (in)	0.138 In
PC Tail Length (mm)	3.50 mm
PCB Locator	Yes
PCB Retention	Yes
PCB Thickness Recommended (in)	0.062 In
PCB Thickness Recommended (mm)	1.60 mm
Packaging Type	Tray
Pitch - Mating Interface (in)	0.165 In
Pitch - Mating Interface (mm)	4.20 mm



EU RoHS
ELV and RoHS
Compliant
REACH SVHC
Contains SVHC: No
Halogen-Free
Status
Halogen-Free

China RoHS

Need more information on product environmental compliance?

Email productcompliance@molex.com
For a multiple part number RoHS Certificate of Compliance, [click here](#)

Please visit the [Contact Us](#) section for any non-product compliance questions.

Search Parts in this Series
[5566Series](#)

Mates With
[5557](#) Mini-Fit Jr.™ Receptacle Housing

Pitch - Term. Interface (in)	0.165 In
Pitch - Term. Interface (mm)	4.20 mm
Plating min: Mating (µin)	355.6
Plating min: Mating (µm)	8.89
Plating min: Termination (µin)	355.6
Plating min: Termination (µm)	8.89
Polarized to Mating Part	Yes
Polarized to PCB	Yes
Shrouded	Fully
Stackable	No
Surface Mount Compatible (SMC)	No
Temperature Range - Operating	-40°C to +105°C
Termination Interface: Style	Through Hole

Electrical

Current - Maximum per Contact	13A
Voltage - Maximum	600V

Solder Process Data

Duration at Max. Process Temperature (seconds)	5
Lead-free Process Capability	Wave Capable (TH only)
Max. Cycles at Max. Process Temperature	1
Process Temperature max. C	240

Material Info


Old Part Number	5566-04B2
-----------------	-----------

Reference - Drawing Numbers

Packaging Specification	PK-5566-001
Product Specification	PS-5556-001
Sales Drawing	SDA-5566-N*2*-*
Test Summary	TS-5556-002

This document was generated on 05/21/2010

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION



NOTES:

1) HOUSING MATERIAL:

"BLANK" - NYLON 6/6, U.L. 94V-2,
COLOR: NATURAL.

210 - NYLON 6/6, U.L. 94V-0,
COLOR: NATURAL.

BL - NYLON 6/6, U.L. 94V-2,
COLOR: DYED BLACK.

2) TERMINAL MATERIAL: BRASS ALLOY 260

3) PART MATES WITH MINI-FIT JR. RECEPTACLE #5557.

4) PACKAGING: SEE CHARTS

5) MOUNTING OPTIONS:

"BLANK" - NO MOUNTING
(SEE SD-5566-NA AND -NB SERIES DWGS.)
2 - PEG MOUNT

6) TERMINAL PLATING:

"BLANK" - .000035/(.00090) MIN. TIN OVER
.000020/(.00050) MIN. COPPER.
*GS - .000030/(.00076) MIN. SELECT GOLD
.000100/(.00254) MIN. SELECT MATTE TIN
OVER .000050/(.00127) MIN. NICKEL OVERALL.
*GS2 - .000015/(.00038) MIN. SELECT GOLD AND
.000100/(.00254) MIN. SELECT MATTE TIN
OVER .000050/(.00127) MIN. NICKEL OVERALL.
S - .000100/(.00254) MIN. TIN
OVER .000050/(.00127) MIN. NICKEL.


*THE PRIMARY SHIPPING CARTON WILL BE LABELED "COMPLIANT TO RoHS
DIRECTIVE 2002/95/EC AND ELV ANNEX II OF DIRECTIVE 2000/53/EC."
*CARTONS WITHOUT THIS LABEL MAY CONTAIN PRODUCT WITH TIN-LEAD PLATING.

7) PRODUCT SPECIFICATION AND PROCESSING PARAMETERS: SEE PS-5556-001

8) ANTI-SHINGLING RIB MAY OR MAY NOT APPEAR ON HOUSINGS.

9) CONNECTORS ARE NOT TO BE MATED OR UNMATED WHILE CIRCUITS ARE LIVE.

10) PARTS ARE NOT DESIGNED FOR CURRENT SHARING.



RECOMMENDED HOLE LAYOUT FOR .070/(1.78) MAX. THICK P. C. BOARD

VIEWED FROM COMPONENT SIDE

LEGEND:

5566 - N * * * * *

BASE NUMBER

CIRCUIT SIZE

ASSEMBLY TYPE
A - W/O DRAIN HOLES
B - WITH DRAIN HOLES

MOUNTING OPTION
(SEE NOTE 5.)

PLATING
(SEE NOTE 6.)

HOUSING MAT'L.
(SEE NOTE 1.)

PACKAGING
BLANK = TRAY
I = TUBE

4	R2
3	R2
2	R2
1	R2
SHT.	REV.

REVISED NOTES 8 EC NO: UCP2009-1336 DRAWN: JLOSTEMEIER 2008/11/24 CHKD: JEBEL 2008/11/24 APPR: FSMITH 2008/11/24	DESCRIPTION REV	QUALITY SYMBOLS ▽=0 ▽=0	GENERAL TOLERANCES (UNLESS SPECIFIED) mm INCH 4 PLACES ± --- ± --- 3 PLACES ± --- ± .015 2 PLACES ± 0.38 ± .015 1 PLACE ± 0.38 ± --- ANGULAR ± 1/2°	DIMENSION STYLE IN/MM DRAWN BY DATE RJF 8/19/87 CHECKED BY DATE GT 8/19/87 APPROVED BY DATE RAS 8/19/87	SCALE 1:1	DESIGN UNITS METRIC	THIRD ANGLE PROJECTION	TITLE MINI-FIT JR. VERTICAL HEADER ASSEMBLIES WITH MOUNTING PEGS MOLEX INCORPORATED	DOCUMENT NO. SDA-5566-N*2*-*	SHEET NO. 1 OF 4

	13	12	11	10	9	8	7	6	5	4	3	2	1			
J	PLATING:		35 M.I. TIN		PLATING:		35 M.I. TIN		PLATING:		30 M.I. GOLD		PLATING:		30 M.I. GOLD	
	DRAIN HOLES:		WITHOUT DRAIN HOLES		DRAIN HOLES:		WITHOUT DRAIN HOLES		DRAIN HOLES:		WITHOUT DRAIN HOLES		DRAIN HOLES:		WITHOUT DRAIN HOLES	
	MTG. OPTION:		WITH PEGS		MTG. OPTION:		WITH PEGS		MTG. OPTION:		WITH PEGS		MTG. OPTION:		WITH PEGS	
	HOUSING MAT'L:		NYLON 6/6 94V-2 NATURAL		HOUSING MAT'L:		NYLON 6/6 94V-0 NATURAL		HOUSING MAT'L:		NYLON 6/6 94V-2 NATURAL		HOUSING MAT'L:		NYLON 6/6 94V-0 NATURAL	
	PACKAGING:		TRAY		PACKAGING:		TRAY		PACKAGING:		TRAY		PACKAGING:		TRAY	
I	PART NO.	ENG NO.	CKTS		PART NO.	ENG NO.	CKTS		PART NO.	ENG NO.	CKTS		PART NO.	ENG NO.	CKTS	
	39-29-9023	5566 -02A2	2		39-29-9027	5566 -02A2-210	2		39-29-9025	5566 -02A2GS	2		39-29-9029	5566 -02A2GS-210	2	
	39-29-9043	5566 -04A2	4		39-29-9047	5566 -04A2-210	4		39-29-9045	5566 -04A2GS	4		39-29-9049	5566 -04A2GS-210	4	
	39-29-9063	5566 -06A2	6		39-29-9067	5566 -06A2-210	6		39-29-9065	5566 -06A2GS	6		39-29-9069	5566 -06A2GS-210	6	
	39-29-9083	5566 -08A2	8		39-29-9087	5566 -08A2-210	8		39-29-9085	5566 -08A2GS	8		39-29-9089	5566 -08A2GS-210	8	
H	39-29-9103	5566 -10A2	10		39-29-9107	5566 -10A2-210	10		39-29-9105	5566 -10A2GS	10		39-29-9109	5566 -10A2GS-210	10	
	39-29-9123	5566 -12A2	12		39-29-9127	5566 -12A2-210	12		39-29-9125	5566 -12A2GS	12		39-29-9129	5566 -12A2GS-210	12	
	39-29-9143	5566 -14A2	14		39-29-9147	5566 -14A2-210	14		39-29-9145	5566 -14A2GS	14		39-29-9149	5566 -14A2GS-210	14	
	39-29-9163	5566 -16A2	16		39-29-9167	5566 -16A2-210	16		39-29-9165	5566 -16A2GS	16		39-29-9169	5566 -16A2GS-210	16	
	39-29-9183	5566 -18A2	18		39-29-9187	5566 -18A2-210	18		39-29-9185	5566 -18A2GS	18		39-29-9189	5566 -18A2GS-210	18	
	39-29-9203	5566 -20A2	20		39-29-9207	5566 -20A2-210	20		39-29-9205	5566 -20A2GS	20		39-29-9209	5566 -20A2GS-210	20	
	39-29-9223	5566 -22A2	22		39-29-9227	5566 -22A2-210	22		39-29-9225	5566 -22A2GS	22		39-29-9229	5566 -22A2GS-210	22	
	39-29-9243	5566 -24A2	24		39-29-9247	5566 -24A2-210	24		39-29-9245	5566 -24A2GS	24		39-29-9249	5566 -24A2GS-210	24	
		-				-				-				-		
		-				-				-				-		
G	PLATING:		35 M.I. TIN		PLATING:		35 M.I. TIN		PLATING:		30 M.I. GOLD		PLATING:		30 M.I. GOLD	
	DRAIN HOLES:		WITH DRAIN HOLES		DRAIN HOLES:		WITH DRAIN HOLES		DRAIN HOLES:		WITH DRAIN HOLES		DRAIN HOLES:		WITH DRAIN HOLES	
	MTG. OPTION:		WITH PEGS		MTG. OPTION:		WITH PEGS		MTG. OPTION:		WITH PEGS		MTG. OPTION:		WITH PEGS	
	HOUSING MAT'L:		NYLON 6/6 94V-2 NATURAL		HOUSING MAT'L:		NYLON 6/6 94V-0 NATURAL		HOUSING MAT'L:		NYLON 6/6 94V-2 NATURAL		HOUSING MAT'L:		NYLON 6/6 94V-0 NATURAL	
	PACKAGING:		TRAY		PACKAGING:		TRAY		PACKAGING:		TRAY		PACKAGING:		TRAY	
F	PART NO.	ENG NO.	CKTS		PART NO.	ENG NO.	CKTS		PART NO.	ENG NO.	CKTS		PART NO.	ENG NO.	CKTS	
	39-29-9022	5566 -02B2	2		39-29-9026	5566 -02B2-210	2		39-29-9024	5566 -02B2GS	2		39-28-9028	5566 -02B2GS-210	2	
	39-29-9042	5566 -04B2	4		39-29-9046	5566 -04B2-210	4		39-29-9044	5566 -04B2GS	4		39-28-9048	5566 -04B2GS-210	4	
	39-29-9062	5566 -06B2	6		39-29-9066	5566 -06B2-210	6		39-29-9064	5566 -06B2GS	6		39-28-9068	5566 -06B2GS-210	6	
	39-29-9082	5566 -08B2	8		39-29-9086	5566 -08B2-210	8		39-29-9084	5566 -08B2GS	8		39-28-9088	5566 -08B2GS-210	8	
E	39-29-9102	5566 -10B2	10		39-29-9106	5566 -10B2-210	10		39-29-9104	5566 -10B2GS	10		39-28-9108	5566 -10B2GS-210	10	
	39-29-9122	5566 -12B2	12		39-29-9126	5566 -12B2-210	12		39-29-9124	5566 -12B2GS	12		39-28-9128	5566 -12B2GS-210	12	
	39-29-9142	5566 -14B2	14		39-29-9146	5566 -14B2-210	14		39-29-9144	5566 -14B2GS	14		39-28-9148	5566 -14B2GS-210	14	
	39-29-9162	5566 -16B2	16		39-29-9166	5566 -16B2-210	16		39-29-9164	5566 -16B2GS	16		39-28-9168	5566 -16B2GS-210	16	
	39-29-9182	5566 -18B2	18		39-29-9186	5566 -18B2-210	18		39-29-9184	5566 -18B2GS	18		39-28-9188	5566 -18B2GS-210	18	
	39-29-9202	5566 -20B2	20		39-29-9206	5566 -20B2-210	20		39-29-9204	5566 -20B2GS	20		39-28-9208	5566 -20B2GS-210	20	
	39-29-9222	5566 -22B2	22		39-29-9226	5566 -22B2-210	22		39-29-9224	5566 -22B2GS	22		39-28-9228	5566 -22B2GS-210	22	
	39-29-9242	5566 -24B2	24		39-29-9246	5566 -24B2-210	24		39-29-9244	5566 -24B2GS	24		39-28-9248	5566 -24B2GS-210	24	
		-				-				-				-		
		-				-				-				-		
D																
C																
B																
A																

	13	12	11	10	9	8	7	6	5	4	3	2	1																														
J	PLATING:		100 M.I. TIN		PLATING:		100 M.I. TIN		PLATING:		15 M.I. SELECT GOLD		PLATING:		15 M.I. SELECT GOLD																												
	DRAIN HOLES:		WITHOUT DRAIN HOLES		DRAIN HOLES:		WITHOUT DRAIN HOLES		DRAIN HOLES:		WITHOUT DRAIN HOLES		DRAIN HOLES:		WITHOUT DRAIN HOLES																												
	MTG. OPTION:		WITH PEGS		MTG. OPTION:		WITH PEGS		MTG. OPTION:		WITH PEGS		MTG. OPTION:		WITH PEGS																												
	HOUSING MAT'L:		NYLON 6/6 94V-2 NATURAL		HOUSING MAT'L:		NYLON 6/6 94V-0 NATURAL		HOUSING MAT'L:		NYLON 6/6 94V-2 NATURAL		HOUSING MAT'L:		NYLON 6/6 94V-0 NATURAL																												
	PACKAGING:		TRAY		PACKAGING:		TRAY		PACKAGING:		TRAY		PACKAGING:		TRAY																												
I	PART NO.	ENG NO.	CKTS		PART NO.	ENG NO.	CKTS		PART NO.	ENG NO.	CKTS		PART NO.	ENG NO.	CKTS																												
	39-30-6025	5566 -02A2S	2		39-30-6026	5566 -02A2S-2IO	2		39-30-0026	5566 -02A2GS2	2		39-30-0027	5566 -02A2GS2-2IO	2																												
	39-30-6045	5566 -04A2S	4		39-30-6046	5566 -04A2S-2IO	4		39-30-0046	5566 -04A2GS2	4		39-30-0047	5566 -04A2GS2-2IO	4																												
	39-30-6065	5566 -06A2S	6		39-30-6066	5566 -06A2S-2IO	6		39-30-0066	5566 -06A2GS2	6		39-30-0067	5566 -06A2GS2-2IO	6																												
	39-30-6085	5566 -08A2S	8		39-30-6086	5566 -08A2S-2IO	8		39-30-0086	5566 -08A2GS2	8		39-30-0087	5566 -08A2GS2-2IO	8																												
	39-30-6105	5566 -10A2S	10		39-30-6106	5566 -10A2S-2IO	10		39-30-0106	5566 -10A2GS2	10		39-30-0107	5566 -10A2GS2-2IO	10																												
	39-30-6125	5566 -12A2S	12		39-30-6126	5566 -12A2S-2IO	12		39-30-0126	5566 -12A2GS2	12		39-30-0127	5566 -12A2GS2-2IO	12																												
H	39-30-6145	5566 -14A2S	14		39-30-6146	5566 -14A2S-2IO	14		39-30-0146	5566 -14A2GS2	14		39-30-0147	5566 -14A2GS2-2IO	14																												
	39-30-6165	5566 -16A2S	16		39-30-6166	5566 -16A2S-2IO	16		39-30-0166	5566 -16A2GS2	16		39-30-0167	5566 -16A2GS2-2IO	16																												
	39-30-6185	5566 -18A2S	18		39-30-6186	5566 -18A2S-2IO	18		39-30-0186	5566 -18A2GS2	18		39-30-0187	5566 -18A2GS2-2IO	18																												
	39-30-6205	5566 -20A2S	20		39-30-6206	5566 -20A2S-2IO	20		39-30-0206	5566 -20A2GS2	20		39-30-0207	5566 -20A2GS2-2IO	20																												
	39-30-6225	5566 -22A2S	22		39-30-6226	5566 -22A2S-2IO	22		39-30-0226	5566 -22A2GS2	22		39-30-0227	5566 -22A2GS2-2IO	22																												
	39-30-6245	5566 -24A2S	24		39-30-6246	5566 -24A2S-2IO	24		39-30-0246	5566 -24A2GS2	24		39-30-0247	5566 -24A2GS2-2IO	24																												
		-				-				-				-																													
		-				-				-				-																													
G	PLATING:		100 M.I. TIN		PLATING:		100 M.I. TIN		PLATING:		15 M.I. SELECT GOLD		PLATING:		15 M.I. SELECT GOLD																												
	DRAIN HOLES:		WITH DRAIN HOLES		DRAIN HOLES:		WITH DRAIN HOLES		DRAIN HOLES:		WITH DRAIN HOLES		DRAIN HOLES:		WITH DRAIN HOLES																												
	MTG. OPTION:		WITH PEGS		MTG. OPTION:		WITH PEGS		MTG. OPTION:		WITH PEGS		MTG. OPTION:		WITH PEGS																												
	HOUSING MAT'L:		NYLON 6/6 94V-2 NATURAL		HOUSING MAT'L:		NYLON 6/6 94V-0 NATURAL		HOUSING MAT'L:		NYLON 6/6 94V-2 NATURAL		HOUSING MAT'L:		NYLON 6/6 94V-0 NATURAL																												
	PACKAGING:		TRAY		PACKAGING:		TRAY		PACKAGING:		TRAY		PACKAGING:		TRAY																												
F	PART NO.	ENG NO.	CKTS		PART NO.	ENG NO.	CKTS		PART NO.	ENG NO.	CKTS		PART NO.	ENG NO.	CKTS																												
	39-30-6027	5566 -02B2S	2		39-30-6028	5566 -02B2S-2IO	2		39-30-0028	5566 -02B2GS2	2		39-30-0029	5566 -02B2GS2-2IO	2																												
	39-30-6047	5566 -04B2S	4		39-30-6048	5566 -04B2S-2IO	4		39-30-0048	5566 -04B2GS2	4		39-30-0049	5566 -04B2GS2-2IO	4																												
	39-30-6067	5566 -06B2S	6		39-30-6068	5566 -06B2S-2IO	6		39-30-0068	5566 -06B2GS2	6		39-30-0069	5566 -06B2GS2-2IO	6																												
	39-30-6087	5566 -08B2S	8		39-30-6088	5566 -08B2S-2IO	8		39-30-0088	5566 -08B2GS2	8		39-30-0089	5566 -08B2GS2-2IO	8																												
	39-30-6107	5566 -10B2S	10		39-30-6108	5566 -10B2S-2IO	10		39-30-0108	5566 -10B2GS2	10		39-30-0109	5566 -10B2GS2-2IO	10																												
E	39-30-6127	5566 -12B2S	12		39-30-6128	5566 -12B2S-2IO	12		39-30-0128	5566 -12B2GS2	12		39-30-0129	5566 -12B2GS2-2IO	12																												
	39-30-6147	5566 -14B2S	14		39-30-6148	5566 -14B2S-2IO	14		39-30-0148	5566 -14B2GS2	14		39-30-0149	5566 -14B2GS2-2IO	14																												
	39-30-6167	5566 -16B2S	16		39-30-6168	5566 -16B2S-2IO	16		39-30-0168	5566 -16B2GS2	16		39-30-0169	5566 -16B2GS2-2IO	16																												
	39-30-6187	5566 -18B2S	18		39-30-6188	5566 -18B2S-2IO	18		39-30-0188	5566 -18B2GS2	18		39-30-0189	5566 -18B2GS2-2IO	18																												
	39-30-6207	5566 -20B2S	20		39-30-6208	5566 -20B2S-2IO	20		39-30-0208	5566 -20B2GS2	20		39-30-0209	5566 -20B2GS2-2IO	20																												
	39-30-6227	5566 -22B2S	22		39-30-6228	5566 -22B2S-2IO	22		39-30-0228	5566 -22B2GS2	22		39-30-0229	5566 -22B2GS2-2IO	22																												
	39-30-6247	5566 -24B2S	24		39-30-6248	5566 -24B2S-2IO	24		39-30-0248	5566 -24B2GS2	24		39-30-0249	5566 -24B2GS2-2IO	24																												
D		-				-				-				-																													
		-				-				-				-																													
C																																											
B																																											
A																																											
REV. PACKAGING EC NO: UCP2009-1336 DRWN:JKLOSTEMEIER 2008/11/24 CHKD:JBELL 2008/11/24 APPR:FSMITH 2008/11/24 REV DESCRIPTION QUALITY SYMBOLS ▽=0 ▽=0 GENERAL TOLERANCES (UNLESS SPECIFIED) <table><tr><td></td><td>mm</td><td>INCH</td></tr><tr><td>4 PLACES</td><td>± ---</td><td>± ---</td></tr><tr><td>3 PLACES</td><td>± ---</td><td>± .015</td></tr><tr><td>2 PLACES</td><td>± 0.38</td><td>± .015</td></tr><tr><td>1 PLACE</td><td>± 0.38</td><td>± ---</td></tr></table> ANGULAR ±1/2° DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS DIMENSION STYLE IN/MM <table><tr><td>DRAWN BY</td><td>DATE</td></tr><tr><td>LEM</td><td>2/17/99</td></tr><tr><td>CHECKED BY</td><td>DATE</td></tr><tr><td>MAB</td><td>2/17/99</td></tr><tr><td>APPROVED BY</td><td>DATE</td></tr><tr><td>RRE</td><td>2/17/99</td></tr></table> MATERIAL NO. SEE CHART SIZE C SCALE 1:1 DESIGN UNITS METRIC THIRD ANGLE PROJECTION TITLE MINI-FIT JR VERT. HEADER ASSEMBLIES WITH MOUNTING PEGS MOLEX MOLEX INCORPORATED DOCUMENT NO. SDA-5566-N*2*-* SHEET NO. 3 1b_frame_C.P_ME.T Rev. D 2004/04/02 12 11 10 9 8 7 6 5 4 3 2 1																		mm	INCH	4 PLACES	± ---	± ---	3 PLACES	± ---	± .015	2 PLACES	± 0.38	± .015	1 PLACE	± 0.38	± ---	DRAWN BY	DATE	LEM	2/17/99	CHECKED BY	DATE	MAB	2/17/99	APPROVED BY	DATE	RRE	2/17/99
	mm	INCH																																									
4 PLACES	± ---	± ---																																									
3 PLACES	± ---	± .015																																									
2 PLACES	± 0.38	± .015																																									
1 PLACE	± 0.38	± ---																																									
DRAWN BY	DATE																																										
LEM	2/17/99																																										
CHECKED BY	DATE																																										
MAB	2/17/99																																										
APPROVED BY	DATE																																										
RRE	2/17/99																																										

	13	12	11	10	9	8	7	6	5	4	3	2	1																											
J	PLATING:		35 M.I. TIN		PLATING:		35 M.I. TIN		PLATING:		PLATING:																													
	DRAIN HOLES:		WITHOUT DRAIN HOLES		DRAIN HOLES:		WITHOUT DRAIN HOLES		DRAIN HOLES:		DRAIN HOLES:																													
	MTG. OPTION:		WITH PEGS		MTG. OPTION:		WITH PEGS		MTG. OPTION:		MTG. OPTION:																													
	HOUSING MAT'L:		NYLON 6/6 94V-2 (BLACK)		HOUSING MAT'L:		94V-2 NATURAL		HOUSING MAT'L:		HOUSING MAT'L:																													
	PACKAGING:		TRAY		PACKAGING:		TUBE		PACKAGING:		PACKAGING:																													
I	PART NO.	ENG NO.	CKTS		PART NO.	ENG NO.	CKTS		PART NO.	ENG NO.	CKTS	PART NO.	ENG NO.	CKTS																										
	39-31-9028	5566 -02A2-BL	2		39-34-8028	5566 -02A2-I	2			-			-																											
	39-31-9048	5566 -04A2-BL	4		39-34-8048	5566 -04A2-I	4			-			-																											
	39-31-9068	5566 -06A2-BL	6		39-34-8068	5566 -06A2-I	6			-			-																											
	39-31-9088	5566 -08A2-BL	8		39-34-8088	5566 -08A2-I	8			-			-																											
	39-31-9108	5566 -10A2-BL	10		39-34-8108	5566 -10A2-I	10			-			-																											
	39-31-9128	5566 -12A2-BL	12		39-34-8128	5566 -12A2-I	12			-			-																											
	39-31-9148	5566 -14A2-BL	14		39-34-8148	5566 -14A2-I	14			-			-																											
	39-31-9168	5566 -16A2-BL	16		39-34-8168	5566 -16A2-I	16			-			-																											
	39-31-9188	5566 -18A2-BL	18		39-34-8188	5566 -18A2-I	18			-			-																											
	39-31-9208	5566 -20A2-BL	20		39-34-8208	5566 -20A2-I	20			-			-																											
	39-31-9228	5566 -22A2-BL	22		39-34-8228	5566 -22A2-I	22			-			-																											
	39-31-9248	5566 -24A2-BL	24		39-34-8248	5566 -24A2-I	24			-			-																											
		-				-				-			-																											
		-				-				-			-																											
G	PLATING:				PLATING:				PLATING:		PLATING:																													
	DRAIN HOLES:				DRAIN HOLES:				DRAIN HOLES:		DRAIN HOLES:																													
	MTG. OPTION:				MTG. OPTION:				MTG. OPTION:		MTG. OPTION:																													
	HOUSING MAT'L:				HOUSING MAT'L:				HOUSING MAT'L:		HOUSING MAT'L:																													
	PACKAGING:				PACKAGING:				PACKAGING:		PACKAGING:																													
F	PART NO.	ENG NO.	CKTS		PART NO.	ENG NO.	CKTS		PART NO.	ENG NO.	CKTS	PART NO.	ENG NO.	CKTS																										
		-				-				-			-																											
		-				-				-			-																											
		-				-				-			-																											
		-				-				-			-																											
		-				-				-			-																											
		-				-				-			-																											
		-				-				-			-																											
		-				-				-			-																											
		-				-				-			-																											
		-				-				-			-																											
		-				-				-			-																											
		-				-				-			-																											
		-				-				-			-																											
D		-				-				-			-																											
		-				-				-			-																											
C																																								
B																																								
A																																								
REV. PACKAGING EC NO: UCP2009-1336 DRWN:JKLOSTENE IER 2008/11/24 CHKD:JBELL 2008/11/24 APPR:FSMITH 2008/11/24 REV DESCRIPTION QUALITY SYMBOLS ▽=0 ▽=0 GENERAL TOLERANCES (UNLESS SPECIFIED) <table><tr><td></td><td>mm</td><td>INCH</td></tr><tr><td>4 PLACES</td><td>± ---</td><td>± ---</td></tr><tr><td>3 PLACES</td><td>± ---</td><td>± .015</td></tr><tr><td>2 PLACES</td><td>± .38</td><td>± .015</td></tr><tr><td>1 PLACE</td><td>± .38</td><td>± ---</td></tr></table> ANGULAR ±1/2° DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS DIMENSION STYLE IN/MM <table><tr><td>DRAWN BY</td><td>DATE</td></tr><tr><td>LEM</td><td>2/17/99</td></tr><tr><td>CHECKED BY</td><td>DATE</td></tr><tr><td>MAB</td><td>2/17/99</td></tr><tr><td>APPROVED BY</td><td>DATE</td></tr><tr><td>RRE</td><td>2/17/99</td></tr></table> MATERIAL NO. SEE CHART SIZE C THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION SCALE 1:1 DESIGN UNITS METRIC THIRD ANGLE PROJECTION TITLE MINI FIT JR. VERT HEADER ASSEMBLIES WITH MOUNTING PEGS DOCUMENT NO. SDA-5566-N*2*-* SHEET NO. 4															mm	INCH	4 PLACES	± ---	± ---	3 PLACES	± ---	± .015	2 PLACES	± .38	± .015	1 PLACE	± .38	± ---	DRAWN BY	DATE	LEM	2/17/99	CHECKED BY	DATE	MAB	2/17/99	APPROVED BY	DATE	RRE	2/17/99
	mm	INCH																																						
4 PLACES	± ---	± ---																																						
3 PLACES	± ---	± .015																																						
2 PLACES	± .38	± .015																																						
1 PLACE	± .38	± ---																																						
DRAWN BY	DATE																																							
LEM	2/17/99																																							
CHECKED BY	DATE																																							
MAB	2/17/99																																							
APPROVED BY	DATE																																							
RRE	2/17/99																																							
tb_frame_C.P_ME.T Rev. D 2004/04/02	12	11	10	9	8	7	6	5	4	3	2	1																												