

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: 0022023073
Status: Active
Overview:
Description: 2.54mm (.100") Vertical, Non-ZIF, Low Profile Receptacle, 7 Circuits

Agency Certification

UL E29179

General

Product Family FFC/FPC Connectors
Series 5229
Overview ffc_fpc_throughhole
Product Name N/A

Physical

Circuits (Loaded) 7
Contact Position N/A
Entry Angle Vertical
Flammability 94V-0
Mated Height (in) 0.256 In
Mated Height (mm) 6.50 mm
Number of Rows 1
Orientation Vertical
PC Tail Length (in) 0.142 In
PC Tail Length (mm) 3.60 mm
PCB Retention None
Packaging Type Tray
Pitch - Mating Interface (in) 0.100 In
Pitch - Mating Interface (mm) 2.54 mm
Polarized to PCB No
Stackable No
Surface Mount Compatible (SMC) No
Temperature Range - Operating -40°C to +105°C
Termination Interface: Style Through Hole
Wire/Cable Type FFC/FPC

Electrical

Current - Maximum per Contact 0.5A, 1A
Voltage - Maximum 200V

Material Info

Old Part Number 5229-07CPB

Reference - Drawing Numbers

Packaging Specification SPK-5229-001
Product Specification PS-5229-001, PS-5229-002, PS-5229-005,
PS-5229-006, PS-5229-007
Sales Drawing SD-5229-NCPB

EU RoHS
ELV and RoHS
Compliant
REACH SVHC
Contains SVHC: No
Halogen-Free
Status

China RoHS






Not Reviewed

Need more information on product environmental compliance?


Email productcompliance@molex.com
For a multiple part number RoHS Certificate of Compliance, [click here](#)

Please visit the [Contact Us](#) section for any non-product compliance questions.

Search Parts in this Series
[5229Series](#)

基板取付穴推奨寸法
RECOMMENDED PC BOARD HOLE DIMENSION

9&10, 18&19	71.12	71.42	66.04	73.44	22-02 - 3273	5229 - 27CPB	27
8&9, 18&19	68.58	68.88	63.5	70.9	- 3263	- 26CPB	26
8&9, 17&18	66.04	66.34	60.96	68.36	- 3253	- 25CPB	25
8&9, 16&17	63.5	63.8	58.42	65.82	- 3243	- 24CPB	24
8&9, 15&16	60.96	61.26	55.88	63.28	- 3233	- 23CPB	23
7&8, 15&16	58.42	58.72	53.34	60.74	- 3223	- 22CPB	22
7&8, 14&15	55.88	56.18	50.8	58.2	- 3213	- 21CPB	21
10&11	53.34	53.64	48.26	55.66	- 3203	- 20CPB	20
9&10	50.8	51.1	45.72	53.12	- 3193	- 19CPB	19
9&10	48.26	48.56	43.18	50.58	- 3183	- 18CPB	18
8&9	45.72	46.02	40.64	48.04	- 3173	- 17CPB	17
8&9	43.18	43.48	38.1	45.5	- 3163	- 16CPB	16
7&8	40.64	40.94	35.56	42.96	- 3153	- 15CPB	15
7&8	38.1	38.4	33.02	40.42	- 3143	- 14CPB	14
6&7	35.56	35.86	30.48	37.88	- 3133	- 13CPB	13
6&7	33.02	33.32	27.94	35.34	- 3123	- 12CPB	12
5&6	30.48	30.78	25.4	32.8	- 3113	- 11CPB	11
—+—	27.94	28.24	22.86	30.26	- 3103	- 10CPB	10
—+—	25.4	25.7	20.32	27.72	- 3093	- 09CPB	9
—+—	22.86	23.16	17.78	25.18	- 3083	- 08CPB	8
—+—	20.32	20.62	15.24	22.64	- 3073	- 07CPB	7
—+—	17.78	18.08	12.7	20.1	- 3063	- 06CPB	6
—+—	15.24	15.54	10.16	17.56	- 3053	- 05CPB	5
—+—	12.7	13	7.62	15.02	- 3043	- 04CPB	4
—+—	10.16	10.46	5.08	12.48	22-02 - 3033	5229 - 03CPB	3
PEDESTAL LOCATION (BETWEEN THE CKTS)	D	C	B	A	EDP.NO.	ENG.NO.	NO. OF CKTS.

適合F.F.C.推奨寸法
APPLICABLE FFC RECOMMENDED DIMENSION

角度	ANGLE	±3°
30°以上	OVER	±0.3
10°以上 30°未満	OVER	±0.25
10°未満	UNDER	±0.2

一般公差	GENERAL TOLERANCES
記号	LTR
変更内容	REVISION RECORD
DR.	CHK.
日付	DATE

H	REVISED (JC2001 - Q774)	N.Y.	S.K.	01/03/14
G	REDRAWN (JC70323)	M.H.	M.F.	06/05/23

材料	MATERIAL
ハウジング: ポリエステル樹脂 (94V-0)	HOUSING: POLYESTER RESIN (94V-0)
ターミナル: 銅メッキ・銅リンめっき	TERMINAL: PHOSPHOR BRONZE, PRE-TINNED PLATING
仕上げ	FINISH
適用電線範囲	WIRE RANGE
被覆外径	INS. RANGE
DRAWN BY: 96/05/23	CHK'D BY: 01/03/14
M. HANAMURA	S. KUNISHI
APP'D BY: 01/03/14	DATE
M. FUKUSHIMA	SCALE 4:1

molex MOLEX-JAPAN CO., LTD.
日本モレックス株式会社

REVISE ONLY ON CAD SYSTEM

TITLE 名称

F.F.C. CONN.
RECEPTACLE HSG ASS'YDWG. NO. SD-5229-NCPB
REV H