

SPECIFICATION SHEET**JFW MODEL 50D-050****DETECTOR**

JFW Industries, Inc.
Phone: 317-887-1340
sales@jfwindustries.com
www.jfwindustries.com

Frequency Range	1-1000 MHz
Impedance	50 Ohms nominal
VSWR	1.2:1 maximum 1-1000 MHz
Flatness	± 0.2 dB
Typical Output Voltage	
(-20 dBm)	0.006 V
(-10 dBm)	0.050 V
(0 dBm)	0.220 V
(+10 dBm)	0.840 V
(+20 dBm)	2.650 V
Output Capacitance	1000 pF nominal
DC Output Polarity	Positive or Negative (customer to specify)
RF Input Power	100 mW maximum
RF Input Connector	BNC, TNC, N or SMA male or female
DC Output Connector	BNC, TNC, N, or SMA female
Operating Temperature Range	-40°C to +85°C
Physical Size	See outline drawing:
	092-5252 (BNC M / BNC F)
	092-5251 (N M / BNC F)
	092-5402 (SMA M / BNC F)
	092-4276 (SMA M / SMA F)

ECR/ECN #	DATE	REV	APPR / DATE	ECR/ECN #	DATE	REV	APPR / DATE
	11/20/2006		CLK 11/20/2006	18130	01/19/2010	C	SMR 01/19/2010
14146	05/02/2007	A	CLK 05/02/2007				
15350	02/11/2008	B	CLK 02/11/2008				