

Silicon NPN Power Transistors


2SC4051

DESCRIPTION

- With TO-220C package
- Switching power transistor

PINNING

PIN	DESCRIPTION
1	Base
2	Collector
3	Emitter

Absolute maximum ratings($T_a=25^\circ\text{C}$)

SYMBOL	PARAMETER	CONDITIONS	VALUE	UNIT
V_{CBO}	Collector-base voltage	Open emitter	600	V
V_{CEO}	Collector-emitter voltage	Open base	450	V
V_{EBO}	Emitter-base voltage	Open collector	7	V
I_C	Collector current		3	A
I_{CM}	Collector current-Peak		6	A
I_B	Base current		1	A
I_{BM}	Base current-Peak		2	A
P_T	Total power dissipation	$T_C=25$	40	W
T_j	Junction temperature		150	
T_{stg}	Storage temperature		-55~150	

THERMAL CHARACTERISTICS

SYMBOL	PARAMETER	MAX	UNIT
$R_{th\ j-C}$	Thermal resistance junction to case	3.12	/W

Silicon NPN Power Transistors

2SC4051

CHARACTERISTICS

Tj=25 unless otherwise specified

SYMBOL	PARAMETER	CONDITIONS	MIN	TYP.	MAX	UNIT
$V_{CEO(SUS)}$	Collector-emitter sustaining voltage	$I_C=0.1A ; I_B=0$	450			V
V_{CEsat}	Collector-emitter saturation voltage	$I_C=1.5A ; I_B=0.3A$			1.0	V
V_{BEsat}	Base-emitter saturation voltage	$I_C=1.5A ; I_B=0.3A$			1.5	V
I_{CBO}	Collector cut-off current	At rated volatge			0.1	mA
I_{CEO}	Collector cut-off current					
I_{EBO}	Emitter cut-off current	At rated volatge			0.1	mA
h_{FE-1}	DC current gain	$I_C=1.5A ; V_{CE}=5V$	10			
h_{FE-2}	DC current gain	$I_C=1mA ; V_{CE}=5V$	5			
f_T	Transition frequency	$I_C=0.3A ; V_{CE}=10V$		20		MHz

Switching times

t_{on}	Turn-on time	$I_C=1.5A ; I_{B1}=0.3A$ $I_{B2}=0.6A , R_L=100\Omega$ $V_{BB2}=4V$			0.5	μs
t_s	Storage time				2.0	μs
t_f	Fall time				0.2	μs

Silicon NPN Power Transistors

2SC4051

PACKAGE OUTLINE




Fig.2 Outline dimensions (unindicated tolerance:±0.10 mm)