

HC-B 10-TFL/PG16G

Order No.: 1771312

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1771312>

Sleeve housing, for single locking latch, height 45 mm, with screw connection, 1x Pg16, straight cable entry

Commercial data

EAN	4017918036041
Pack	10 pcs.
Customs tariff	85389099
Weight/Piece	0.15747 KG
Catalog page information	Page 482 (PC-2009)

Product notes

WEEE/RoHS-compliant since:
02/17/2006



<http://www.download.phoenixcontact.com>
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Technical data

General data

Note	For contact inserts HC-B10, BB18, DD42, M, K8/24
Design	B10
Height	45 mm
Width	43 mm
Length	73 mm
Housing type	Sleeve housings
Locking type	for single locking latch
Type of the screw connection	1x Pg16

Pg screw connection	With
Wrench size, union nut	22 mm
Cable exit	Straight
External cable diameter	7.5 mm ... 15 mm
Degree of protection	IP65
Ambient temperature (operation)	-40 °C ... 125 °C
Housing material	Aluminum, die-cast
Housing surface material	Powder-coated, gray
Cable gland material	Nickel-plated brass
Cable seal material	NBR

Certificates / Approvals




Certification

GOST

Diagrams/Drawings

Dimensioned drawing



Address

PHOENIX CONTACT Inc., USA
586 Fulling Mill Road
Middletown, PA 17057, USA
Phone (800) 888-7388
Fax (717) 944-1625
<http://www.phoenixcon.com>



© 2010 Phoenix Contact
Technical modifications reserved;