

Preliminary "High Frequency Ceramic Solutions"

2 GHz Antenna Small form factor

P/N 2000AT18A0075


Detail Specification: 03/04/09

Page 1 of 3


General Specifications

Part Number	2000AT18A0075
Frequency Range	1965 - 2040 Mhz
Peak Gain	0.3 dBi typ. (XZ-V)
Average Gain	-3 dBi typ. (XZ-V)
Return Loss	9.5 dB min.

Input Power	2 Watts max.
VSWR	2 max
Operating Temperature	-40 to +85°C
Reel Quantity	3000

No.	Function	Terminal Configuration
1	Feeding Point	
2	NC	


Mechanical Dimensions

	In	mm	
L	0.126 ± 0.008	3.20 ± 0.20	
W	0.063 ± 0.008	1.60 ± 0.20	
T	0.051 ± 0.008	1.30 ± 0.20	
a	0.020 ± 0.012	0.50 ± 0.30	

Mounting Considerations

Mount these devices with brown mark facing up. Units: mm

*Line width should be designed to provide 50Ω impedance matching characteristics.



Johanson Technology, Inc. reserves the right to make design changes without notice.
All sales are subject to Johanson Technology, Inc. terms and conditions.



www.johansontechnology.com

4001 Calle Tecate • Camarillo, CA 93012 • TEL 805.389.1166 FAX 805.389.1821

2009 Johanson Technology, Inc. All Rights Reserved

Preliminary "High Frequency Ceramic Solutions"


2 GHz Antenna

P/N 2000AT18A0075

Detail Specification: 03/04/09

Page 2 of 3

Typical Electrical Characteristics (T=25°C)



Johanson Technology, Inc. reserves the right to make design changes without notice.

All sales are subject to Johanson Technology, Inc. terms and conditions.



Preliminary "High Frequency Ceramic Solutions"







2 GHz Antenna

Detail Specification: 03/04/09

P/N 2000AT18A0075

Page 2 of 3

Typical Radiation Patterns



Johanson Technology, Inc. reserves the right to make design changes without notice.
All sales are subject to Johanson Technology, Inc. terms and conditions.

