

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:

0713492035

Status:

Active

Overview:

cgrid_sl_products

Description:

2.54mm (.100") Pitch C-Grid® Header, Surface Mount, Dual Row, Vertical, Shrouded, 6 Circuits, 0.38µm (15µ") Gold (Au) Selective Plating, with Press-fit Plastic Pegs

Documents:


3D Model

Drawing (PDF)

Product Specification PS-71349-001 (PDF)

RoHS Certificate of Compliance (PDF)

General	
Product Family	PCB Headers
Series	71349
Application	Wire-to-Board
Overview	cgrid_sl_products
Product Name	C-Grid®
Physical	
Breakaway	No
Circuits (Loaded)	6
Color - Resin	Black
Durability (mating cycles max)	50
First Mate / Last Break	No
Glow-Wire Compliant	No
Guide to Mating Part	No
Keying to Mating Part	None
Lock to Mating Part	Yes
Material - Metal	Brass, Phosphor Bronze
Material - Plating Mating	Gold
Material - Plating Termination	Tin
Material - Resin	High Temperature Thermoplastic
Number of Rows	2
Orientation	Vertical
PC Tail Length (in)	0.000 In
PC Tail Length (mm)	0.00 mm
PCB Locator	Yes
PCB Retention	Yes
PCB Thickness Recommended (in)	0.000 In
PCB Thickness Recommended (mm)	0.00 mm
Packaging Type	Tube
Pitch - Mating Interface (in)	0.100 In
Pitch - Mating Interface (mm)	2.54 mm
Plating min: Mating (µin)	15
Plating min: Mating (µm)	0.375
Plating min: Termination (µin)	75
Plating min: Termination (µm)	1.875
Polarized to Mating Part	Yes
Shrouded	Fully
Stackable	No
Temperature Range - Operating	-40°C to +105°C
Termination Interface: Style	Surface Mount
Electrical	
Current - Maximum per Contact	3A
Voltage - Maximum	250V



EU RoHS

ELV and RoHS

Compliant

REACH SVHC

Not Reviewed

Halogen-Free

Status

Not Reviewed

China RoHS



Need more information on product environmental compliance?

Email productcompliance@molex.com

For a multiple part number RoHS Certificate of Compliance, [click here](#)

Please visit the [Contact Us](#) section for any non-product compliance questions.

Search Parts in this Series

71349Series

Solder Process Data

Duration at Max. Process Temperature (seconds)	30
Lead-free Process Capability	Reflow Capable (SMT only)
Max. Cycles at Max. Process Temperature	3
Process Temperature max. C	245

Material Info

Reference - Drawing Numbers



Packaging Specification	PK-70873-0018, PK-70873-0019
Product Specification	PS-71349-001
Sales Drawing	SDA-71349-****

This document was generated on 05/31/2010



PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

NOTES:


- 1- MATERIALS:
SHROUDED WAFER: LCP, COLOR: BLACK, 94V-0
PINS: COPPER ALLOY.
- 2- PLATING FINISHES FOR PINS:
TIN: .000150 MINIMUM TIN OVER
.000050 MINIMUM NICKEL.
- 15 GOLD: .000015 MINIMUM GOLD PLATE IN SELECTED AREA AND
.000075 MINIMUM TIN IN SELECTED AREA
OVER .000050 MINIMUM NICKEL OVER-ALL.
- 30 GOLD: .000030 MINIMUM GOLD PLATE IN SELECTED AREA AND
.000075 MINIMUM TIN IN SELECTED AREA
OVER .000050 MINIMUM NICKEL OVER-ALL.
- 3- PRODUCT CONFORMS TO PS-71349-001.
- 4- SEE SHEETS 3 AND 4 FOR PACKAGING DETAILS.
- 5- ROW TO ROW PIN HEIGHT VARIATION MUST NOT EXCEED
.005/(0.13).
- 6- THIS SHOULDER IS .125/(3.18) FOR 6 CIRCUIT ONLY.
.174/(4.42) FOR ALL OTHER CIRCUIT SIZES.
- 7- 20 CIRCUIT SIZE SHOWN FOR ILLUSTRATION PURPOSES.
- 8- PIN SMT TAILS MUST MEET SOLDERABILITY PER
MIL-STD-202, METHOD 208B.
- 9- PIN PUSHOUT FORCE 4 LBS/(17.79N) MINIMUM
IN THE DIRECTION INDICATED.
- 10- PRODUCT MATES TO 70013B (6 TO 50 CKTS).
- 11- PARTS CONFORM TO CLASS B REQUIREMENTS OF
COSMETIC SPECIFICATION PS-45499-002



SECTION J-J



NOTE FOR LEAD FREE CONVERSION:
THE PRIMARY SHIPPING CARTON WILL BE LABELED "COMPLIANT TO RoHS
DIRECTIVE 2002/95/EC AND ELV ANNEX II OF DIRECTIVE 2000/53/EC".
CARTONS WITHOUT THIS LABEL MAY CONTAIN PRODUCT WITH LEAD.



RECOMMENDED P.C. BOARD LAYOUT

ADD 71349-9005
EC NO: UCP2009-1089
DRAWN: KIPPER 2009/02/18
CHKD: SSOUSEK 2009/02/18
APPR: FSM/TH 2009/02/25

QUALITY SYMBOLS
▽=0
▽=0

GENERAL TOLERANCES (UNLESS SPECIFIED)

	mm	INCH
4 PLACES ± ---	± ---	± ---
3 PLACES ± ---	± .005	± .005
2 PLACES ± .13	± .01	± .01
1 PLACE ± 0.25	± ---	± ---

ANGULAR ±1/2°

DRAFT WHERE APPLICABLE
MUST REMAIN
WITHIN DIMENSIONS

DIMENSION STYLE
IN/MM

DRAWN BY DATE
RB 10/26/1992

CHECKED BY DATE
DJB 10/26/1992

APPROVED BY DATE
DJB 10/26/1992

MATERIAL NO.
SEE TABLE

SIZE
C

SCALE
3:1

DESIGN UNITS
INCH

THIRD ANGLE PROJECTION

TITLE
SALES ASSY, WAFER-4 SIDES
SHROUDED, HIGH TEMP, SMT
POLAR SLOTS, .100 GRID

MOLEX INCORPORATED

DOCUMENT NO.
SDA-71349-****

SHEET NO.
1 OF 4

4	I2
3	J1
2	C
1	J1
SHT	REV

[illegible]

13	12	11	10	9	8	7	6	5	4	3	2	1													
WITH PEGS													WITHOUT PEGS												
PLATING		TIN		15 GOLD		30 GOLD		PLATING		TIN		15 GOLD		30 GOLD											
PACKAGING	TUBES PK-70873-0019	TAPE & REEL PK-71349-001	TUBES PK-70873-0019	TAPE & REEL PK-71349-001	TUBES PK-70873-0019	TAPE & REEL PK-71349-001	PACKAGING	TUBES PK-70873-0018	TAPE & REEL PK-71349-001	TUBES PK-70873-0018	TAPE & REEL PK-71349-001	TUBES PK-70873-0018	TAPE & REEL PK-71349-001												
NO. OF CKTS	ASSEMBLY ITEM NO.		ASSEMBLY ITEM NO.		ASSEMBLY ITEM NO.	ASSEMBLY ITEM NO.	NO. OF CKTS	ASSEMBLY ITEM NO.	ASSEMBLY ITEM NO.	ASSEMBLY ITEM NO.	ASSEMBLY ITEM NO.	ASSEMBLY ITEM NO.	ASSEMBLY ITEM NO.												
06	71349-2001		71349-2035		71349-2069		06	71349-1001		71349-1035		71349-1069													
08	71349-2002		71349-2036		71349-2070		08	71349-1002	71349-9002	71349-1036	71349-0036	71349-1070	71349-5036												
10	71349-2003	71349-6003	71349-2037	71349-8037	71349-2071	71349-4071	10	71349-1003	71349-9003	71349-1037	71349-0037	71349-1071	71349-5037												
12	71349-2004		71349-2038		71349-2072		12	71349-1004		71349-1038		71349-1072													
14	71349-2005		71349-2039		71349-2073		14	71349-1005	71349-9005	71349-1039		71349-1073													
16	71349-2006		71349-2040		71349-2074		16	71349-1006		71349-1040	71349-0040	71349-1074													
18	71349-2007		71349-2041		71349-2075		18	71349-1007		71349-1041		71349-1075													
20	71349-2008	71349-6008	71349-2042	71349-8042	71349-2076	71349-4076	20	71349-1008	71349-9008	71349-1042	71349-0042	71349-1076	71349-5042												
22	71349-2009		71349-2043		71349-2077		22	71349-1009		71349-1043		71349-1077													
24	71349-2010		71349-2044		71349-2078		24	71349-1010		71349-1044		71349-1078													
26	71349-2011		71349-2045		71349-2079		26	71349-1011		71349-1045		71349-1079													
28	71349-2012		71349-2046		71349-2080		28	71349-1012		71349-1046		71349-1080													
30	71349-2013		71349-2047		71349-2081		30	71349-1013		71349-1047		71349-1081													
32	71349-2014		71349-2048		71349-2082		32	71349-1014		71349-1048		71349-1082													
34	71349-2015		71349-2049		71349-2083		34	71349-1015		71349-1049		71349-1083													
36	71349-2016		71349-2050		71349-2084		36	71349-1016		71349-1050		71349-1084													
38	71349-2017		71349-2051		71349-2085		38	71349-1017		71349-1051		71349-1085													
40	71349-2018		71349-2052		71349-2086		40	71349-1018		71349-1052		71349-1086													
42	71349-2019		71349-2053		71349-2087		42	71349-1019		71349-1053		71349-1087													
44	71349-2020		71349-2054		71349-2088		44	71349-1020		71349-1054		71349-1088													
46	71349-2021		71349-2055		71349-2089		46	71349-1021		71349-1055		71349-1089													
48	71349-2022		71349-2056		71349-2090		48	71349-1022		71349-1056		71349-1090													
50	71349-2023	71349-6023	71349-2057	71349-8057	71349-2091	71349-4091	50	71349-1023	71349-9023	71349-1057	71349-0057	71349-1091	71349-5057												
52	71349-2024		71349-2058		71349-2092		52	71349-1024		71349-1058		71349-1092													
54	71349-2025		71349-2059		71349-2093		54	71349-1025		71349-1059		71349-1093													
56	71349-2026		71349-2060		71349-2094		56	71349-1026		71349-1060		71349-1094													
58	71349-2027		71349-2061		71349-2095		58	71349-1027		71349-1061		71349-1095													
60	71349-2028		71349-2062		71349-2096		60	71349-1028		71349-1062		71349-1096													
62	71349-2029		71349-2063		71349-2097		62	71349-1029		71349-1063		71349-1097													
64	71349-2030		71349-2064		71349-2098		64	71349-1030		71349-1064		71349-1098													
66	71349-2031		71349-2065		71349-2099		66	71349-1031		71349-1065		71349-1099													
68	71349-2032		71349-2066		71349-2100		68	71349-1032		71349-1066		71349-1100													
70	71349-2033		71349-2067		71349-2101		70	71349-1033		71349-1067		71349-1101													
72	71349-2034		71349-2068		71349-2102		72	71349-1034		71349-1068		71349-1102													

ADD 71349-9005

EC NO: UCP2009-1089

DRWN:KIPPER 2009/02/18

CHKD:SSOUSEK 2009/02/18

APPR:FSMITH 2009/02/25

J1

REV

DESCRIPTION

QUALITY SYMBOLS

▽=0

▽=0

GENERAL TOLERANCES (UNLESS SPECIFIED)

mm

INCH

4 PLACES ± --- ± ---

3 PLACES ± --- ± ---

2 PLACES ± --- ± ---

1 PLACE ± --- ± ---

ANGULAR ±1/2°

DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS

DIMENSION STYLE

IN/MM

DRAWN BY DATE

WGM 06/10/1996

CHECKED BY DATE

DJB 06/10/1996

APPROVED BY DATE

DJB 06/10/1996

MATERIAL NO.

SEE TABLE

SCALE

DESIGN UNITS

INCH

THIRD ANGLE PROJECTION

TITLE

SALES ASSY,4-SIDES SHROUDED, HIGH TEMP, SMT POLAR SLOTS, .150 GRID

MOLEX INCORPORATED

DOCUMENT NO.

SDA-71349-****

SHEET NO.

3 OF 4

b_frame_C_P_ME_T Rev. D 2004/04/02	12	11	10	9	8	7	6	5	4	3	2	1
---------------------------------------	----	----	----	---	---	---	---	---	---	---	---	---