

isc Silicon NPN Power Transistor

2SD907

DESCRIPTION

- High Collector Current
- Good Linearity of h_{FE}
- High Reliability
- Wide Area of Safe Operation

APPLICATIONS



- Audio amplifier
- Series regulators
- General purpose power amplifiers

ABSOLUTE MAXIMUM RATINGS($T_a=25^{\circ}\text{C}$)

SYMBOL	PARAMETER	VALUE	UNIT
V_{CBO}	Collector-Base Voltage	80	V
V_{CEO}	Collector-Emitter Voltage	80	V
V_{EBO}	Emitter-Base voltage	7	V
I_C	Collector Current-Continuous	10	A
I_B	Base Current-Continuous	1.5	A
P_C	Collector Power Dissipation @ $T_C=25^{\circ}\text{C}$	80	W
T_J	Junction Temperature	150	$^{\circ}\text{C}$
T_{stg}	Storage Temperature Range	-55~150	$^{\circ}\text{C}$

THERMAL CHARACTERISTICS

SYMBOL	PARAMETER	MAX	UNIT
$R_{th\ j-c}$	Thermal Resistance,Junction to Case	1.56	$^{\circ}\text{C}/\text{W}$



ISC Silicon NPN Power Transistor

2SD907

ELECTRICAL CHARACTERISTICS

 $T_C=25^{\circ}\text{C}$ unless otherwise specified

SYMBOL	PARAMETER	CONDITIONS	MIN	TYP.	MAX	UNIT
$V_{(BR)CEO}$	Collector-Emitter Breakdown Voltage	$I_C=10\text{mA}; I_B=0$	80			V
$V_{(BR)CBO}$	Collector-Base Breakdown Voltage	$I_C=0.1\text{mA}; I_E=0$	80			V
$V_{(BR)EBO}$	Emitter-Base Breakdown Voltage	$I_E=0.1\text{mA}; I_C=0$	7			V
$V_{CE(sat)}$	Collector-Emitter Saturation Voltage	$I_C=5\text{A}; I_B=0.5\text{A}$			1.2	V
$V_{BE(sat)}$	Base-Emitter Saturation Voltage	$I_C=5\text{A}; I_B=0.5\text{A}$			2.0	V
I_{CBO}	Collector Cutoff Current	$V_{CB}=80\text{V}; I_E=0$			0.1	mA
I_{EBO}	Emitter Cutoff Current	$V_{EB}=7\text{V}; I_C=0$			0.1	mA
h_{FE}	DC Current Gain	$I_C=2\text{A}; V_{CE}=5\text{V}$	40			

Switching times

t_{on}	Turn-on Time	$I_C=5\text{A}; I_{B1}=-I_{B2}=0.5\text{A}$ $R_L=5\Omega; P_W=20\mu\text{S};$ Duty Cycle $\leq 2\%$			1.0	μS
t_{stg}	Storage Time				2.0	μS
t_f	Fall Time				1.0	μS