

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:

0424108506

Status:

Active

Overview:

[modular_plugs_jacks](#)

Description:

Modular Jack, Vertical, 8/8

Documents:

[3D Model](#)

[Drawing \(PDF\)](#)

[Product Specification PS-42410 \(PDF\)](#)

[RoHS Certificate of Compliance \(PDF\)](#)

Agency Certification

CSA	LR19980
UL	E107635

General

Product Family	Modular Jacks/Plugs
Series	42410
Comments	Flush Mount Flangeless 2 PCB Thick
Component Type	PCB Jack
Magnetic	No
Overview	modular_plugs_jacks
Performance Category	3
Power over Ethernet (PoE)	N/A
Product Name	RJ45

Physical

Color - Resin	Black
Durability (mating cycles max)	500
Flammability	94V-0
Inverted / Top Latch	N/A
Lightpipes/LEDs	None
Material - Metal	Phosphor Bronze
Material - Plating Mating	Gold
Material - Plating Termination	Tin
Material - Resin	Polyester
Orientation	Vertical (Top Entry)
PCB Retention	Yes
PCB Thickness Recommended (in)	0.125 In
PCB Thickness Recommended (mm)	3.20 mm
Packaging Type	Tray
Pitch - Mating Interface (in)	0.050 In
Pitch - Mating Interface (mm)	1.27 mm
Plating min: Mating (µin)	50
Plating min: Mating (µm)	1.25
Plating min: Termination (µin)	100
Plating min: Termination (µm)	2.5
Ports	1
Positions / Loaded Contacts	8/8
Surface Mount Compatible (SMC)	No
Temperature Range - Operating	-40°C to +80°C
Termination Interface: Style	Through Hole
Wire/Cable Type	N/A

Electrical

Current - Maximum per Contact	1.5A
Shielded	No
Voltage - Maximum	125V



image - Reference only

Series

EU RoHS

ELV and RoHS

Compliant

REACH SVHC

Contains SVHC: No

Halogen-Free

Status

Not Reviewed

China RoHS



Need more information on product environmental compliance?

Email productcompliance@molex.com

For a multiple part number RoHS Certificate of Compliance, [click here](#)

Please visit the [Contact Us](#) section for any non-product compliance questions.

Search Parts in this Series

[42410Series](#)

Mates With

FCC 68 Plugs

Solder Process Data

Duration at Max. Process Temperature (seconds)	5
Lead-free Process Capability	Wave Capable (TH only)
Max. Cycles at Max. Process Temperature	1
Process Temperature max. C	235

Material Info

Reference - Drawing Numbers

Packaging Specification	PK-42410-492
Product Specification	PS-42410
Sales Drawing	SDA-42410-****
Test Summary	TS-42878-001

This document was generated on 06/07/2010

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

20

19

18

17

16

15

14

13

12

11

10

9

42410

8

7

6

5

4

3

2



1

NOTES:


- 1) MATERIALS: HOUSING PARTS ARE MADE OF POLYESTER, RATED U.L. 94 V-0, COLOR IS BLACK; TERMINALS ARE .015/(0.38) THICK PHOSPHOR BRONZE.
- 2) TERMINAL PLATING OPTIONS PER ES-88-***:
 - A - SELECT GOLD IN CONTACT AREA; 50 MICROINCHES MIN.,
 - *SELECT TIN IN PC TAIL AREA; 100 MICROINCHES MIN.,
 - WITH OVERALL NICKEL UNDERPLATE; 50 MICROINCHES MIN.
 - *THE PRIMARY SHIPPING CARTON WILL BE LABELED "COMPLIANT TO RoHS DIRECTIVE 2002/95/EC AND ELV ANNEX II OF DIRECTIVE 2000/53/EC". CARTONS WITHOUT THIS LABEL MAY CONTAIN PRODUCT WITH TIN-LEAD IN THE PC TAIL.
- 3) THESE MODULAR JACKS MEET THE PERFORMANCE REQUIREMENTS OF MOLEX PRODUCT SPECIFICATION PS-42410.
- 4) CONNECTORS ARE TO BE PACKED IN THERMOFORMED TRAYS, PER PACKAGING SPECIFICATION PK-42410-492.
- 5) ALL JACKS ARE DESIGNED TO BE USED WITH .062/(1.57) OR .125/(3.18) THICK P.C. BOARDS.
- 6) ALL JACKS CONFORM TO AND ACCEPT PLUGS WHICH CONFORM TO FCC RULES AND REGULATIONS PART 68, SUBPART F, WHEN PLATED WITH 50 MICROINCHES GOLD.
- 7) ALL JACKS MUST BE CAPABLE OF FITTING INTO MOLEX GAGE G-42410 (CONNECTOR SIZE 4).
- 8) SEE SHEETS 1 & 4 FOR CONNECTOR SIZE 4.
- 9) SEE SHEETS 2 & 4 FOR CONNECTOR SIZE 6.
- 10) SEE SHEET 4 FOR ASSEMBLY ITEM NUMBERS.
- 11) THIS MODULAR JACK ASSEMBLY IS ALSO AVAILABLE IN A UL 94V-0 RATED, GLASS-FILLED NYLON. (SEE MOLEX DRAWING SDA-43576)
- 12) ENGRAVED NUMBERS ON HOUSING BODY ARE FOR HOLDING IDENTIFICATION ONLY. THEY ARE NOT INTENDED FOR ASSEMBLY IDENTIFICATION PURPOSES.
- 13) ALL UNTOLERANCED DIMENSIONS ARE SHOWN FOR REFERENCE ONLY.

P.C. BOARD THICKNESS	DIM. "D" (MTG. PEGS)	DIM. "F" (P.C. TAILS)
.062/(1.57)	.128 (3.25)	.120 +.015/- .025 (3.05 +.38/- .63)
.125/(3.18)	.191 (4.85)	.205 +.015/- .025 (5.21 +.38/- .63)




CONNECTOR SIZE	CIRCUIT SIZE	DIM. "G"
8	8	.350 (8.89)
8	6	.250 (6.35)
8	4	.150 (3.81)
8	2	.050 (1.27)



PANEL CUT-OUT FOR CONNECTOR SIZE 8



P.C. BOARD LAYOUT FOR CONNECTOR SIZE 8



SIZE 8 MODULAR JACK LOADED WITH 8 TERMINALS SHOWN ABOVE
(SEE SHEET 4 FOR PART NUMBER AVAILABILITY)

SEE SHEET ONE EC NO. UFP2004-667 DRAWN: SCHMIDT 2004/03/03 CHKD: SCHMIDT 2004/03/03 APPR: F. SMITH 2004/03/03 REV	QUALITY SYMBOLS 0 0	GENERAL TOLERANCES (UNLESS SPECIFIED) 4 PLACES ± .0005 3 PLACES ± .0008 2 PLACES ± .0012 1 PLACE ± .0015 ANGULAR ± 1/2° DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS	SCALE 4:1 DESIGN UNITS INCH DIMENSION STYLE IN/MM	THIRD ANGLE PROJECTION REVISE ON CAD ONLY	ASSEMBLY, VERTICAL MODULAR JACKS (CONNECTOR SIZE 8) MOLEX INCORPORATED MATERIAL NO. (DOCUMENT NO.) SEE SHEET 4 SDA-42410-****	SHEET NO. 3 OF 4

	20	19	18	17	16	15	14	13	12	11	42410	9	8	7	6	5	4	3	2	1	
	SIZE 4 VERTICAL MODJACK ASSEMBLIES																				
	PART CHARACTERISTICS																				
	ASSEMBLY ITEM NUMBER	EXTERNAL CONNECTOR SIZE	NUMBER OF POSITIONS	P.C. BOARD THICKNESS	MOUNTING EARS OPTION	TERMINAL PLATING OPTION															
	42410-4168	4 POS. BODY	4	.062/(1.57)	YES	A															
	42410-4170	↑	↑	.062/(1.57)	NO	A															
	42410-4264	↓	↓	.125/(3.18)	YES	A															
	42410-4266	4 POS. BODY	4	.125/(3.18)	NO	A															
	42410-4312	4 POS. BODY	2	.062/(1.57)	YES	A															
	42410-4314	↑	↑	.062/(1.57)	NO	A															
	42410-4408	↓	↓	.125/(3.18)	YES	A															
	42410-4410	4 POS. BODY	2	.125/(3.18)	NO	A															
	SIZE 6 VERTICAL MODJACK ASSEMBLIES																				
	PART CHARACTERISTICS																				
	ASSEMBLY ITEM NUMBER	EXTERNAL CONNECTOR SIZE	NUMBER OF POSITIONS	P.C. BOARD THICKNESS	MOUNTING EARS OPTION	TERMINAL PLATING OPTION															
	42410-6168	6 POS. BODY	6	.062/(1.57)	YES	A															
	42410-6170	↑	↑	.062/(1.57)	NO	A															
	42410-6264	↓	↓	.125/(3.18)	YES	A															
	42410-6266	6 POS. BODY	6	.125/(3.18)	NO	A															
	42410-6312	6 POS. BODY	4	.062/(1.57)	YES	A															
	42410-6314	↑	↑	.062/(1.57)	NO	A															
	42410-6320			.062/(1.57)	YES	B															
	42410-6408	↓	↓	.125/(3.18)	YES	A															
	42410-6410	6 POS. BODY	4	.125/(3.18)	NO	A															
	42410-6456	6 POS. BODY	2	.062/(1.57)	YES	A															
	42410-6458	↑	↑	.062/(1.57)	NO	A															
	42410-6552	↓	↓	.125/(3.18)	YES	A															
	42410-6554	6 POS. BODY	2	.125/(3.18)	NO	A															
	SIZE 8 VERTICAL MODJACK ASSEMBLIES																				
	PART CHARACTERISTICS																				
	ASSEMBLY ITEM NUMBER	EXTERNAL CONNECTOR SIZE	NUMBER OF POSITIONS	P.C. BOARD THICKNESS	KEYING OPTION	MOUNTING EARS OPTION	TERMINAL PLATING OPTION														
	42410-8312	8 POS. BODY	8	.062/(1.57)	NO	YES	A														
	42410-8314	↑	↑	.062/(1.57)	NO	NO	A														
	42410-8360			.062/(1.57)	YES	YES	A														
	42410-8362			.062/(1.57)	YES	NO	A														
	42410-8504			.125/(3.18)	NO	YES	A														
	42410-8506			.125/(3.18)	NO	NO	A														
	42410-8552	↓	↓	.125/(3.18)	YES	YES	A														
	42410-8554	8 POS. BODY	8	.125/(3.18)	YES	NO	A														
	42410-8600	8 POS. BODY	6	.062/(1.57)	NO	YES	A														
	42410-8602	↑	↑	.062/(1.57)	NO	NO	A														
	42410-8648			.062/(1.57)	YES	YES	A														
	42410-8650			.062/(1.57)	YES	NO	A														
	42410-8792			.125/(3.18)	NO	YES	A														
	42410-8794			.125/(3.18)	NO	NO	A														
	42410-8840	↓	↓	.125/(3.18)	YES	YES	A														
	42410-8842	8 POS. BODY	6	.125/(3.18)	YES	NO	A														
	42410-8888	8 POS. BODY	4	.062/(1.57)	NO	YES	A														
	42410-8890	↑	↑	.062/(1.57)	NO	NO	A														
	42410-8936			.062/(1.57)	YES	YES	A														
	42410-8938			.062/(1.57)	YES	NO	A														
	42410-9080			.125/(3.18)	NO	YES	A														
	42410-9082			.125/(3.18)	NO	NO	A														
	42410-9128	↓	↓	.125/(3.18)	YES	YES	A														
	42410-9130	8 POS. BODY	4	.125/(3.18)	YES	NO	A														
	42410-9176	8 POS. BODY	2	.062/(1.57)	NO	YES	A														
	42410-9178	↑	↑	.062/(1.57)	NO	NO	A														
	42410-9224			.062/(1.57)	YES	YES	A														
	42410-9226			.062/(1.57)	YES	NO	A														
	42410-9368			.125/(3.18)	NO	YES	A														
	42410-9370			.125/(3.18)	NO	NO	A														
	42410-9416	↓	↓	.125/(3.18)	YES	YES	A														
	42410-9418	8 POS. BODY	2	.125/(3.18)	YES	NO	A														

SEE SHEET ONE
EC NO: UFP2004-1617
DRAWN:LSCHMDT 2004/03/03
CHKD:LSCHMDT 2004/03/03
APPR:FSMITH 2004/03/03
N

QUALITY SYMBOLS
▽ 0
▽ 0
DESCRIPTION
REV

GENERAL TOLERANCES (UNLESS SPECIFIED)
4 PLACES ±
3 PLACES ±
2 PLACES ±
1 PLACE ±
ANGULAR ±1/2°
DRAFT WHERE APPLICABLE
MUST REMAIN WITHIN DIMENSIONS

SCALE

INCH
DIMENSION STYLE
IN/MM
DRAWN BY DATE
GLT 1990/10/12
CHECKED BY DATE
BAP 1990/10/12
APPROVED BY DATE
RAS 1990/10/12

THIRD ANGLE PROJECTION
REVISE ON CAD ONLY
TITLE
ASSEMBLY, VERTICAL MODULAR JACKS
MATERIAL NO. MOLEX INCORPORATED
DOCUMENT NO. SDA-42410-****
SHEET NO. 4 OF 4

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION