


SAW Bandpass Filter 272001B



1. Features

- IF Bandpass Filter
- High Attenuation
- Single-Ended Operation
- DIP Package
- Maximum Storage Temperature Range : -40℃ ~ 85℃
- Electrostatics Sensitive Device (ESD)

2. Package Dimension



Package : D2012

Dimensions shown are nominal in millimeters

Base : Fe(SPCC), Au plating over Ni plated

Cap : Cu & Cr Alloy, Ni Plated

Termination : Kovar, Au Plated

Pin Configuration	
1	Input
5	Output
2, 4	Ground
3, 6	Case ground

 Integrated Technology Future	ITF Co., Ltd. 102-901, Bucheon Technopark 364, Samjeong-Dong, Ojeong-Gu, Bucheon-City, Gyeonggi-Do, Korea 421-809	Part No.	272001B	
		Rev. Date	2004-08-09	
		Rev.	NM4021-CS01	1/5

SAW Bandpass Filter 272001B



3. Specifications

Fo = 70.0 MHz

Terminating source impedance : 50Ω and matching network

Terminating load impedance : 50Ω and matching network

		Minimum	Typical	Maximum
Center Frequency	MHz	69.9	70.0	70.1
Insertion Loss	dB	-	23.5	25.0
1dB Bandwidth	MHz	-	20.3	-
3dB Bandwidth	MHz	20.5	20.6	-
40dB Bandwidth	MHz	-	21.95	22.1
Amplitude Ripple (Fo +/-9.75 MHz)	dB	-	0.8	1.0
Group Delay Variation (Fo +/- 9.75 MHz)	nsec	-	50	100
Absolute Delay	usec	-	2.39	-
Ultimate Rejection	dB	50	55	-
Temperature Coefficient of Frequency	ppm/°C	-	-72	-

Notes :

- 1) All specifications are based on the matching schematic shown below
- 2) All specifications are measured by Agilent Network analyzer and full 2 port calibration at room temperature

All attenuation measurements are measured relative to insertion loss


	ITF Co., Ltd. 102-901, Bucheon Technopark 364, Samjeong-Dong, Ojeong-Gu, Bucheon-City, Gyeonggi-Do, Korea 421-809	Part No.	272001B	
		Rev. Date	2004-08-09	
		Rev.	NM4021-CS01	2/5

SAW Bandpass Filter 272001B



4. Matching Schematic

(Actual matching values may vary due to PCB layout and parasitics)



L1 = 180 nH, L2 = 150 nH
C1 = 39 pF

5. Marking Configuration

ITF¹⁾ 04A001²⁾
272001B³⁾

1) Manufacturer name

2) Lot Number



3) Part Number

	ITF Co., Ltd. 102-901, Bucheon Technopark 364, Samjeong-Dong, Ojeong-Gu, Bucheon-City, Gyeonggi-Do, Korea 421-809	Part No.	272001B	
		Rev. Date	2004-08-09	
		Rev.	NM4021-CS01	3/5

SAW Bandpass Filter 272001B



6. Typical Performance (at +25°C)



ITF Co., Ltd.
 102-901, Bucheon Technopark 364,
 Samjeong-Dong, Ojeong-Gu, Bucheon-City,
 Gyeonggi-Do, Korea 421-809

Part No.

272001B

Rev. Date

2004-08-09

Rev.

NM4021-CS01

4/5

