

Silicon PNP Power Transistors

2SA907/908/909

DESCRIPTION

- With TO-3 package
- Complement to type 2SC1584/1585/1586

APPLICATIONS

- For power switching and general purpose applications

PINNING(see Fig.2)

PIN	DESCRIPTION
1	Base
2	Emitter
3	Collector



Fig.1 simplified outline (TO-3) and symbol

Absolute maximum ratings($T_a =$)

SYMBOL	PARAMETER		CONDITIONS	VALUE	UNIT
V_{CBO}	Collector-base voltage	2SA907	Open emitter	-100	V
		2SA908		-150	
		2SA909		-200	
V_{CEO}	Collector-emitter voltage	2SA907	Open base	-100	V
		2SA908		-150	
		2SA909		-200	
V_{EBO}	Emitter-base voltage		Open collector	-6	V
I_C	Collector current			-15	A
I_B	Base current			-5	A
P_C	Collector power dissipation		$T_C = 25$	150	W
T_j	Junction temperature			150	
T_{stg}	Storage temperature			-65~150	

Silicon PNP Power Transistors

2SA907/908/909

CHARACTERISTICS


T_j=25 unless otherwise specified

SYMBOL	PARAMETER		CONDITIONS	MIN	TYP.	MAX	UNIT
V _{(BR)CEO}	Collector-emitter breakdown voltage	2SA907	I _C =-50mA ; I _B =0	-100			V
		2SA908		-150			
		2SA909		-200			
V _{CEsat}	Collector-emitter saturation voltage		I _C =-10A; I _B =-1A			-3.0	V
I _{CBO}	Collector cut-off current	2SA907	V _{CB} =-100V; I _E =0			-1.0	mA
		2SA908	V _{CB} =-150V; I _E =0				
		2SA909	V _{CB} =-200V; I _E =0				
I _{EBO}	Emitter cut-off current		V _{EB} =-6V; I _C =0			-1.0	mA
h _{FE}	DC current gain		I _C =-5A ; V _{CE} =-4V	30			
f _T	Transition frequency		I _C =-0.5A ; V _{CE} =-12V		10		MHz

Silicon PNP Power Transistors

2SA907/908/909

PACKAGE OUTLINE

Fig.2 outline dimensions (unindicated tolerance: $\pm 0.1\text{mm}$)