

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: [0447690603](#)
Status: **Active**
Overview: [microfit_30](#)
Description: 3.00mm (.118") Pitch Micro-Fit 3.0, BMI™ Receptacle Header, Dual Row, Vertical, with Press-fit Plastic Pegs, 0.8µm (30µ") Gold (Au) Selective, 6 Circuits

Documents:
[3D Model](#)
[Drawing \(PDF\)](#)
[Product Specification PS-44300-001 \(PDF\)](#)
[RoHS Certificate of Compliance \(PDF\)](#)

Agency Certification

CSA	LR19980
TUV	R72081037
UL	E29179

General

Product Family	PCB Receptacles
Series	44769
Application	Board-to-Board, Wire-to-Board
Overview	microfit_30
Product Literature Order No	USA-106
Product Name	Micro-Fit 3.0 BMI™

Physical


Circuits (Loaded)	6
Durability (mating cycles max)	30
Flammability	94V-0
Glow-Wire Compliant	No
Material - Metal	Phosphor Bronze
Material - Plating Mating	Gold
Material - Plating Termination	Tin
Number of Rows	2
Orientation	Vertical
PCB Locator	Yes
PCB Retention	Yes
PCB Thickness Recommended (in)	0.062 In
PCB Thickness Recommended (mm)	1.60 mm
Packaging Type	Tray
Pitch - Mating Interface (in)	0.118 In
Pitch - Mating Interface (mm)	3.00 mm
Plating min: Mating (µin)	30
Plating min: Mating (µm)	0.75
Plating min: Termination (µin)	100
Plating min: Termination (µm)	2.5
Polarized to PCB	Yes
Surface Mount Compatible (SMC)	No
Temperature Range - Operating	-40°C to +105°C
Termination Interface: Style	Through Hole

Electrical

Current - Maximum per Contact	5A
Voltage - Maximum	250V

Solder Process Data

Duration at Max. Process Temperature (seconds)	5
Lead-free Process Capability	Wave Capable (TH only)
Max. Cycles at Max. Process Temperature	1



Series

image - Reference only

EU RoHS
ELV and RoHS
Compliant
REACH SVHC
Not Reviewed
Halogen-Free
Status
Not Reviewed

China RoHS



Need more information on product environmental compliance?

Email productcompliance@molex.com
For a multiple part number RoHS Certificate of Compliance, [click here](#)

Please visit the [Contact Us](#) section for any non-product compliance questions.

Search Parts in this Series
[44769Series](#)

Mates With
[44428](#) , [44300](#) , [44432](#)

Process Temperature max. C260

Material Info

Reference - Drawing Numbers

Packaging SpecificationPK-44769-001



Product SpecificationPS-44300-001, RPS-44300-001

Sales DrawingSD-44769-001

This document was generated on 05/21/2010

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

		44769	
MATERIAL NUMBER	NUMBER OF POSITIONS	PLATING OPTION	
44769-0401	04	A	
44769-0402	04	B	
44769-0403	04	C	
44769-0601	06	A	
44769-0602	06	B	
44769-0603	06	C	
44769-0801	08	A	
44769-0802	08	B	
44769-0803	08	C	
44769-1001	10	A	
44769-1002	10	B	
44769-1003	10	C	
44769-1201	12	A	
44769-1202	12	B	
44769-1203	12	C	
44769-1401	14	A	
44769-1402	14	B	
44769-1403	14	C	
44769-1601	16	A	
44769-1602	16	B	
44769-1603	16	C	
44769-1801	18	A	
44769-1802	18	B	
44769-1803	18	C	
44769-2001	20	A	
44769-2002	20	B	
44769-2003	20	C	
44769-2201	22	A	
44769-2202	22	B	
44769-2203	22	C	
44769-2401	24	A	
44769-2402	24	B	
44769-2403	24	C	



ADD MATING DIMENSIONS EC NO: UCP2005-2881 DRWN: JLOWE 2005/07/07 CHKD: SSOUSEK 2005/07/13 APPR: FSMTH 2005/07/15	DESCRIPTION	QUALITY SYMBOLS	GENERAL TOLERANCES (UNLESS SPECIFIED)		SCALE ---	DESIGN UNITS INCH	THIRD ANGLE PROJECTION	REVISE ON CAD ONLY		
		 -0  -0		mm	INCH	DIMENSION STYLE IN/MM		MICRO-FIT (3.0) BMI VERT. RECEPTACLE ASS'Y 4 - 24 CIRCUIT		
			4 PLACES	± ---	± ---	DRAWN BY	DATE			
			3 PLACES	± ---	± .010	BURLESON	2000/07/13			
			2 PLACES	± 0.25	± .014	CHECKED BY	DATE			
		1 PLACE	± 0.35	± ---	MUELLER	2000/07/13	MOLEX MOLEX INCORPORATED			
		ANGULAR ±1/2°		APPROVED BY	DATE	MATERIAL NO.	DOCUMENT NO.	SHEET NO.		
		DRAFT WHERE APPLICABLE		EDGLEY	2000/07/13	SEE CHART	SD-44769-001	1 OF 1		
E1	REV	MUST REMAIN WITHIN DIMENSIONS		THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION						C