

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:

0850130414

Status:

Active

Overview:

[din_41612](#)

Description:

2.54mm (.100") Pitch DIN 41612 Header, Vertical, Style R Reverse,1µm (40 µ")
Selective Gold (Au), 96 Circuits, Lead free

Documents:	
3D Model	RoHS Certificate of Compliance (PDF)
Drawing (PDF)	

Agency Certification	
CSA	LR19980
UL	E29179
General	
Product Family	Backplane Connectors
Series	85013
Application	Backplane
Component Type	PCB Header
Overview	din_41612
Product Name	IEC 603-2/DIN 41612
Style	R
Physical	
Circuits (Loaded)	96
Circuits (maximum)	96
Circuits Detail	Rows A, B, & C
Durability (mating cycles max)	500
First Mate / Last Break	No
Flammability	94V-0
Guide to Mating Part	No
Keying to Mating Part	Yes
Number of Columns	32
Number of Pairs	Open Pin Field
Number of Rows	3
Orientation	Vertical
PC Tail Length (in)	0.524 In
PC Tail Length (mm)	13.30 mm
PCB Locator	No
PCB Retention	Yes
PCB Thickness Recommended (in)	0.062 In
PCB Thickness Recommended (mm)	1.60 mm
Packaging Type	Tray
Pitch - Mating Interface (in)	0.100 In
Pitch - Mating Interface (mm)	2.54 mm
Pitch - Term. Interface (in)	0.100 In
Pitch - Term. Interface (mm)	2.54 mm
Plating min: Mating (µin)	39
Plating min: Mating (µm)	1
Surface Mount Compatible (SMC)	No
Temperature Range - Operating	-55°C to +125°C
Electrical	
Current - Maximum per Contact	1A
Data Rate	622.0 Mbps
Voltage - Maximum	1000V (RMS)

EU RoHS

ELV and RoHS

Compliant

REACH SVHC

Not Reviewed

Halogen-Free

Status

Not Reviewed

China RoHS



Need more information on product environmental compliance?

Email productcompliance@molex.com
For a multiple part number RoHS Certificate of Compliance, [click here](#)

Please visit the [Contact Us](#) section for any non-product compliance questions.

Search Parts in this Series

[85013Series](#)

Mates With

85042 Backplane Header, [85052](#) Backplane Header

Solder Process Data

Duration at Max. Process Temperature (seconds)	10
Lead-free Process Capability	Wave Capable (TH only)
Process Temperature max. C	260


Material Info

Reference - Drawing Numbers

Sales Drawing	SD-85013-0414, SDA-85013-0001, SDA-85013-0414
---------------	---

This document was generated on 05/17/2010

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION



24-border.DGN REV A
96/06/12 LEVEL 6

VIEW ON MATING SIDE																															
A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	
A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	
A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32


A = 96 STANDARD CONTACTS L = 13.3

MARKING	STANDARD
PERFORMANCE LEVEL	G/O = CONTACT AREA LEVEL 1 / TERMINATION TIN
FLUX PROOF	NO
FIXING CLIP	NO
DIMENSIONS	SD-85013-0001 SHT 1







A	G/O	a1-32 b1-32 c1-32
CONTACT SYMBOL	PERFORMANCE LEVEL	CONTACT POSITION NUMBER

EC NO. I 2004-XXXX DRAWN NS 31/03/04 CHKD G.L. 31/03/04 APPR G.L. 31/03/04 B		QUALITY SYMBOLS MAJOR CRITICAL	GENERAL TOLERANCES* (UNLESS SPECIFIED)		SCALE	DESIGN UNITS	 THIRD ANGLE PROJECTION	DIMENSIONS:			SHT	REV
						 		 		mm ONLY	REVISE ON CAD ONLY	
REV			DESCRIPTION	mm INCH		DRAWN BY & DATE S.S. 26/08/02		TITLE 96 POS MOLEX CONNECTOR ACCORDING DIN 4162 STYLE R CONTACTS ARRANGEMENT				
			4 PLACES $\pm 0.$ $\pm .$		CHECKED BY & DATE G.L. 26/08/02		 MOLEX INCORPORATED					
			3 PLACES $\pm 0.$ $\pm .$		APPROVED BY & DATE G.L. 26/08/02							
			2 PLACES $\pm 0.$ $\pm .$									
			1 PLACE $\pm 0.$ $\pm .$									
			ANGULAR $\pm$		CAD FILENAME S850130414.S01		MATERIAL NO. 85013-0414		DRAWING NO. SD-85013-0414		SHEET NO. 1 OF 1	
			DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION.							SIZE

Section A - B
5:1



View X
5:1



FIRST ANGLE PROJECTION

REVISE ONLY ON CAD SYSTEM

SH. REV.

UNLESS OTHERWISE SPECIFIED
TOLERANCES: ANGULAR $\pm 2^\circ$

	INCH	METRIC
3 PLACE	$\pm .$	$\pm$
2 PLACE	$\pm .$	$\pm$
1 PLACE	$\pm .$	$\pm$

DRAFT WHERE APPLICABLE MUST
REMAIN WITHIN DIMENSIONS

DESIGN DIMENSION ☒ MM
☐ IN.

EQUIVALENT DIMENSION ☐ MM
☐ IN.

IF TWO DIMENSIONS ARE SHOWN THE UPPER IS
THE DESIGN DIMENSION, LOWER IS SECONDARY

DRWG
BY

SIGN

Ca

CHK'D
BY

SIGN

KN

APP'D
BY

SIGN

SCALE

1:1

CAD/CAM PROJECT NAME

85013000
611

TITLE

96 pos. Male connector

acc. DIN 41612 Style R

Dimensions

MOLEX EUROPE

PART NO.

SDA-85013-0001

SIZE

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO
MOLEX INC. & SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION

SHEET NO. DATE

1 OF 95/06/07

SIZE

B

first release
see ECN No. 1887

REVISIONS

LTR

A

[illegible][illegible][illegible][illegible][illegible][illegible][illegible]