



Micro Commercial Components

Micro Commercial Components
20736 Marilla Street Chatsworth
CA 91311
Phone: (818) 701-4933
Fax: (818) 701-4939

2N7002DW

Features

- Case Material: Molded Plastic. UL Flammability Classification Rating 94V-0 and MSL Rating 1
- Power Dissipation: 0.2W(Tamb=25°C)
- Drain Current: 115mA
- Drain-source Voltage: 60V
- Operating Junction Temperature: -55 to +150°C
- Storage Temperature: -55 to +150°C
- Marking: K72


Electrical Characteristics @ 25°C Unless Otherwise Specified

Symbol	Parameter	Min	Typ	Max	Units
$V_{(BR)DSS}$	Drain-Source Breakdown Voltage* ($V_{GS}=0Vdc$, $I_D=10\mu A$)	60	70	---	Vdc
$V_{th(GS)}$	Gate-Threshold Voltage* ($V_{DS}=V_{GS}$, $I_D=250\mu A$)	1.0	1.5	2.0	Vdc
I_{GSS}	Gate-body Leakage* ($V_{DS}=0Vdc$, $V_{GS}=\pm 20Vdc$)	---	---	± 10	nAdc
I_{DSS}	Zero Gate Voltage Drain Current* ($V_{DS}=60Vdc$, $V_{GS}=0Vdc$) ($V_{DS}=60Vdc$, $V_{GS}=0Vdc$, $T_J=125^\circ C$)	---	---	1 500	μA dc
$I_{D(ON)}$	On-state Drain Current* ($V_{DS}=7.5Vdc$, $V_{GS}=10Vdc$)	0.5	1.0	---	A
$r_{DS(on)}$	Drain-Source On-Resistance* ($V_{GS}=5Vdc$, $I_D=50mA$) ($V_{GS}=10Vdc$, $I_D=500mA$)	---	3.2 4.4	7.5 13.5	Ω
g_{FS}	Forward Transconductance* ($V_{DS}=10Vdc$, $I_D=200mA$)	80	---	---	ms
C_{iss}	Input Capacitance	$V_{DS}=25Vdc$, $V_{GS}=0Vdc$ $f=1MHz$	22	50	pF
C_{oss}	Output Capacitance		11	25	
C_{rss}	Reverse Transfer Capacitance		2	5	

Switching


$t_{d(on)}$	Turn-on Time	$V_{DD}=30Vdc$, $V_{GEN}=10Vdc$	---	7	20	ns
$t_{d(off)}$	Turn-off Time	$R_L=150\Omega$, $I_D=200mA$, $R_G=25\Omega$	---	11	20	

* Pulse test, pulse width $\leq 300 \mu s$, duty cycle $\leq 20\%$



N-Channel MOSFET

SOT-363



DIM	INCHES		MM		NOTE
	MIN	MAX	MIN	MAX	
A	.006	.014	0.15	0.35	
B	.045	.053	1.15	1.35	
C	.085	.096	2.15	2.45	
D	.026		0.65Nominal		
G	.047	.055	1.20	1.40	
H	.071	.087	1.80	2.20	
J	---	.004	---	0.10	
K	.035	.043	0.90	1.10	
L	.010	.018	0.26	0.46	
M	.003	.006	0.08	0.15	

Ordering Information

Device	Packing
(Part Number)-TP	Tape&Reel;3Kpcs/Reel

IMPORTANT NOTICE

Micro Commercial Components Corp. reserves the right to make changes without further notice to any product herein to make corrections, modifications , enhancements , improvements , or other changes .
Micro Commercial Components Corp. does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights ,nor the rights of others . The user of products in such applications shall assume all risks of such use and will agree to hold *Micro Commercial Components Corp.* and all the companies whose products are represented on our website, harmless against all damages.

APPLICATIONS DISCLAIMER

Products offer by *Micro Commercial Components Corp.* are not intended for use in Medical, Aerospace or Military Applications.