

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: [0015060040](#)
Status: **Active**
Overview: [minifit_bmi](#)
Description: 4.20mm (.165") Pitch Mini-Fit BMI™ Receptacle Housing, Dual Row with Panel Mount Ears, PA Polyamide Nylon 6/6, UL 94V-2, 4 Circuits

Documents:
[3D Model](#)
[Drawing \(PDF\)](#)

[Product Specification PS-5556-002 \(PDF\)](#)
[RoHS Certificate of Compliance \(PDF\)](#)

Agency Certification

CSA	LR19980
TUV	R72081037
UL	E29179

General

Product Family	Crimp Housings
Series	42474
Comments	Current = 13A max. per circuit when header is mated to a receptacle loaded with 45750 series terminals crimped to 16 AWG wire. . See Molex product specification PS-45750-001 for additional current de-rating information.
MolexKits	Yes
Overview	minifit_bmi
Product Name	Mini-Fit BMI™

Physical

Breakaway	No
Circuits (maximum)	4
Color - Resin	Natural
Flammability	94V-2
Gender	Female
Glow-Wire Compliant	No
Lock to Mating Part	None
Material - Resin	Nylon
Number of Rows	2
Packaging Type	Bag
Panel Mount	Yes
Pitch - Mating Interface (in)	0.165 In
Pitch - Mating Interface (mm)	4.20 mm
Polarized to Mating Part	Yes
Stackable	No
Temperature Range - Operating	-40°C to +105°C

Electrical

Current - Maximum per Contact	13A
-------------------------------	-----

Material Info

Old Part Number	42474-0411
-----------------	------------

Reference - Drawing Numbers

Packaging Specification	PK-42474-001
Product Specification	PS-5556-002
Sales Drawing	SD-42474-****
Test Summary	TS-5556-002




image - Reference only

Series

EU RoHS

ELV and RoHS Compliant
REACH SVHC Contains SVHC: No
Halogen-Free Status

China RoHS



Need more information on product environmental compliance?

Email productcompliance@molex.com
For a multiple part number RoHS Certificate of Compliance, [click here](#)

Please visit the [Contact Us](#) section for any non-product compliance questions.

Search Parts in this Series
[42474Series](#)

Mates With


[42475](#) Mini-Fit BMI™ Plug Housing. [43879](#) MiniFit CPI™ Header. Mini-Fit BMI™ Header [42404](#) , [42440](#). Mini-Fit SMC™ Surface Mount Compatible Header [43810](#) , [44068](#)

Use With



[5556](#) Mini-Fit™ Crimp Terminal

This document was generated on 05/27/2010


PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION




SECTION "A-A"
TERMINAL ORIENTATION




THIS AREA CAN BE
SHARP OR RADIUS



2-8 & 12-24 CIRCUIT HEADER
(SEE SHEET 2 FOR 10 CIRCUIT HEADER DESIGN)



RECOMMENDED PANEL CUT-OUT FOR .050±.012/(1.27±0.30) THICK PANEL
(SEE NOTE 11)



NOTES:


- MATERIAL:
 - *1 = NYLON 6/6, 94V-2, COLOR: NATURAL.
 - *2 = NYLON 6/6, 94V-0, COLOR: NATURAL.
 - *3 = NYLON 6/6, 94V-2, COLOR: BLACK.
 - *4 = NYLON 6/6, 94V-0, COLOR: BLACK.
- FINISH: NOT APPLICABLE.
- PRODUCT SPECIFICATION: PS-5556-002
- PACKAGING: PK-42474-001
- PART MATES WITH MINI-FIT B.M.I. PLUG *42475, AND HEADERS 42404, 42440, 43810, 44068 & 43879.
- PART TO BE USED WITH MOLEX FEMALE TERMINAL *5556.
- THIS CONNECTOR ALLOWS FOR .050/(1.27) MAX. MISALIGNMENT IN ANY DIRECTION.
- THIS DIMENSION TO BE USED FOR ALIGNMENT OF THE MATING CONNECTOR.
- CONNECTOR ASSEMBLIES ARE NOT TO BE MATED OR UNMATED WHILE CIRCUITS ARE LIVE.
- THIS PART IS INTENDED FOR ONE PANEL INSERTION ONLY. REMOVAL AND RE-INSERTION CAN DAMAGE THE MOUNTING SPIRALS.
- PANEL SHOULD BE PUNCHED IN THE DIRECTION OF CONNECTOR INSERTION.
- BOTH SPIRALS SHOULD BE INSERTED INTO THE PANEL AT THE SAME TIME. ROCKING THE PART INTO PLACE MAY CAUSE SPIRAL DAMAGE.
- THIS PART IS NOT INTENDED TO PROVIDE ANY ALIGNMENT OF CUSTOMER COMPONENTS OR MODULES, SUCH AS POWER SUPPLIES AND CHASSIS.
- IF THIS PRODUCT IS STORED IN AN ENVIRONMENT WITH A RELATIVE HUMIDITY OF LESS THAN 50%, MOISTURE MUST BE ADDED. REFER TO TECHNICAL ADVISORY AS-45499-001 FOR INSTRUCTIONS.
- A MAXIMUM TOLERANCE OF .050/(1.27) ALLOWS FOR 2 POINTS OF ELECTRICAL CONTACT. A MAXIMUM TOLERANCE OF .020/(.51) ALLOWS FOR 4 POINTS OF CONTACT.
- WIRES ARE TO BE DRESSED IN SUCH A MANNER TO ALLOW THE TERMINALS TO FLOAT FREELY IN THE POCKET.
- PART CONFORMS TO CLASS 'B' REQUIREMENTS OF COSMETIC SPECIFICATION PS-45499-002.

LEGEND:

42474 - ** * I
BASE NUMBER
CIRCUIT SIZE
(02-24)
MATERIAL
(SEE NOTE 1.)

CORRECTED REF NOTE EC NO: UCP2010-0135 DRAWN: J.BELL CHKD: J.BELL APPR: FSW TH P4	QUALITY SYMBOLS ▽=0 ▽=0	DESCRIPTION	GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION STYLE IN/MM		SCALE 1:1	DESIGN UNITS METRIC	 THIRD ANGLE PROJECTION
			mm	INCH	DRAWN BY GEP	DATE 1989/08/24	TITLE PANEL-MOUNT RECEPTACLE BLIND MATE MINI-FIT JR. SERIES		
			4 PLACES ±.005	±.015	CHECKED BY R.J.F.	DATE 1989/08/24	MOLEX INCORPORATED		
			3 PLACES ±.005	±.015	APPROVED BY RAS	DATE 1989/08/24	SD-42474-****		
			2 PLACES ±.038						
			1 PLACE ±.005						
P4	REV	DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS	ANGULAR ±1/2°		MATERIAL NO. SEE SHEET 2		DOCUMENT NO. SD-42474-****		SHEET NO. 1 OF 2
			SIZE D		THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION				

13		12		11		10		9		8		7		6		5		4		3		2		1									
PART NUMBER		ENG. NUMBER		CKT. SIZE		MATERIAL (SEE NOTE 1.)				PART NUMBER		ENG. NUMBER		CKT. SIZE		MATERIAL (SEE NOTE 1.)				ITEM NUMBER		CKT. SIZE		MATERIAL (SEE NOTE 1.)				ITEM NUMBER		CKT. SIZE		MATERIAL (SEE NOTE 1.)	
J	NOT TOOLED	42474-0211	2	94V-2		NOT TOOLED	42474-0221	2	94V-0		NOT TOOLED	2	94V-2		NOT TOOLED	2	94V-2		NOT TOOLED	2	94V-0												
	I5-06-0040	42474-0411	4	94V-2		I5-06-0041	42474-0421	4	94V-0		42474-0431	4	94V-2		42474-0441	4	94V-2		42474-0441	4	94V-0												
	I5-06-0060	42474-0611	6	94V-2		I5-06-0061	42474-0621	6	94V-0		42474-0631	6	94V-2		42474-0641	6	94V-2		42474-0641	6	94V-0												
	I5-06-0080	42474-0811	8	94V-2		I5-06-0081	42474-0821	8	94V-0		42474-0831	8	94V-2		NOT TOOLED	8	94V-2		NOT TOOLED	8	94V-0												
I	I5-06-0100	42474-1011	10	94V-2		I5-06-0101	42474-1021	10	94V-0		42474-1031	10	94V-2		42474-1041	10	94V-2		42474-1041	10	94V-0												
	NOT TOOLED	42474-1211	12	94V-2		NOT TOOLED	42474-1221	12	94V-0		NOT TOOLED	12	94V-2		NOT TOOLED	12	94V-2		NOT TOOLED	12	94V-0												
	I5-06-0140	42474-1411	14	94V-2		I5-06-0141	42474-1421	14	94V-0		42474-1431	14	94V-2		42474-1441	14	94V-2		42474-1441	14	94V-0												
	NOT TOOLED	42474-1611	16	94V-2		NOT TOOLED	42474-1621	16	94V-0		NOT TOOLED	16	94V-2		NOT TOOLED	16	94V-2		NOT TOOLED	16	94V-0												
H	I5-06-0180	42474-1811	18	94V-2		I5-06-0181	42474-1821	18	94V-0		42474-1831	18	94V-2		42474-1841	18	94V-2		42474-1841	18	94V-0												
	NOT TOOLED	42474-2011	20	94V-2		NOT TOOLED	42474-2021	20	94V-0		NOT TOOLED	20	94V-2		NOT TOOLED	20	94V-2		NOT TOOLED	20	94V-0												
	NOT TOOLED	42474-2211	22	94V-2		NOT TOOLED	42474-2221	22	94V-0		NOT TOOLED	22	94V-2		NOT TOOLED	22	94V-2		NOT TOOLED	22	94V-0												
	I5-06-0240	42474-2411	24	94V-2		I5-06-0241	42474-2421	24	94V-0		42474-2431	24	94V-2		42474-2441	24	94V-2		42474-2441	24	94V-0												



CORRECTED TEXT		QUALITY SYMBOLS		GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION STYLE		SCALE		DESIGN UNITS		THIRD ANGLE PROJECTION	
EC NO: UCP2010-0135		▽=0		mm		IN/MM		1:1		METRIC		TITLE	
DRWN:JBELL		▽=0		4 PLACES ± ---		DRAWN BY		DATE		DATE		PANEL-MOUNT RECEPTACLE	
CHKD:JBELL				3 PLACES ± ---		CHECKED BY		DATE		DATE		BLIND MATE	
APPR:FSMITH				2 PLACES ± ---		MB		1999/03/24		1999/03/24		MINI-FIT JR. SERIES	
				1 PLACE ± ---		APPROVED BY		DATE		DATE		MOLEX INCORPORATED	
						RE		1999/03/24					
						ANGULAR ± 5 °							
						DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		MATERIAL NO.		DOCUMENT NO.		SHEET NO.	
								SEE CHART		SD-42474-****		2 OF 2	
								THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION					