

Silicon PNP Power Transistors

2SB1157

DESCRIPTION


- With TO-3PFa package
- Complement to type 2SD1712
- High f_T
- Wide area of safe operation

APPLICATIONS

- For high power amplifier applications

PINNING

PIN	DESCRIPTION
1	Base
2	Collector
3	Emitter



Absolute maximum ratings($T_a=25^{\circ}\text{C}$)

SYMBOL	PARAMETER	CONDITIONS	VALUE	UNIT
V_{CBO}	Collector-base voltage	Open emitter	-100	V
V_{CEO}	Collector-emitter voltage	Open base	-100	V
V_{EBO}	Emitter-base voltage	Open collector	-5	V
I_C	Collector current		-5	A
I_{CP}	Collector current-peak		-8	A
P_C	Collector power dissipation	$T_C=25^{\circ}\text{C}$	60	W
		$T_a=25^{\circ}\text{C}$	3	
T_j	Junction temperature		150	$^{\circ}\text{C}$
T_{stg}	Storage temperature		-55~150	$^{\circ}\text{C}$

Silicon PNP Power Transistors

2SB1157

CHARACTERISTICS

Tj=25°C unless otherwise specified

SYMBOL	PARAMETER	CONDITIONS	MIN	TYP.	MAX	UNIT
V_{CEsat}	Collector-emitter saturation voltage	$I_C=-3A$; $I_B=-0.3A$			-2.0	V
V_{BE}	Base-emitter on voltage	$I_C=-3A$; $V_{CE}=-5V$			-1.8	V
I_{CBO}	Collector cut-off current	$V_{CB}=-100V$; $I_E=0$			-50	μA
I_{EBO}	Emitter cut-off current	$V_{EB}=-3V$; $I_C=0$			-50	μA
h_{FE-1}	DC current gain	$I_C=-20mA$; $V_{CE}=-5V$	20			
h_{FE-2}	DC current gain	$I_C=-1A$; $V_{CE}=-5V$	60		200	
h_{FE-3}	DC current gain	$I_C=-3A$; $V_{CE}=-5V$	20			
C_{OB}	Output capacitance	$I_E=0$; $V_{CB}=-10V$; $f=1MHz$		130		pF
f_T	Transition frequency	$I_C=-0.5A$; $V_{CE}=-5V$		20		MHz

◆ h_{FE-2} classifications

Q	S	P
60-120	80-160	100-200

Silicon PNP Power Transistors

2SB1157

PACKAGE OUTLINE

