

Distinctive Characteristics

Top or side actuation permits flexible board design.

Compact dimensions and low profile allow high density mounting and close stacking of PC boards.


Crisp actuation positively indicates circuit status.

Double molded thermoset base and thermoplastic housing prevent loosening of terminals due to high soldering temperatures.


Award-winning STC mechanism with benefits unavailable in conventional mechanisms: smoother, positive detent actuation, increased contact stability, and unparalleled logic-level reliability. (Additional STC details in Terms and Acronyms in the Supplement section.)

Insert molded terminals lock out flux, solvents, and other contaminants.

Inch or metric terminal spacing for standard PC board grid (.100" x .100" or 2.0mm x 2.0mm).



Actual Size



General Specifications

Electrical Capacity (Resistive Load)

Power Level (code 2):	0.1A @ 30V DC
Logic Level (code 4):	0.4VA maximum @ 28V AC/DC maximum (Applicable Range 0.1mA ~ 0.1A @ 20mV ~ 28V) Note: Find additional explanation of operating range in Supplement section.

Other Ratings

Contact Resistance:	20 milliohms maximum for power level; 40 milliohms maximum for logic level
Insulation Resistance:	100 megohms minimum @ 500V DC
Dielectric Strength:	500V AC minimum 1 minute minimum
Mechanical Life:	10,000 operations minimum
Electrical Life:	10,000 operations minimum
Contact Timing:	Shorting (make-before-break)
Total Travel:	.079" (2.0mm)

Materials & Finishes

Actuator:	Polyamide
Upper Case:	Polyester for 3-On models; polyacetal for all other models
Lower Case:	Glass fiber reinforced polyester for 3-On models; glass fiber reinforced polybutylene terephthalate (thermoplastic) for other models
Movable Contact:	Phosphor bronze with silver plating (code 2) or phosphor bronze with gold plating (code 4)
Interior Base:	Phenolic resin (thermoset)
Terminals:	Brass with silver plating over copper plating or brass with gold plating

Environmental Data

Operating Temp Range:	-15°C through +60°C (+5°F through +140°F)
Humidity:	90 ~ 95% humidity for 96 hours @ 40°C (104°F)
Vibration:	10 ~ 55Hz with peak-to-peak amplitude of 1.5mm traversing the frequency range & returning in 1 minute; 3 right angled directions for 2 hours
Shock:	50G (490m/s²) acceleration (tested in 6 right angled directions, with 5 shocks in each direction)

PCB Processing

Soldering:	Wave Soldering: See Profile B in Supplement section. Manual Solder: See Profile B in Supplement section.
Cleaning:	Hand clean locally using alcohol based solution.

Standards & Certifications

UL Recognition or CSA Certification:	The SS series devices have not been tested for UL recognition and CSA certification. These switches are designed for use in a low-voltage, low-current circuit. When used as intended in a low-voltage, low-current circuit, the results do not produce hazardous energy.
---	---

TYPICAL SWITCH ORDERING EXAMPLE

SS

12S

D

P

2

POLES & CIRCUITS				
12S	SPDT	ON	NONE	ON
*14M	SP3T	ON	ON	ON
22S	DPDT	ON	NONE	ON

See Poles & Circuits chart below.

* 14M Circuit with silver contacts only.

CONTACT MATERIAL & RATINGS	
2	Silver Rated 0.1A @ 30V DC
*4	Gold Rated 0.4VA maximum @ 28V AC/DC maximum

* Gold not available with SS14M.

TERMINAL SPACING	
B	Metric 2.0mm x 2.0mm
D	Inch .100" x .100"

ACTUATION	
P	Top Actuated
H	Side Actuated

DESCRIPTION FOR TYPICAL ORDERING EXAMPLE

SS12SDP2

Top Actuated

Silver Contacts Rated 0.1A @ 30V DC



SPDT ON-NONE-ON Circuit



Terminals with .100" Spacing

POLES & CIRCUITS								
		Slide Position			Connected Terminals			Throw & Schematics
Pole	Model	Right	Center	Left	Right	Center	Left	
								Note: Terminal numbers are not actually on switch.
SP	SS12S	ON	NONE	ON	2-1	OPEN	2-3	SPDT 
SP	SS14M	ON	ON	ON	3-4	3-2	3-1	SP3T  Make-Before-Break ON-OFF-ON circuit can be created by not connecting terminal 2.
DP	SS22S	ON	NONE	ON	2-1 5-4	OPEN	2-3 5-6	DPDT 



TERMINAL SPACING

B



Metric 2.0mm x 2.0mm with Black Base



On-None-On Single Pole Models





On-None-On Double Pole Models





3-On Models

D



Inch .100" x .100" with Gray Base



On-None-On Single Pole Models



On-None-On Double Pole Models




3-On Models

ACTUATION


P

Top Actuated



H

Side Actuated



CONTACT MATERIALS & RATINGS

2

Silver over Phosphor Bronze

Power Level

0.1A @ 30V DC

4

Gold over Silver/Phosphor Bronze

Logic Level


0.4VA max @ 28V AC/DC max

Complete explanation of operating range in Supplement section.

TYPICAL SWITCH DIMENSIONS

Top Actuated


Single & Double Pole



SS12SDP2

Side Actuated


Single & Double Pole



SS12SDH2

3-On Circuit • Top Actuated


Single Pole



SS14MDP2

3-On Circuit • Side Actuated

Single Pole



SS14MDH2