

Wirewound Resistors, Open Air, Current Sense, Low Value



FEATURES

- Open air design
- Low resistance values for all types of current sensing, voltage division and pulse applications including switching and linear supplies, instrumentation and power amplifiers
- All welded construction
- Solid metal nickel-chrome or copper-nickel alloy resistive element
- Solderable terminations
- Very low inductance
- Lead (Pb)-free version is RoHS compliant



RoHS*
COMPLIANT

STANDARD ELECTRICAL SPECIFICATIONS

MODEL	POWER RATING $P_{70\text{ }^{\circ}\text{C}}$ W	TOLERANCE $\pm \%$	RESISTANCE RANGE Ω
SR1	1.0	1, 5	0.005 - 0.03
SR3	3.0	1, 5	0.005 - 0.05
SR5	5.0	1, 5	0.004 - 0.05

TECHNICAL SPECIFICATIONS

PARAMETER	UNIT	SR Resistor Characteristics
Temperature Coefficient	ppm/ $^{\circ}\text{C}$	0.004 Ω - 0.005 Ω = ± 300 0.0051 Ω - 0.0099 Ω = ± 175 0.01 Ω - 0.05 Ω = ± 100
Operating Temperature Range	$^{\circ}\text{C}$	- 65 to + 275
Maximum Continuous Current	A	$(P/R)^{1/2}$


SAP ORDERING INFORMATION (Part Number 18 digits)

Global Part Numbering Example: SR55L000JE14

S	R	5	5	L	0	0	0	J	E	1	4			
GLOBAL MODEL		VALUE			TOLERANCE			PACKAGING		SPECIAL				
SR1 SR3 SR5		L = m Ω (below 0.01 Ω) R = Decimal 5L000 = 0.005 Ω R0100 = 0.01 Ω			F = $\pm 1.0 \%$ J = $\pm 5.0 \%$ K = $\pm 10 \%$			E14 = Lead (Pb)-free bulk B14 = Tin/lead bulk		(Dash Number) (up to 3 digits) From 1 - 999 as applicable				

* Pb containing terminations are not RoHS compliant, exemptions may apply

DIMENSIONS in inches [millimeters]



MODEL	DIMENSIONS in inches [millimeters]				
	A	B	C	E	F
SR1	0.450 + 0.020 [11.43 + 0.508]	-	0.125 ± 0.030 [3.18 ± 0.762]	0.070 [1.78]	0.040 ± 0.002 [1.02 ± 0.051]
SR3	0.600 + 0.040/- 0.020 [15.24 + 1.020/- 0.508]	1.0 maximum [25.4 maximum]		0.065 + 0.010/- 0.005 [1.65 + 0.254/- 0.127]	
SR5	0.800 + 0.040/- 0.020 [20.32 + 1.020/- 0.508]				


MATERIAL SPECIFICATIONS

Element: Nickel-chrome or copper-nickel alloy depending on resistance value

Terminals: Tinned copper

Encapsulation: None

Marking: None



PERFORMANCE		
TEST	CONDITIONS OF TEST	TEST LIMITS
Temperature Cycling	- 55 °C to + 125 °C, 1000 cycles, 15 min at each extreme	± (1.0 % + 0.0005 Ω) ΔR
Low Temperature Storage	- 65 °C for 24 h	± (0.5 % + 0.0005 Ω) ΔR
High Temperature Exposure	1000 h at + 275 °C	± (2.0 % + 0.0005 Ω) ΔR
Bias Humidity	+ 85 °C, 85 % RH, 10 % bias, 1000 h	± (1.0 % + 0.0005 Ω) ΔR
Mechanical Shock	100 g's for 11 ms, 5 pulses	± (0.2 % + 0.0005 Ω) ΔR
Vibration	Frequency varied 10 to 2000 Hz in 1 min, 3 directions, 12 h	± (0.2 % + 0.0005 Ω) ΔR
Load Life	1000 h at rated power, + 70 °C, 1.5 h "ON", 0.5 h "OFF"	± (2.0 % + 0.0005 Ω) ΔR
Resistance to Solder Heat	+ 260 °C solder, 10 - 12 s dwell, 25 mm/s emergence	± (0.5 % + 0.0005 Ω) ΔR
Moisture Resistance	MIL-STD-202 Method 106, 0 % power, 7a and 7b not required	± (0.5 % + 0.0005 Ω) ΔR



Disclaimer

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.