


Carbon Film Resistors, Special Purpose High Frequency Load (Tubes)



FEATURES

- High stability and excellent high frequency characteristics
- Particularly suited for high frequency applications involving high power, high accuracy RF measurements
- Carbon film construction

APPLICATIONS

High frequency wattmeters for output measurement in radio, TV and radar transmitters, dielectric heating and similar RF generating equipment. Ideal for use as non-reactive radio frequency terminations. Special high power designs with internal water cooling are available. Contact factory.

STANDARD ELECTRICAL SPECIFICATIONS

GLOBAL MODEL	HISTORICAL MODEL	POWER RATING WATTAGE FREE AIR $P_{25^{\circ}\text{C}}$ W	RESISTANCE TOLERANCE %	LINEARITY TOLERANCE %	RESISTANCE RANGE Ω	TEMPERATURE COEFFICIENT ppm/ $^{\circ}\text{C}$
SPW236	SPW-236	120	$\pm 2, \pm 5$	± 10	50 ohm standard. Other values available on special order.	± 200 average ± 250 maximum
SPW227	SPW-227	55	$\pm 2, \pm 5$	± 10		
SPW210	SPW-210	40	$\pm 2, \pm 5$	± 10		
SPW214	SPW-214	10	$\pm 2, \pm 5$	± 10		
SPW212	SPW-212	2	$\pm 2, \pm 5$	± 10		

Cooling:

Approximate increase in wattage when forced air cooling is employed is 3 times wattages shown and for liquid cooling (with heat exchanger) is 60 times wattages shown. The limiting factor insofar as the resistor is concerned is the film temperature. This should not exceed $+200^{\circ}\text{C}$ and for maximum stability should not exceed $+150^{\circ}\text{C}$.

MECHANICAL SPECIFICATIONS

Identification:	Type designation resistance value, tolerance and code date of manufacture are printed on each unit.
Terminations:	All types electroplated copper except SPW-212. The SPW-212 has silver coated termination bands.

MARKING

— DALE
— Model
— Value
— Tolerance
— Date code

GLOBAL PART NUMBER INFORMATION


New Global Part Numbering: SPW21050R00JSL (preferred part numbering format)

S	P	W	2	1	0	5	0	R	0	0	J	S	L			
GLOBAL MODEL			RESISTANCE VALUE			TOLERANCE CODE			PACKAGING			SPECIAL				
(see Standard Electrical Specification Table)			R = Decimal 25R00 = 25Ω 600R0 = 600Ω			G = ± 2% J = ± 5% K = ± 10%			SL = Custom Package			Blank = Standard (Dash Number) (up to 3 digits) From 1-999 as applicable				

Historical Part Number: SPW-210505% (will continue to be accepted)

SPW-210	50	5%	S51
HISTORICAL MODEL	RESISTANCE VALUE	TOLERANCE CODE	PACKAGING

DIMENSIONS in inches [millimeters]




GLOBAL MODEL	A	B	C (O.D.)	D (I.D.)
SPW236	18.0 ± 0.062 [457.20 ± 1.57]	1.75 ± 0.025 [44.45 ± 0.64]	1.0 ± 0.063 [25.40 ± 1.60]	1.25 ± 0.025 [31.75 ± 0.64]
SPW227	12.0 ± 0.062 [304.80 ± 1.57]	1.125 ± 0.025 [28.58 ± 0.64]	0.500 ± 0.032 [12.70 ± 0.81]	0.875 ± 0.020 [22.23 ± 0.51]
SPW210	12.0 ± 0.062 [304.80 ± 1.57]	0.875 ± 0.010 [22.23 ± 0.25]	0.625 ± 0.032 [15.88 ± 0.81]	0.625 ± 0.020 [15.88 ± 0.51]
SPW214	5.0 ± 0.032 [127.0 ± 0.81]	0.562 ± 0.006 [14.27 ± 0.81]	0.500 ± 0.032 [12.70 ± 0.81]	0.375 ± 0.013 [9.53 ± 0.33]
SPW212*	2.0 ± 0.062 [50.80 ± 1.57]	0.250 ± 0.006 [6.35 ± 0.15]	0.250 ± 0.032 [6.35 ± 0.81]	Solid Rod

* Representative types only. Consult factory for special requirements.

Note: 1. C dimension may be varied on special order.

2. Wattage ratings do not allow for mounting hardware.



LOAD TEMPERATURE RISE

[Operation in Free Air]



Disclaimer

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.