



Solid State Devices, Inc.

14701 Firestone Blvd * La Mirada, Ca 90638
Phone: (562) 404-4474 * Fax: (562) 404-1773
ssdi@ssdi-power.com * www.ssdi-power.com

DESIGNER'S DATA SHEET

Part Number / Ordering Information ^{1/}

SPT5006

SPT5008

Screening ^{2/} ___ = Not Screened

TX = TX Level

TXV = TXV Level

S = S Level

Lead Bend ^{3/ 4/} ___ = Straight Leads

UB = Up Bend

DB = Down Bend

Package ^{3/} /61 = TO-61

/3 = TO-3

M = TO-254

S1 = SMD1

SPT5006 and SPT5008 Series

10 AMPS

100 Volts


**High Power - High Speed
NPN Transistors**

Features:


- Radiation Tolerant
- Fast Switching, 100 ns Maximum t_d
- High Frequency, $f_T > 30\text{MHz}$
- BV_{CEO} 80 Volts Minimum
- High Linear Gain, Low Saturation Voltage
- 200°C Operating Temperature
- Designed for Complementary Use With SPT5007 and SPT5009
- TX, TXV, S-Level Screening Available. Consult Factory.

Maximum Ratings	Symbol	Value	Units
Collector – Emitter Voltage	V_{CEO}	80	Volts
Collector – Base Voltage	V_{CBO}	100	Volts
Emitter – Base Voltage	V_{EBO}	6	Volts
Collector Current	I_C	10	Amps
Base Current	I_B	3	Amps
Total Power Dissipation @ $T_C = 50^\circ\text{C}$ Derate Above 50°C	P_D	100 0.667	Watts W/°C
Operating & Storage Temperature	T_J & T_{STG}	-65 to +200	°C
Maximum Thermal Resistance (Junction to Case)	$R_{\theta JC}$	1.5	°C/W


TO-61 (/61)




TO-3(/3)



TO-254 (M)



SMD1 (S1)



NOTE: All specifications are subject to change without notification.
SCD's for these devices should be reviewed by SSDI prior to release.

DATA SHEET #: TR0113A

DOC



Solid State Devices, Inc.

14701 Firestone Blvd * La Mirada, Ca 90638
Phone: (562) 404-4474 * Fax: (562) 404-1773
ssdi@ssdi-power.com * www.ssdi-power.com

SPT5006 and SPT5008 Series

Electrical Characteristics		Symbol	Min	Max	Units
Collector – Emitter Blocking Voltage *	(I _C = 200 mA)	BV _{CEO}	80	—	Volts
Collector – Base Blocking Voltage	(I _C = 200 μA)	BV _{CBO}	100	—	Volts
Emitter – Base Blocking Voltage	(I _E = 200 μA)	BV _{EBO}	6	—	Volts
Collector Cutoff Current	(V _{CE} = 40 V) (V _{CE} = 60 V)	I _{CEO} I _{CES}	— —	50 1.0	μA μA
Collector Cutoff Current	(V _{CE} = 100 V) (V _{CE} = 60 V, V _{BE} = 2 V, T _C = 150°C)	I _{CEx} I _{CEx}	—	1.0 500	mA μA
Emitter Cutoff Current	(V _{EB} = 4 V) (V _{EB} = 5.5 V)	I _{EBO}	— —	1.0 1.0	μA mA
DC Current Gain *	(I _C = 100 mA, V _{CE} = 5 V) 2N5006 2N5008 (I _C = 5 A, V _{CE} = 5 V) 2N5006 2N5008 (I _C = 10 A, V _{CE} = 5 V) 2N5006 2N5008	h _{FE}	20 50 30 70 20 45	— — 90 200 — —	
Collector-Emitter Saturation Voltage *	(I _C = 5 A, I _B = 500 mA) (I _C = 10 A, I _B = 500 mA)		— —	0.9 1.5	
Base-Emitter Saturation Voltage *	(I _C = 5 A, I _B = 500 mA) (I _C = 10 A, I _B = 1 A)		— —	1.8 2.2	
Base – Emitter Voltage*	(V _{CE} = 5 V, I _C = 5 A)		—	1.8	
Current Gain – Bandwidth Product	(V _{CE} = 5 V, I _C = 0.5 A, f = 20 MHz) 2N5006 2N5008		30 40	— —	
Output Capacitance	V _{CB} = 10 V, I _E = 0 A, f = 1.0MHz	C _{ob}	—	275	pF
Delay Time	(V _{CC} = 40 V, I _C = 2 A, V _{EB (OFF)} = 3.0 V, I _{B1} = I _{B2} = 200 mA) (tp = 2μs)	t _(on)	t _d	—	100 ns
Rise Time			t _r	—	100 ns
Storage Time		t _(off)	t _s	—	2.0 μs
Fall Time			t _f	—	200 ns

NOTES:

* Pulse Test: Pulse Width = 300μsec, Duty Cycle = 2%

1/ For Ordering Information, Price, and Availability Contact Factory.

2/ Screening based on MIL-PRF-19500. Screening flows are available on request.

3/ For Package Outlines Contact Factory.

4/ Up and Down Bend Configurations are Available for 'M' (TO-254) Packages Only.

5/ Unless Otherwise Specified, All Electrical Characteristics @25°C.

Available Part Numbers:

SPT5006/61, SPT5006/3, SPT5006M, SPT5006MUB, SPT5006MDB, SPT5006S1,
SPT5008/61, SPT5008/3, SPT5008M, SPT5008MUB, SPT5008MDB, SPT5008S1

PIN ASSIGNMENT (Standard)

Package	Collector	Emitter	Base
TO-61 (/61)	Pin 3	Pin 1	Pin 2
TO-3 (/3)	Case	Pin 2	Pin 3
TO-254 (M)	Pin 1	Pin 2	Pin 3
SMD1(S1)	Pin 2	Pin 1	Pin 3

NOTE: All specifications are subject to change without notification.
SCD's for these devices should be reviewed by SSDI prior to release.

DATA SHEET #: TR0113A

DOC