

RR2 Polarity Reversal Relay Module



Model

RR2

General Description

The RR2 Polarity Reversal Relay Module is intended for use with 2-wire and 4-wire detectors with built-in sounder, such as the following System Sensor models: 2100AT, 2112/24AT, 2112/24ATR and 2112/24AITR. Per NFPA requirements, the RR2 is designed to allow all detectors on a loop to sound when one goes into alarm. The RR2 can differentiate between steady and pulsed panel outputs.

RR2



Product Overview

Can be used with a single alarm output panel that provides both coded (pulsed) output for fire and continuous output for burglary.

Fulfills NFPA 72 requirement for sounder models

Designed for use with System Sensor 2100 Series sounder models

Colored wires facilitate easy installation

Compatible with 2-wire and 4-wire smoke detectors

Can be used with 12 VDC and 24 VDC systems

Plug-in quick disconnects for easy wiring

Specifications

Operating Voltage Range:	8.5 to 35 VDC
Maximum Operating Current	25mA
Relay Contacts:	2A at 35 VDC
Operating Temperature Range:	32° to 131° F (0° to 55° C)
Operating Humidity Range:	5% to 95% non-condensing
Dimensions:	2 1/2" x 2 1/2" x 1"
Wire connections:	18 AWG stranded, tinned, 16" long



Frequently Asked Questions

Q. What advantage does the RR2 have over the RR1?

- A. The RR2 has the ability to differentiate between continuous and pulsed panel outputs and can be used on single output panels.

Q. What panel types are compatible with the RR2?

- A. The RR2 can be used with 2-wire, 4-wire, 12 VDC or 24 VDC single or combination output panels.

Q. Does the RR2 operate with Ademco panels? Are separate Ademco modules also required?

- A. The RR2 operates with Ademco panels and does not require a separate Ademco module.

Q. Does the RR2 operate with continuous and coded (pulsed) alarm signals?

- A. The RR2 offers a field-selectable switch for setting the RR2 for continuous or coded outputs.

Q. Are there any special wiring instructions to follow with the RR2?

- A. Polarity should be observed and the RR2 must be connected to an auxiliary power supply.

Q. What kind of panel outputs are required for use with the RR2?


- A. The RR2 can be used with fire control panels with a bell/alarm output or an alarm relay output.

Q. Does the RR2 accommodate more than one 2-wire sounder detector (2100AT) on a loop?

- A. Yes, more than one model 2100AT can be placed on a zone when the panel switches to a reverse polarity, non-current-limited auxiliary power supply*. Refer to wiring diagrams below for specific 2-wire detector wiring.

* Current supply must be adequate per appropriate calculations.


2-Wire System Triggered from IAC/Bell Circuit:



NOTE:

If optional Style A (Class A) wiring is used, a second RR2 module must be added to enable concurrent loop polarity reversal.

2-Wire System Triggered from Alarm Relay Contact:



System Sensor Sales and Service

System Sensor Headquarters
3825 Ohio Avenue
St. Charles, IL 60174
Ph: 800/736-7672
Fx: 630/377-6495
Documents-on-Demand:
800/736-7672 x3
Web: www.systemsensor.com

System Sensor in Canada
Ph: 905/812-0767
Fx: 905/812-0771

System Sensor in Europe
Ph: + 44.1403.276500
Fx: + 44.1403.276501

System Sensor in China
Ph: + 86.29.524.6253
Fx: + 86.29.524.6259

System Sensor in Singapore
Ph: + 65.273.2230
Fx: + 65.273.2610

System Sensor in the Far East
Ph: + 852.21919003
Fx: + 852.27366580

System Sensor in Australia
Ph: + 613.54.281.142
Fx: + 613.54.281.172

System Sensor in India
Ph: + 91.11.558.2119
Fx: + 91.11.527.6815