

RL3JG

**ULTRAFAST EFFICIENT
GLASS PASSIVATED RECTIFIER**
VOLTAGE: 600V CURRENT: 2.0A




FEATURE

Low power loss
High surge capability
Ultra-fast recovery time for high efficiency
High temperature soldering guaranteed
250°C/10sec/0.375" lead length at 5 lbs tension

MECHANICAL DATA

Terminal: Plated axial leads solderable per
MIL-STD 750, method 2026
Case: Molded with UL-94 Class V-0 recognized Flame
Retardant Epoxy
Polarity: color band denotes cathode
Mounting position: any

DO-201AD



Dimensions in inches and (millimeters)

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS


(single-phase, half -wave, 60HZ, resistive or inductive load rating at 25°C, unless otherwise stated)

	SYMBOL	RL3JG	units
Maximum Recurrent Peak Reverse Voltage	V _{rrm}	600	V
Maximum RMS Voltage	V _{rms}	420	V
Maximum DC blocking Voltage	V _{dc}	600	V
Maximum Average Forward Rectified Current 3/8" lead length at Ta =45°C	I _{f(av)}	2.0	A
Peak Forward Surge Current 8.3ms single half sine-wave superimposed on rated load	I _{fsm}	130.0	A
Maximum Forward Voltage at Forward current 2A Peak	V _f	1.5	V
Maximum DC Reverse Current Ta =25°C at rated DC blocking voltage Ta =125°C	I _r	10.0 100.0	μ A μ A
Maximum Reverse Recovery Time (Note 1)	T _{rr}	30	nS
Typical Thermal Resistance (Note 2)	R(ja)	10.0	°C/W
Storage and Operating Junction Temperature	T _{stg,Tj}	-55 to +150	°C

Note:

1. Reverse Recovery Condition I_f =0.5A, I_r =1.0A, I_{rr} =0.25A
2. Thermal Resistance from Junction to Ambient at 3/8" lead length, P.C. Board Mounted

PF(AV) - IF(AV) CHARACTERISTICS



IF(AV) - TL CHARACTERISTICS

