

Part No.

QSCM-2MSA-20-2

QSCM manifold, 1/4" male NPT gauge adapter, 2 hoses, 2 process connections, nylon bag

Attach a gauge or pressure calibrator directly to the calibration manifold and easily perform static pressure calibrations (pressure gauge not included)

Features

Item Includes

- Assembly - QSCM Assembly (QSCM)
- Gauge Adapter - 1/4" male NPT x male female QT, no check-valve, 300 series S.S. (QTHA-2MSA)
- Hose - Quick-test hose, S.S. hose ends, 20 ft (6.10 m) long (QSQS-HOS-20ft)
- Hose - Quick-test hose, S.S. hose ends, 2 ft (61 cm) long (QSQS-HOS-2ft)
- Hose Adapter - 1/4" male NPT x male QT, no check-valve, S.S. (QTHA-2MS0)
- Hose Adapter - 1/4" male NPT x male QT, no check-valve, S.S. (QTHA-2MS0)



QSCM-2MSA-20-2

Specifications

Pressure Range	0 to 5000 psi (0 to 345 bar)
Temperature range	0 to 130 °F (-18 to 54 °C)
Construction	Stainless Steel
Seal materials	Buna-N, Delrin, Teflon
Weight	2.09 lb (0.9 kg)
Dimensions	H: 3.78 in (9.60 cm) x W: 5.16 in (13.11 cm) x D: 2.63 in (6.68 cm)