




PN2907A

PNP EPITAXIAL SILICON TRANSISTOR

PNP GENERAL PURPOSE AMPLIFIER

■ DESCRIPTION

This UTC **PN2907A** is designed for use as a general purpose amplifier and switch requiring collector currents to 500 mA.



* Pb-free plating product number: PN2907AL

■ PIN CONFIGURATION

PIN NO.	PIN NAME
1	Emitter
2	Base
3	Collector

■ ORDERING INFORMATION

Order Number		Package	Packing
Normal	Lead free		
PN2907A-T92-B	PN2907AL-T92-B	TO-92	Tape Box
PN2907A-T92-K	PN2907AL-T92-K	TO-92	Bulk

■ ABSOLUTE MAXIMUM RATINGS (Note 1) (Ta=25°C, unless otherwise specified.)

PARAMETER	SYMBOL	RATINGS	UNIT
Collector-Emitter Voltage	V_{CEO}	60	V
Collector-Base Voltage	V_{CBO}	60	V
Emitter-Base Voltage	V_{EBO}	5	V
Collector Current-Continuous	I_C	800	mA
Power Dissipation	P_D	625	mW
Derate above 25°C		5.0	mW/°C
Junction Temperature	T_J	+150	°C
Storage Temperature	T_{STG}	-40 ~ +150	°C

Note 1: These ratings are limiting values above which the serviceability of any semiconductor device may be impaired.

Note 2: These are steady state limits. The factory should be consulted on applications involving pulsed or low duty cycle operations.

Note 3: All voltage (V) and currents (V) are negative polarity for PNP transistors.

■ ELECTRICAL CHARACTERISTICS (Ta=25°C, unless otherwise specified.)

PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
OFF CHARACTERISTICS						
Collector-Emitter Breakdown Voltage*	V _{(BR)CEO}	I _C =10mA, I _B =0	60			V
Collector-Base Breakdown Voltage	V _{(BR)CBO}	I _C =10μA, I _E =0	60			V
Emitter-Base Breakdown Voltage	V _{(BR)EBO}	I _E =10μA, I _C =0	5			V
Base Cutoff Current	I _B	V _{CB} =30V, V _{EB} =0.5V			50	nA
Collector Cutoff Current	I _{CEX}	V _{CE} =30V, V _{BE} =0.5V			50	nA
Collector Cutoff Current	I _{CBO}	V _{CB} =50V, I _E =0			0.02	μA
		V _{CB} =50V, I _E =0, T _a =150°C			20	μA
ON CHARACTERISTICS						
DC Current Gain	h _{FE}	I _C =0.1mA, V _{CE} =10V	75			
		I _C =1.0 mA, V _{CE} =10V	100			
		I _C =10 mA, V _{CE} =10V	100			
		I _C =150 mA, V _{CE} =10V*	100		300	
		I _C =500 mA, V _{CE} =10V*	50			
Collector-Emitter Saturation Voltage*	V _{CE(sat)}	I _C =150mA, I _B =15mA			0.4	V
		I _C =500mA, I _B =50mA			1.6	V
Base-Emitter Saturation Voltage	V _{BE(sat)}	I _C =150mA, I _B =15mA*			1.3	V
		I _C =500mA, I _B =50mA			2.6	V
SMALL SIGNAL CHARACTERISTICS						
Current Gain – Bandwidth Product	f _T	I _C =50mA, V _{CE} =20V, f=100MHz	200			MHz
Output Capacitance	C _{obo}	V _{CB} =10V, I _E =0, f=100kHz			8	pF
Input Capacitance	C _{ibo}	V _{EB} =2V, I _C =0, f=100kHz			30	pF
SWITCHING CHARACTERISTICS						
Turn-on Time	t _{ON}	V _{CC} =30V, I _C =150mA I _{B1} =15mA			45	ns
Delay Time	t _{DLY}				10	ns
Rise Time	t _R				40	ns
Turn-off Time	t _{OFF}	V _{CC} =6V, I _C =150mA I _{B1} =I _{B2} =15mA			100	ns
Storage Time	t _S				80	ns
Fall Time	t _F				30	ns

* Pulse Test: Pulse Width $\leq 300ms$, Duty Cycle $\leq 2.0\%$

Note: All voltages (V) and currents (A) are negative polarity for PNP transistors

THERMAL DATA

PARAMETER	SYMBOL	RATINGS	UNIT
Thermal Resistance Junction- Ambient	Θ_{JA}	200	°C/W
Thermal Resistance Junction- Case	Θ_{JC}	83.3	

TEST CIRCUIT




Fig. 1 Saturated Turn-On Switching Time Test Circuit









Fig. 2 Saturated Turn-Off Switching Time Test Circuit




■ TYPICAL CHARACTERISTICS



■ TYPICAL CHARACTERISTICS(cont.)



■ TYPICAL CHARACTERISTICS FOR COMMON EMITTER ($f=1\text{kHz}$)



UTC assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all UTC products described or contained herein. UTC products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. The information presented in this document does not form part of any quotation or contract, is believed to be accurate and reliable and may be changed without notice.