



DC COMPONENTS CO., LTD.

DISCRETE SEMICONDUCTORS

PN2907

TECHNICAL SPECIFICATIONS OF PNP EPITAXIAL PLANAR TRANSISTOR

Description


Designed for general purpose amplifier and high-speed, medium-power switching applications.

Pinning

- 1 = Emitter
- 2 = Base
- 3 = Collector

Absolute Maximum Ratings($T_A=25^{\circ}\text{C}$)

Characteristic	Symbol	Rating	Unit
Collector-Base Voltage	V_{CB0}	-60	V
Collector-Emitter Voltage	V_{CE0}	-40	V
Emitter-Base Voltage	V_{EB0}	-5	V
Collector Current	I_C	-600	mA
Total Power Dissipation	P_D	625	mW
Junction Temperature	T_J	+150	$^{\circ}\text{C}$
Storage Temperature	T_{STG}	-55 to +150	$^{\circ}\text{C}$



Electrical Characteristics

(Ratings at 25°C ambient temperature unless otherwise specified)

Characteristic	Symbol	Min	Typ	Max	Unit	Test Conditions
Collector-Base Breakdown Voltage	BV_{CB0}	-60	-	-	V	$I_C=-10\mu\text{A}$, $I_E=0$
Collector-Emitter Breakdown Voltage	BV_{CE0}	-40	-	-	V	$I_C=-10\text{mA}$, $I_B=0$
Emitter-Base Breakdown Voltage	BV_{EB0}	-5	-	-	V	$I_E=-10\mu\text{A}$, $I_C=0$
Collector Cutoff Current	I_{CBO}	-	-	-20	nA	$V_{CB}=-50\text{V}$, $I_E=0$
Collector-Emitter Saturation Voltage ⁽¹⁾	$V_{CE(sat)1}$	-	-	-0.4	V	$I_C=-150\text{mA}$, $I_B=-15\text{mA}$
	$V_{CE(sat)2}$	-	-	-1.6	V	$I_C=-500\text{mA}$, $I_B=-50\text{mA}$
Base-Emitter Saturation Voltage ⁽¹⁾	$V_{BE(sat)1}$	-	-	-1.3	V	$I_C=-150\text{mA}$, $I_B=-15\text{mA}$
	$V_{BE(sat)2}$	-	-	-2.6	V	$I_C=-500\text{mA}$, $I_B=-50\text{mA}$
DC Current Gain ⁽¹⁾	h_{FE1}	35	-	-	-	$I_C=0.1\text{mA}$, $V_{CE}=-10\text{V}$
	h_{FE2}	50	-	-	-	$I_C=1\text{mA}$, $V_{CE}=-10\text{V}$
	h_{FE3}	75	-	-	-	$I_C=10\text{mA}$, $V_{CE}=-10\text{V}$
	h_{FE4}	100	-	300	-	$I_C=150\text{mA}$, $V_{CE}=-10\text{V}$
	h_{FE5}	30	-	-	-	$I_C=500\text{mA}$, $V_{CE}=-10\text{V}$
Transition Frequency	f_T	200	-	-	MHz	$I_C=50\text{mA}$, $V_{CE}=-20\text{V}$, $f=100\text{MHz}$
Output Capacitance	C_{ob}	-	-	8	pF	$V_{CB}=-10\text{V}$, $f=1\text{MHz}$, $I_E=0$

(1) Pulse Test: Pulse Width $\leq 380\mu\text{s}$, Duty Cycle $\leq 2\%$