




Low Capacitance ESD Protection Diodes for High-Speed Data Interfaces



MARKING (example only)



Bar = cathode marking

YYY = type code (see table below)

XX = date code

FEATURES

- IEC 61000-4-5 (lightning) see I_{PPM} below
- ESD-protection acc. IEC 61000-4-2
± 8 kV contact discharge
± 15 kV air discharge
- Small package for use in portable electronics
- Space saving SOT-23 package
- High temperature soldering guaranteed:
260 °C/10 s at terminals
- Low capacitance for high speed data lines, cellular handsets, USB port protection, LAN equipment, peripherals
- AEC-Q101 qualified
- e3 - Sn
- Compliant to RoHS Directive 2002/95/EC and in accordance to WEEE 2002/96/EC



RoHS
COMPLIANT
GREEN
(5-2008)**
Available

Note

** Please see document "Vishay Material Category Policy":
www.vishay.com/doc?99902

ORDERING INFORMATION

DEVICE NAME	ENVIRONMENTAL STATUS	ORDERING CODE	TAPED UNITS PER REEL (8 mm TAPE ON 7" REEL)	MINIMUM ORDER QUANTITY
GL05T	Standard	GL05T-GS08	3000	15 000
	Green	GL05T-V-G-08		
GL12T	Standard	GL12T-GS08	3000	15 000
	Green	GL12T-V-G-08		
GL15T	Standard	GL15T-GS08	3000	15 000
	Green	GL15T-V-G-08		
GL24T	Standard	GL24T-GS08	3000	15 000
	Green	GL24T-V-G-08		

PACKAGE DATA

DEVICE NAME	PACKAGE NAME	TYPE CODE	ENVIRONMENTAL STATUS	WEIGHT	MOLDING COMPOUND FLAMMABILITY RATING	MOISTURE SENSITIVITY LEVEL	SOLDERING CONDITIONS
GL05T	SOT-23	L05	Standard	8.8 mg	UL 94 V-0	MSL level 1 (according J-STD-020)	260 °C/10 s at terminals
		L06	Green	8.1 mg	UL 94 V-0	MSL level 1 (according J-STD-020)	260 °C/10 s at terminals
GL12T	SOT-23	L12	Standard	8.8 mg	UL 94 V-0	MSL level 1 (according J-STD-020)	260 °C/10 s at terminals
		L13	Green	8.1 mg	UL 94 V-0	MSL level 1 (according J-STD-020)	260 °C/10 s at terminals
GL15T	SOT-23	L15	Standard	8.8 mg	UL 94 V-0	MSL level 1 (according J-STD-020)	260 °C/10 s at terminals
		L16	Green	8.1 mg	UL 94 V-0	MSL level 1 (according J-STD-020)	260 °C/10 s at terminals
GL24T	SOT-23	L24	Standard	8.8 mg	UL 94 V-0	MSL level 1 (according J-STD-020)	260 °C/10 s at terminals
		L25	Green	8.1 mg	UL 94 V-0	MSL level 1 (according J-STD-020)	260 °C/10 s at terminals

**ABSOLUTE MAXIMUM RATINGS GL05T**

PARAMETER	TEST CONDITIONS	SYMBOL	VALUE	UNIT
Peak pulse current	8/20 μ s	I_{PPM}	17	A
Peak pulse power	8/20 μ s waveform	P_{PP}	300	W
ESD immunity	Contact discharge acc. IEC 61000-4-2; 10 pulses	V_{ESD}	± 8	kV
	Air discharge acc. IEC 61000-4-2; 10 pulses		± 15	kV
Operating temperature	Junction temperature	T_J	- 55 to + 125	$^{\circ}$ C
Storage temperature		T_{STG}	- 55 to + 150	$^{\circ}$ C

ABSOLUTE MAXIMUM RATINGS GL12T

PARAMETER	TEST CONDITIONS	SYMBOL	VALUE	UNIT
Peak pulse current	8/20 μ s	I_{PPM}	12	A
Peak pulse power	8/20 μ s waveform	P_{PP}	300	W
ESD immunity	Contact discharge acc. IEC 61000-4-2; 10 pulses	V_{ESD}	± 8	kV
	Air discharge acc. IEC 61000-4-2; 10 pulses		± 15	kV
Operating temperature	Junction temperature	T_J	- 55 to + 125	$^{\circ}$ C
Storage temperature		T_{STG}	- 55 to + 150	$^{\circ}$ C

ABSOLUTE MAXIMUM RATINGS GL15T

PARAMETER	TEST CONDITIONS	SYMBOL	VALUE	UNIT
Peak pulse current	8/20 μ s	I_{PPM}	10	A
Peak pulse power	8/20 μ s waveform	P_{PP}	300	W
ESD immunity	Contact discharge acc. IEC 61000-4-2; 10 pulses	V_{ESD}	± 8	kV
	Air discharge acc. IEC 61000-4-2; 10 pulses		± 15	kV
Operating temperature	Junction temperature	T_J	- 55 to + 125	$^{\circ}$ C
Storage temperature		T_{STG}	- 55 to + 150	$^{\circ}$ C

ABSOLUTE MAXIMUM RATINGS GL24T

PARAMETER	TEST CONDITIONS	SYMBOL	VALUE	UNIT
Peak pulse current	8/20 μ s	I_{PPM}	5	A
Peak pulse power	8/20 μ s waveform	P_{PP}	300	W
ESD immunity	Contact discharge acc. IEC 61000-4-2; 10 pulses	V_{ESD}	± 8	kV
	Air discharge acc. IEC 61000-4-2; 10 pulses		± 15	kV
Operating temperature	Junction temperature	T_J	- 55 to + 125	$^{\circ}$ C
Storage temperature		T_{STG}	- 55 to + 150	$^{\circ}$ C

ELECTRICAL CHARACTERISTICS GL05T

PARAMETER	TEST CONDITIONS/REMARKS	SYMBOL	MIN.	TYP.	MAX.	UNIT
Protection paths	Number of lines which can be protected	$N_{channel}$	-	-	-	lines
Reverse stand-off voltage	at $I_R = 1 \mu$ A	V_{RWM}	-	-	5	V
Reverse current	at $V_R = 5$ V	I_R	-	-	20	μ A
Reverse breakdown voltage	at $I_R = 1$ mA	V_{BR}	6	-	-	V
Reverse clamping voltage	at $I_{PP} = 1$ A	V_C	-	-	9.8	V
	at $I_{PP} = 5$ A		-	-	11	V
Capacitance	at $V_R = 0$ V; $f = 1$ MHz	C_D	-	5	-	pF

ELECTRICAL CHARACTERISTICS GL12T




PARAMETER	TEST CONDITIONS/REMARKS	SYMBOL	MIN.	TYP.	MAX.	UNIT
Protection paths	Number of lines which can be protected	N_{channel}	-	-	-	lines
Reverse stand-off voltage	at $I_R = 1 \mu\text{A}$	V_{RWM}	-	-	12	V
Reverse current	at $V_R = 5 \text{ V}$	I_R	-	-	1	μA
Reverse breakdown voltage	at $I_R = 1 \text{ mA}$	V_{BR}	13.3	-	-	V
Reverse clamping voltage	at $I_{\text{PP}} = 1 \text{ A}$	V_C	-	-	19	V
	at $I_{\text{PP}} = 5 \text{ A}$		-	-	24	V
Capacitance	at $V_R = 0 \text{ V}$; $f = 1 \text{ MHz}$	C_D	-	5	-	pF

ELECTRICAL CHARACTERISTICS GL15T


PARAMETER	TEST CONDITIONS/REMARKS	SYMBOL	MIN.	TYP.	MAX.	UNIT
Protection paths	Number of lines which can be protected	N_{channel}	-	-	-	lines
Reverse stand-off voltage	at $I_R = 1 \mu\text{A}$	V_{RWM}	-	-	15	V
Reverse current	at $V_R = 5 \text{ V}$	I_R	-	-	1	μA
Reverse breakdown voltage	at $I_R = 1 \text{ mA}$	V_{BR}	16.7	-	-	V
Reverse clamping voltage	at $I_{\text{PP}} = 1 \text{ A}$	V_C	-	-	24	V
	at $I_{\text{PP}} = 5 \text{ A}$		-	-	33	V
Capacitance	at $V_R = 0 \text{ V}$; $f = 1 \text{ MHz}$	C_D	-	5	-	pF

ELECTRICAL CHARACTERISTICS GL24T

PARAMETER	TEST CONDITIONS/REMARKS	SYMBOL	MIN.	TYP.	MAX.	UNIT
Protection paths	Number of lines which can be protected	N_{channel}	-	-	-	lines
Reverse stand-off voltage	at $I_R = 1 \mu\text{A}$	V_{RWM}	-	-	24	V
Reverse current	at $V_R = 5 \text{ V}$	I_R	-	-	1	μA
Reverse breakdown voltage	at $I_R = 1 \text{ mA}$	V_{BR}	26.7	-	-	V
Reverse clamping voltage	at $I_{\text{PP}} = 1 \text{ A}$	V_C	-	-	43	V
	at $I_{\text{PP}} = 5 \text{ A}$		-	-	55	V
Capacitance	at $V_R = 0 \text{ V}$; $f = 1 \text{ MHz}$	C_D	-	5	-	pF

PACKAGE DIMENSIONS in millimeters (inches): **SOT-23**





Foot print recommendation:






Document no.: 6.541-5014.01-4


Rev. 8 - Date: 23.Sept.2009

17418



PACKAGE DIMENSIONS in millimeters (inches)

Foot print recommendation:



Document no.: 6.541-5014.01-4

Rev. 8 - Date: 23.Sept.2009

17418



Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and/or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk and agree to fully indemnify and hold Vishay and its distributors harmless from and against any and all claims, liabilities, expenses and damages arising or resulting in connection with such use or sale, including attorneys fees, even if such claim alleges that Vishay or its distributor was negligent regarding the design or manufacture of the part. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.