

塑封超快速整流二极管


反向电压 100---600V

正向电流 20A

Plastic Ultra-Fast Recover Rectifier

Reverse Voltage 100 to 600 V

Forward Current 20 A



特征 Features

- 大电流承受能力。High Current Capability
- 正向压降低。Low Forward Voltage Drop
- 低功耗高效率。Low Power Loss, High Efficiency
- 引线 and 管体皆符合RoHS标准。

Lead and body according with RoHS standard

机械数据 Mechanical Data

- 封装: 塑料封装 Case: Molded Plastic
- 极性: 标记模压或印于本体 Polarity: Symbols molded or marked on body
- 安装位置: 任意 Mounting Position: Any
- 安装扭矩: 推荐值 0.3牛*米 Mounting torque: Recommend 0.3 N*m

极限值和温度特性 $T_A = 25^\circ\text{C}$ 除非另有规定。

Maximum Ratings & Thermal Characteristics

Ratings at 25°C ambient temperature unless otherwise specified.

	符号 Symbols	MUR2010CT	MUR2020CT	MUR2040CT	MUR2060CT	单位 Unit
最大可重复峰值反向电压 Maximum repetitive peak reverse voltage	V _{RRM}	100	200	400	600	V
最大均方根电压 Maximum RMS voltage	V _{RMS}	70	140	280	420	V
最大直流阻断电压 Maximum DC blocking voltage	V _{DC}	100	200	400	600	V
最大正向平均整流电流 Maximum average forward rectified current	I _{F(AV)}	20				A
峰值正向浪涌电流 8.3ms单一正弦半波 Peak forward surge current 8.3 ms single half sine-wave	I _{FSM}	150				A
典型热阻 Typical thermal resistance	R _{θJC}	3.0		2.0		℃/W
工作结温和存储温度 Operating junction and storage temperature range	T _j , T _{STG}	-55---+150				℃

电特性 $T_A = 25^\circ\text{C}$ 除非另有规定。

Electrical Characteristics

Ratings at 25°C ambient temperature unless otherwise specified.

	符号 Symbols	MUR2010CT	MUR2020CT	MUR2040CT	MUR2060CT	单位 Unit
最大正向电压 $I_F = 10\text{A}$ Maximum forward voltage	V_F	1.00		1.30	1.50	V
最大反向电流 $T_A = 25^\circ\text{C}$ Maximum reverse current $T_A = 125^\circ\text{C}$	I_R	10 250				μA
最大反向恢复时间 $I_F = 0.5\text{A}$ $I_R = 1.0\text{A}$ $I_{REC} = 0.25\text{A}$ MAX. Reverse Recovery Time	t_{rr}	35		50		nS

特性曲线 Characteristic Curves

