

LVDS Dual 2x2 Crosspoint/Repeater Switch

Features

- Dual 2x2 Crosspoint/Repeater Switch
- Meets or Exceeds the Requirements of ANSI TIA/EIA-644-1995
- Designed for Signaling Rates up to 650 Mbit/s (325 MHz)
- Operates from a 3.3V Supply: -40°C to 85°C
- Low Voltage Differential Signaling with Output Voltages of $\pm 350\text{mV}$ into:
 - 100Ω load (PI90LV024)
 - 50Ω load Bus LVDS Signaling (PI90LVB024)
- Accepts $\pm 350\text{mV}$ differential inputs
- Wide common mode input range: 0.2V to 2.7V
- Output drivers are high impedance when disabled or when $V_{CC} \leq 1.5\text{V}$
- Inputs are open, short, and terminated fail safe
- Propagation Delay Time: 3.5ns
- ESD protection is 10kV on bus pins
- Bus Pins are High Impedance when disabled or with V_{CC} less than 1.5V
- TTL Inputs are 5V Tolerant
- Power Dissipation at 400Mbit/s of 250mW
- Packaging (Pb-free & Green Available):
 - 28-pin QSOP (Q)
 - 28-pin TSSOP (L)


Description

The PI90LV024 and PI90LVB024 are monolithic dual 2x2 asynchronous crosspoint/repeater switches. The crosspoint function is based on a multiplexer tree architecture. Each 2x2 switch can be considered as a pair of 2:1 multiplexers that share the same inputs. The signal path through each switch is fully differential with minimal propagation delay. The signal path is unregistered, so no clock is required for the data inputs. The signal line drivers and receivers use Low Voltage Differential Signaling (LVDS) to achieve signaling rates as high as 650 Mbps.


The LVDS standard provides a minimum differential output voltage magnitude of 247mV into a 100Ω load and receipt of 100mV signals with up to 1V of ground potential difference between a transmitter and receiver. The PI90LVB024 doubles the output drive current to achieve Bus LVDS signaling levels with a 50Ω load.

The intended application of these devices is for loop-through and redundant channel switching for both point-to-point base-band (PI90LV024) and multipoint (PI90LVB024) data transmissions over controlled impedance media. The package pin assignments enables easy routing for applications requiring signal feedback.

Block Diagram



Pin Configuration




MUX Truth Table

Input		Output		Function
S_3, S_1	S_2, S_0	${}_1Y/{}_1Z - {}_3Y/{}_3Z$	${}_2Y/{}_2Z - {}_4Y/{}_4Z$	
0	0	${}_1A/{}_1B - {}_3A/{}_3B$	${}_1A/{}_1B - {}_3A/{}_3B$	Splitter
0	1	${}_2A/{}_2B - {}_4A/{}_4B$	${}_2A/{}_2B - {}_4A/{}_4B$	Splitter
1	0	${}_1A/{}_1B - {}_3A/{}_3B$	${}_2A/{}_2B - {}_4A/{}_4B$	Router
1	1	${}_2A/{}_2B - {}_4A/{}_4B$	${}_1A/{}_1B - {}_3A/{}_3B$	Router

Note:

- Setting nDE to 0 will set Output nY/nZ to High Impedance.


Figure 1. Possible Signal Routing



Supply Voltage Range, $V_{CC}^{(2)}$	-0.5V to 4V
Voltage Range (DE, S ₀ , S ₁)	-0.5 to 6V
Input Voltage Range, V_I (A or B)	-0.5V to $V_{CC} + 0.5V$
Electrostatic Discharge: A, B, Y, Z, and GND ⁽³⁾	Class 3, A: 16kV, B: 600V
All Pins	Class 3, A: 7kV, B: 500V
Storage Temperature Range	-65°C to 150°C
Lead Temperature 1, 6 mm (1/16 inch) from case for 10 seconds	260°C

1. Stresses beyond those listed under "Absolute Maximum Ratings" may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated under "Recommended Operating Conditions" is not implied. Exposure to Absolute-Maximum-Rated conditions for extended periods may affect device reliability.
2. All voltage values, except differential I/O bus voltages, are with respect to ground terminal.
3. Tested in accordance with MIL-STD-883C Method 3015.7

Parameter	Description		Min.	Typ.	Max.	Units
V _{CC}	Supply Voltage		3.0	3.3	3.6	V
V _{IH}	High-Level Input Voltage	S ₀ - S ₃ , I _{DE} - 4DE	2			
V _{IL}	Low-Level Input Voltage				0.8	
V _{ID}	Magnitude of Differential Input		0.1		0.6	
V _{IC}	Common-Mode Input Voltage (see fig 2)		$\frac{ V_{ID} }{2}$		$2.4 - \frac{ V_{ID} }{2}$	
					V _{CC} - 0.8	
T _A	Operating Free-air temperature		-40		85	°C




Figure 2. Common-Mode Input Voltage vs. Differential Voltage

Receiver Electrical Characteristics Over Recommended Operating Conditions (unless otherwise noted)

Symbol	Parameter	Test Conditions	Min.	Typ.	Max	Units
V_{ITH+}	Positive-going differential input voltage threshold	$V_{CM} = 1.2V$			100	mV
V_{ITH-}	Negative-going differential input voltage threshold		-100			
I_I	Input Current (A or B inputs)	$V_I = 0V$	-2		-20	μA
		$V_I = 2.4V$	-1.2			
$I_{I(OFF)}$	Power-off Input current (A or B inputs)	$V_{CC} = 0V$			20	

Receiver / Driver Electrical Characteristics Over Recommended Operating Conditions

(unless otherwise noted)

Symbol	Parameter		Test Conditions		Min.	Typ.	Max	Units
V _{OD}	Differential Output Voltage Magnitude		R _L = 100Ω (LV024)	See Fig. 3	247	440	590	mV
ΔV _{OD}	Change in Differential Output Voltage Magnitude between Logic States				-50		50	
V _{OC(SS)}	Steady-State Common-Mode Output Voltage		R _L = 100Ω (LVB024)	See Fig. 4	1.062		1.375	V
ΔV _{OC(SS)}	Change in Steady-State Common-Mode Output Voltage between Logic States				-50	3	50	mV
V _{OC(PP)}	Peak-to-peak common-mode output voltage						150	
I _{CC}	Supply Current		No Load			16	24	mA
			R _L = 100Ω (LV024)			26	40	
			R _L = 50Ω (LVB024)			42	54	
			Both Channels Disabled			6	12	
I _H	High-Level Input Current	DE	V _{IH} = 5V				40	nA
		S ₁ , S ₂ , S ₃ , S ₄					-3	μA
I _L	Low-Level Input Current	DE	V _{IL} = 0.8V				-20	nA
		S ₁ , S ₂ , S ₃ , S ₄					10	μA
I _{OS}	Short Circuit Output Current		V _{OY} or V _{OZ} = 0V				-10	mA
			V _{OD} = 0V				-10	
I _{OZ}	High-Impedance Output Current		V _{OD} = 600mV			1.5	±25	nA
			V _O - 0V or V _{CC}			1.5	±25	
I _{O(OFF)}	Power-Off Output Current		V _{CC} - 0V, V _O = 3.6V			1.5	±40	
C _{IN}	Input Capacitance					3		pF
			S ₀ - S ₃ , 1D _E - 4D _E			8		

Note:

- All typical values are at 25°C and with a 3.3V supply

Differential Receiver to Driver Switching Characteristics Over Recommended Operating Conditions
(unless otherwise noted)

Symbol	Parameter		Test Conditions	Min.	Typ.	Max.	Units
t _{PLH}	Differential propagation delay, low-to-high		C _L = 10pF (see fig. 5)		4.0	6.0	ns
t _{PHL}	Differential propagation delay, high-to-low				4.0	6.0	
t _{sk(p)}	Pulse skew (t _{PHL} - t _{PLH})				0.5	-	
t _r	Transistion, low-to-high	LV024			1.0	1.5	
		LVB024			0.8	1.3	
t _f	Transition, high-to-low	LV024			1.0	1.5	
		LVB024			0.8	1.3	
t _{PHZ}	Propagation delay time, high-level to high impedance output		See fig. 6		4.0	10	
t _{PLZ}	Propagation delat time, low-level to high impedance output				4.3	10	
t _{PZH}	Propagation delat time, high-level to high impedance output				3.0	10	
t _{PZL}	Propagation delat time, high-level to lowimpedance output				2.0	10	
t _{PHL_R1_DX}	Channel-to-channel skew, receiver to driver ⁽²⁾				95		ps
t _{PLH_R1_DX}					95		
t _{PHL_R2_DX}					95		
t _{PLH_R2_DX}					95		

Notes:

1. All typical values are at 25°C and with a 3.3V supply
2. These parametric values are measured over supply voltage and temperature ranges recommended for the device

Parameter Measurement Information




Figure 3. Test Circuit and Voltage Definitions for the Differential Output Signal

Notes:

1. All input pulses are supplied by a generator having the following characteristics: t_r or $t_f \leq 1$ ns, pulse repetition rate (PRR) - 50 Mpps, pulse width = 10 ± 0.2 ns.
2. $R_L = 100\Omega$ or $50\Omega \pm 1\%$.
3. C_L includes instrumentation and fixture capacitance within 6mm of the D.U.T.
4. The measurement of $V_{OC(PP)}$ is made on test equipment with a -3dB bandwidth of at least 300 MHz.




Figure 4. Test Circuit and Definitions for the Driver Common-Mode Output Voltage

Notes:

1. All input pulses are supplied by a generator having the following characteristics: t_r or $t_f \leq 1$ ns, pulse repetition rate (PRR) - 50 Mpps, pulse width = 10 ± 0.2 ns.
2. $R_L = 100\Omega$ or $50\Omega \pm 1\%$.
3. C_L includes instrumentation and fixture capacitance within 6mm of the D.U.T.
4. The measurement of $V_{OC(PP)}$ is made on test equipment with a -3dB bandwidth of at least 300 MHz.




Figure 5. Differential Receiver to Driver Propagation Delay and Driver Transition Time Waveforms

Notes:

1. $R_L = 100\Omega$ or $50\Omega \pm 1\%$
2. All input pulses are supplied by a generator having the following characteristics: pulse repetition rate (PPR) = 50 Mpps, pulse width = $10 \pm 0.2\text{ns}$.




Figure 6. Enable and Disable Timing Circuit

Notes:

1. $R_L = 100\Omega$ or $50\Omega \pm 1\%$
2. All input pulses are supplied by a generator having the following characteristics: pulse repetition rate (PPR) = 0.5 Mpps, pulse width = 500 ± 10 ns.

Typical Characteristics




Figure 7




Figure 8




Figure 9




Figure 10

Figure 1: Dimensional drawings of the 28-pin DIP package. The top drawing is a plan view showing a 28-pin package with dimensions: width .386 to .394 inches (9.804 to 10.009 mm), height .0150 to .0157 inches (3.81 to 3.99 mm), and pin pitch .025 inches (0.635 mm). The bottom drawing is a side view showing a maximum height of 1.35 inches (34.14 mm) and a seating plane offset of .053 inches (1.35 mm). It also shows pin dimensions: .033 inches (0.84 mm) for the top of the pins, .025 inches (0.635 mm) for the pin body, and .008 inches (0.203 mm) for the pin base. A detail view 'Detail A' shows the pin profile with dimensions: .016 inches (0.41 mm) for the pin body, .008 inches (0.20 mm) for the pin base, and .015 inches (0.38 mm) for the pin height. The package is shown with a .015 x 45 degree chamfer on the top edge.

Technical drawings of a 28-pin DIP package showing top, side, and end views with dimensions in inches and millimeters.

Top View:

- Pin 1 indicator circle.
- Pin pitch: $.050$ / 1.27
- Body width: $.378$ / 9.6
- Body length: $.169$ / 4.3
- Overall length: $.177$ / 4.5

Side View:

- Seating Plane.
- Maximum height: $.047$ / 1.20 Max
- Standoff height: $.002$ / 0.05
- Lead thickness: $.007$ / 0.19
- Lead width: $.012$ / 0.30
- Lead spacing: $.0256$ BSC / 0.65

End View:

- Lead thickness: $.004$ / 0.09
- Lead width: $.008$ / 0.20
- Body width: $.018$ / $.030$
- Body length: $.252$ BSC / 6.4
- Body width: $.045$ / $.075$

Legend:

- X.XX DENOTES CONTROLLING DIMENSIONS IN MILLIMETERS

Ordering Information

Ordering Code	Package Code	Packaging Description
PI90LV024Q	Q	28-pin 150-mil SOIC
PI90LV024QE	Q	Pb-free & Green, 28-pin 150-mil SOIC
PI90LV024L	L	28-pin 170-mil TSSOP
PI90LV024LE	L	Pb-free & Green, 28-pin 170-mil TSSOP
PI90LVB024Q	Q	28-pin 150-mil SOIC
PI90LVB024QE	Q	Pb-free & Green, 28-pin 150-mil SOIC
PI90LVB024L	L	28-pin 170-mil TSSOP
PI90LVB024LE	L	Pb-free & Green, 28-pin 170-mil TSSOP

Notes:

1. Thermal Characteristics can be found on the company web site at www.pericom.com/packaging/