

UERP15D

Ultra fast Plastic Power Rectifiers

VOLTAGE: 200V

CURRENT:15.0A



FEATURE


- Plastic package has Underwriters Laboratories Flammability Classification 94V-0
- Ideally suited for use in very high frequency switching power supplies, inverters and as free wheeling diodes
- Ultra fast recovery time for high efficiency
- Excellent high temperature switching
- Glass passivated junction
- High voltage and high reliability
- High speed switching
- Low forward voltage

MECHANICAL DATA

Case: JEDEC ITO-220AB molded plastic body over passivated chip

Terminals: Plated Insert leads, solderable per MIL-STD-750, Method 2026

Mounting Position: Any



MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

(single-phase, half-wave, 60HZ, resistive or inductive load rating at 25°C, unless otherwise stated)

	SYMBOL	UERP15D	units
Maximum Recurrent Peak Reverse Voltage	V _{rrm}	200	V
Maximum RMS Voltage	V _{rms}	140	V
Maximum DC blocking Voltage	V _{dc}	200	V
Maximum Average Forward Rectified at T _c =100°C	I _{f(av)}	15.0	A
Peak Forward Surge Current 8.3ms single half sine-wave superimposed on rated load	I _{fsm}	120	A
Maximum Forward Voltage at Forward Current at 7.5A per leg	V _f	0.98	V
Maximum Reverse Recovery Time (Note 1)	T _{rr}	35	nS
Typical thermal resistance junction to case	R _{θ Jc}	5.0	°C/W
Maximum DC Reverse Current T _a =25°C at rated DC blocking voltage T _a =125°C	I _r	10 500	μA μA
Storage and Operating Temperature Range	T _{stg} , T _j	-55 to +150	°C

Note:

1. Reverse Recovery Condition I_f =0.5A, I_r =1.0A, I_{rr} =0.25A

RATINGS AND CHARACTERISTIC CURVES UERP15D

1

