


## "Half-Bridge" IGBT INT-A-PAK (Standard Speed IGBT), 200 A



INT-A-PAK

### FEATURES

- Generation 4 IGBT technology
- Standard: Optimized for hard switching speed DC to 1 kHz
- Very low conduction losses
- Industry standard package
- UL approved file E78996 
- Compliant to RoHS directive 2002/95/EC
- Designed and qualified for industrial level


**RoHS**  
COMPLIANT

### PRODUCT SUMMARY

$V_{CES}$	600 V
$I_C$ DC	480 A
$V_{CE(on)}$ at 200 A, 25 °C	1.13 V

### BENEFITS

- Increased operating efficiency
- Direct mounting to heatsink
- Performance optimized as output inverter stage for TIG welding machines

### ABSOLUTE MAXIMUM RATINGS

PARAMETER	SYMBOL	TEST CONDITIONS	MAX.	UNITS
Collector to emitter voltage	$V_{CES}$		600	V
Continuous collector current	$I_C$	$T_C = 25\text{ °C}$	480	A
		$T_C = 116\text{ °C}$	200	
Pulsed collector current	$I_{CM}$		800	
Peak switching current	$I_{LM}$		800	
Gate to emitter voltage	$V_{GE}$		$\pm 20$	V
RMS isolation voltage	$V_{ISOL}$	Any terminal to case, $t = 1$ minute	2500	
Maximum power dissipation	$P_D$	$T_C = 25\text{ °C}$	830	W
		$T_C = 85\text{ °C}$	430	

### ELECTRICAL SPECIFICATIONS ( $T_J = 25\text{ °C}$ unless otherwise specified)

PARAMETER	SYMBOL	TEST CONDITIONS	MIN.	TYP.	MAX.	UNITS
Collector to emitter breakdown voltage	$V_{BR(CES)}$	$V_{GE} = 0\text{ V}$ , $I_C = 1\text{ mA}$	600	-	-	V
Collector to emitter voltage	$V_{CE(on)}$	$V_{GE} = 15\text{ V}$ , $I_C = 200\text{ A}$	-	1.13	1.21	
		$V_{GE} = 15\text{ V}$ , $I_C = 200\text{ A}$ , $T_J = 125\text{ °C}$	-	1.08	1.18	
Gate threshold voltage	$V_{GE(th)}$	$I_C = 0.25\text{ mA}$	3	4.5	6	
Collector to emitter leakage current	$I_{CES}$	$V_{GE} = 0\text{ V}$ , $V_{CE} = 600\text{ V}$	-	0.025	1	mA
		$V_{GE} = 0\text{ V}$ , $V_{CE} = 600\text{ V}$ , $T_J = 125\text{ °C}$	-	-	10	
Gate to emitter leakage current	$I_{GES}$	$V_{GE} = \pm 20\text{ V}$	-	-	$\pm 250$	nA

<b>SWITCHING CHARACTERISTICS</b> ( $T_J = 25\text{ }^{\circ}\text{C}$ unless otherwise specified)						
PARAMETER	SYMBOL	TEST CONDITIONS	MIN.	TYP.	MAX.	UNITS
Total gate charge	$Q_g$	$I_C = 200\text{ A}$ $V_{CC} = 400\text{ V}$ $V_{GE} = 15\text{ V}$	-	1600	1700	nC
Gate to emitter charge	$Q_{ge}$		-	260	340	
Gate to collector charge	$Q_{gc}$		-	580	670	
Turn-on switching loss	$E_{on}$	$I_C = 200\text{ A}$ , $V_{CC} = 480\text{ V}$ , $V_{GE} = 15\text{ V}$ $R_g = 10\text{ }\Omega$ Freewheeling diode: 30EPH06, $T_J = 25\text{ }^{\circ}\text{C}$	-	30	-	mJ
Turn-off switching loss	$E_{off}$		-	50	-	
Total switching loss	$E_{ts}$		-	80	-	
Turn-on switching loss	$E_{on}$	$I_C = 200\text{ A}$ , $V_{CC} = 480\text{ V}$ , $V_{GE} = 15\text{ V}$ $R_g = 10\text{ }\Omega$ Freewheeling diode: 30EPH06, $T_J = 125\text{ }^{\circ}\text{C}$	-	34	-	mJ
Turn-off switching loss	$E_{off}$		-	104	-	
Total switching loss	$E_{ts}$		-	138	151	
Input capacitance	$C_{ies}$	$V_{GE} = 0\text{ V}$ $V_{CC} = 30\text{ V}$ $f = 1.0\text{ MHz}$	-	32 500	-	pF
Output capacitance	$C_{oes}$		-	2080	-	
Reverse transfer capacitance	$C_{res}$		-	380	-	

<b>THERMAL AND MECHANICAL SPECIFICATIONS</b>					
PARAMETER	SYMBOL	MIN.	TYP.	MAX.	UNITS
Operating junction temperature range	$T_J$	- 40	-	150	$^{\circ}\text{C}$
Storage temperature range	$T_{Stg}$	- 40	-	125	
Junction to case per leg	$R_{thJC}$	-	-	0.15	$^{\circ}\text{C/W}$
Case to sink	$R_{thCS}$	-	0.1	-	
Mounting torque	case to heatsink	-	-	4	Nm
	case to terminal 1, 2, 3	-	-	3	
Weight		-	185	-	g




Fig. 1 - Typical Output Characteristics




Fig. 2 - Typical Transfer Characteristics




Fig. 3 - Case Temperature vs. Maximum Collector Current




Fig. 6 - Typical Switching Losses vs. Gate Resistance




Fig. 4 - Typical Collector to Emitter Voltage vs. Junction Temperature




Fig. 7 - Typical Switching Losses vs. Collector to Emitter Current






Fig. 5 - Typical Gate Charge vs. Gate to Emitter Voltage



Functional Diagram



Electrical Diagram

# GA200HS60S1PbF



Vishay High Power Products "Half-Bridge" IGBT INT-A-PAK  
(Standard Speed IGBT), 200 A

## ORDERING INFORMATION TABLE

Device code	GA	200	H	S	60	S	1	PbF
	①	②	③	④	⑤	⑥	⑦	⑧
①	- Essential part number IGBT modules							
②	- Current rating (200 = 200 A)							
③	- Circuit configuration (H = Half bridge without f/w diode)							
④	- INT-A-PAK							
⑤	- Voltage code (60 = 600 V)							
⑥	- Speed/type (S = Standard speed IGBT)							
⑦	- Assy location Italy							
⑧	- PbF = Lead (Pb)-free							

LINKS TO RELATED DOCUMENTS	
Dimensions	<a href="http://www.vishay.com/doc?95067">www.vishay.com/doc?95067</a>

**DIMENSIONS** in millimeters (inches)





## Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and/or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk and agree to fully indemnify and hold Vishay and its distributors harmless from and against any and all claims, liabilities, expenses and damages arising or resulting in connection with such use or sale, including attorneys fees, even if such claim alleges that Vishay or its distributor was negligent regarding the design or manufacture of the part. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.