

NEW

Surface Mount Metal Oxide Varistors

NV73 Type

ISO 9001
CERTIFIED

1. General


- Multilayer structure
- High surge current
- Protector against static electricity, switching and incoming surges

2. Features

- Chip type structure suitable for surface mount
- Compact package with large withstanding surge capability
- Symmetrical V-I characteristics make surge absorption possible in either direction

3. Dimensions

Table 1



Dimensions - inches (mm)				
Part	L	W	H	P
1J (0603)	0.063±0.006 (1.60±0.15)	0.031±0.006 (0.80±0.15)	0.031±0.006 (0.80±0.15)	0.016± ^{+0.006} _{-0.008} (0.40± ^{+0.15} _{-0.2})
2A (0805)	0.079±0.008 (2.00±0.20)	0.049±0.008 (1.25±0.20)	0.051 Max (1.30 Max)	0.02±0.010 (0.50±0.25)
2B (1206)	0.126±0.008 (3.20±0.20)	0.063±0.008 (1.60±0.20)	0.065 Max (1.65 Max)	0.02± ^{+0.014} _{-0.010} (0.50± ^{+0.35} _{-0.25})

4. Ordering and Specifying Information

NV73	A	1J	T	TE	8R2
Type	Energy Code	Size	Termination Material	Packaging	Varistor Voltage
	A B C	1J: 0603 2A: 0805 2B: 1206	T: Sn	TE: 7" Embossed Plastic 2,500 pcs/reel	8.2V 8R2 18V 18 "R" indicates decimal on value <10Ω

5. Standard Applications

Part Designation	Reference Varistor Voltage @ 1mA nom. (Range) V _c	Clamping Voltage V _P	I _P	Maximum Peak Current I _P (A) @ 8/20 microsecond (2 pulses)	Maximum Energy E (J)	Capacitance Typ. C (1k to 1MHz) (pF)	Maximum Allowable Voltage a.c rms (V)	Maximum Allowable Voltage d.c (V)	Varistor Voltage (V)	Energy (J)	Peak Current (8/20μs) A (2 pulses)	Operating Temp. T _{opt} (°C)	Storage Temp. T _{stg} (°C)	
NV73A1J*TE8R2	8.2 (6.8 - 9.8)	21	2A	30	0.1	370	4.2	6.0	8.2 - 27	0.1	30	-40°C to +85°C	-40°C to +125°C	
NV73A1J*TE12	12 (10 - 14.4)	29				290	6.1	8.6						
NV73A1J*TE15	15 (12.5 - 18)	35				270	7.6	10.8						
NV73A1J*TE18	18 (16 - 20)	37				230	9.1	12.8						
NV73A1J*TE20	20 (18 - 22)	40				180	10.6	15.0						
NV73A1J*TE22	22 (19 - 24)	42				160	12.0	16.5						
NV73A1J*TE24	24 (21.8 - 26.5)	46				140	14.0	18.0						
NV73A1J*TE27	27 (25 - 32)	49				100	17.0	22.0						
NV73A2A*TE8R2	8.2 (6.8 - 9.8)	16	1A	10	0.01	400 - 80	4.2	6.0	4.2 - 47	0.01 - 0.16	10/20/25	-40°C to +85°C	-40°C to +125°C	
NV73A2A*TE12	12 (10 - 14.4)	22		20	0.03		6.1	8.6						
NV73A2A*TE15	15 (12.5 - 18)	27			0.04		7.6	10.8						
NV73A2A*TE18	18 (16 - 20)	29			0.05		9.1	12.8						
NV73A2A*TE20	20 (18 - 22)	33					10.6	15.0						
NV73A2A*TE22	22 (19 - 24)	39	12.0	16.5										
NV73A2A*TE24	24 (21.8 - 26.5)	42	20	0.06	14.0	18.0	4.2 - 47	0.01 - 0.16	10/20/25	10/20/25	10/20/25			10/20/25
NV73A2A*TE27	27 (25 - 32)	50		0.07	17.0	22.0								
NV73A2A*TE33	33 (30 - 39)	60		1A	0.12	20.0								
NV73A2A*TE39	39 (37 - 47)	72	25		0.14	25.0	31.0							
NV73A2A*TE47	47 (45 - 54)	86			0.16	30.0	38.0							
NV73B2A*TE8R2	8.2 (6.8 - 9.8)	18	2A	20	0.03	1000 - 200	4.2	6.0	4.2 - 33	0.02 - 0.25	20/35/50			-40°C to +85°C
NV73B2A*TE12	12 (10 - 14.4)	22		35	0.05		6.1	8.6						
NV73B2A*TE15	15 (12.5 - 18)	30			0.07		7.6	10.8						
NV73B2A*TE18	18 (16 - 20)	32			0.08		9.1	12.8						
NV73B2A*TE20	20 (18 - 22)	36			0.09		10.6	15.0						
NV73B2A*TE22	22 (19 - 24)	40			0.11		12.0	16.5						
NV73B2A*TE24	24 (21.8 - 26.5)	42			0.12		14.0	18.0						
NV73B2A*TE27	27 (25 - 32)	58			0.24		17.0	22.0						
NV73B2A*TE33	33 (30 - 39)	66		50	0.25		20.0	26.0						
NV73C2A*TE8R2	8.2 (6.8 - 9.8)	16		2A	25		0.04	1000 - 300				4.2	6.0	
NV73C2A*TE12	12 (10 - 14.4)	22	50		0.09	6.1	8.6							
NV73C2A*TE15	15 (12.5 - 18)	28			0.11	7.6	10.8							
NV73C2A*TE18	18 (16 - 20)	32			0.13	9.1	12.8							
NV73C2A*TE20	20 (18 - 22)	35			0.14	10.6	15.0							
NV73C2A*TE22	22 (19 - 24)	40			0.17	12.0	16.5							
NV73C2A*TE24	24 (21.8 - 26.5)	42			0.18	14.0	18.0							

* Add termination material character (T)

Maximum allowable voltage - the maximum sinusoidal RMS voltage or maximum DC voltage which can be applied continuously

E: Maximum energy - the maximum energy within the varistor voltage change of ±10% when a single impulse of 2m sec. is applied

I_P: Maximum peak current - the maximum peak current within the varistor voltage change of ±10% when a single standard impulse of 8/20μ sec. is applied two times with an interval of 5 min.

T_{opt}: Operating temperature - Ambient temperature range when the device is operating

T_{stg}: Storage temperature - Temperature range without causing the device any failure

5. Standard Applications (continued)

Part Designation	Reference Varistor Voltage @ 1mA nom. (Range) Vc	Clamping Voltage V _P	I _P	Maximum Peak Current I _P (A) @ 8/20 microsecond (2 pulses)	Maximum Energy E (J)	Capacitance Typ. C (1k to 1MHz) (pF)	Maximum Allowable Voltage a.c rms (V)	Maximum Allowable Voltage d.c (V)	Varistor Voltage (V)	Energy (J)	Peak Current (8/20μs) A (2 pulses)	Operating Temp. T _{opt} (°C)	Storage Temp. T _{stg} (°C)
NV73A2B*TE27	27 (25 - 32)	55	2A	40	0.13	500 - 100	17.0	22.0	27 - 56	0.13 - 0.26	40	-40°C to +85°C	-40°C to +125°C
NV73A2B*TE33	33 (30 - 39)	60			0.15		20.0	26.0					
NV73A2B*TE39	39 (37 - 47)	72			0.18		25.0	31.0					
NV73A2B*TE47	47 (45 - 54)	85			0.22		30.0	38.0					
NV73A2B*TE56	56 (52 - 62)	100			0.26		35.0	45.0					
NV73B2B*TE8R2	8.2 (6.8 - 9.8)	16	2A	30	0.03	1000 - 300	4.2	6.0	4.2 - 27	0.02 - 0.16	30/50		
NV73B2B*TE12	12 (10 - 14.4)	22		50	0.07		6.1	8.6					
NV73B2B*TE15	15 (12.5 - 18)	28			0.09		7.6	10.8					
NV73B2B*TE18	18 (16 - 20)	32			0.1		9.1	12.8					
NV73B2B*TE20	20 (18 - 22)	35			0.11		10.6	15.0					
NV73B2B*TE22	22 (19 - 24)	40			0.12		12.0	16.5					
NV73B2B*TE24	24 (21.8 - 26.5)	42			0.14		14.0	18.0					
NV73B2B*TE27	27 (25 - 32)	52			0.16		17.0	22.0					
NV73C2B*TE8R2	8.2 (6.8 - 9.8)	15	2A	40	0.06	2000 - 500	4.2	6.0	4.2 - 27	0.02 - 0.24	40/70		
NV73C2B*TE12	12 (10 - 14.4)	21		70	0.1		6.1	8.6					
NV73C2B*TE15	15 (12.5 - 18)	27			0.13		7.6	10.8					
NV73C2B*TE18	18 (16 - 20)	29			0.15		9.1	12.8					
NV73C2B*TE20	20 (18 - 22)	31			0.17		10.6	15.0					
NV73C2B*TE22	22 (19 - 24)	35			0.19		12.0	16.5					
NV73C2B*TE24	24 (21.8 - 26.5)	38			0.2		14.0	18.0					
NV73C2B*TE27	27 (25 - 32)	48			0.24		17.0	22.0					

* Add termination material character (T)

Maximum allowable voltage - the maximum sinusoidal RMS voltage or maximum DC voltage which can be applied continuously

E: Maximum energy - the maximum energy within the varistor voltage change of ±10% when a single impulse of 2m sec. is applied

I_P: Maximum peak current - the maximum peak current within the varistor voltage change of ±10% when a single standard impulse of 8/20μ sec. is applied two times with an interval of 5 min.

T_{opt}: Operating temperature - Ambient temperature range when the device is operating


T_{stg}: Storage temperature - Temperature range without causing the device any failure

6. Rating Table

Terms	Symbol	Description
Maximum Allowable Voltage	—	The maximum sinusoidal RMS voltage or maximum DC voltage which can be applied continuously
Maximum Energy	E	The maximum energy within the varistor voltage change of $\pm 10\%$ when a single impulse of 2m sec. is applied
Maximum Peak Current	I_P	The maximum peak current within the varistor voltage change of $\pm 10\%$ when a single standard impulse of 8/20 μ sec. is applied in two times with an interval of 5 min.
Operating Temperature	T_{opt}	Ambient temperature range while the device is operating
Storage Temperature	T_{stg}	Temperature range without causing the device any failure


7. Voltage-Current Characteristics

NV73A1J ($T_a = +25^\circ\text{C}$) Voltage-Current Characteristics




7. Voltage-Current Characteristics (continued)

NV73A2A (Ta = +25°C) Voltage-Current Characteristics




NV73B2A (Ta = +25°C) Voltage-Current Characteristics




7. Voltage-Current Characteristics (continued)

NV73C2A (Ta = +25°C) Voltage-Current Characteristics




NV73A2B (Ta = +25°C) Voltage-Current Characteristics




7. Voltage-Current Characteristics (continued)

NV73B2B ($T_a = +25^\circ\text{C}$) Voltage-Current Characteristics




NV73C2B ($T_a = +25^\circ\text{C}$) Voltage-Current Characteristics



8. Packaging


(1) Dimensions of Carrier Tape



Tape	A	B	Ko	F	J	H	E	G	D
NV73-1J	0.047±0.004 (1.2±0.1)	0.075±0.004 (1.9±0.1)	0.051 Max. (1.3 Max.)						
NV73-2A	0.063±0.004 (1.6±0.1)	0.094±0.004 (2.4±0.1)	0.063 Max. (1.6 Max.)	0.157±0.004 (4.0±0.1)	0.059±0.004 (1.5±0.1/-0.0)	0.157±0.004 (4.0±0.1)	0.069±0.004 (1.75±0.10)	0.079±0.002 (2.0±0.05)	0.138±0.002 (3.5±0.05)
NV73-2B	0.079±0.004 (2.0±0.1)	0.142±0.004 (3.6±0.1)							

Tape	W	C	t	K ₁	Ø	K
NV73-1J	0.315±0.008 (8.0±0.2)	0.209±0.004 (5.3±0.1)	0.008+0.004 /-0.002 (0.2+0.1/-0.05)	0.067 Max. (1.7 Max.)	30° Max.	0.069 Max. (1.75 Max.)
NV73-2A						
NV73-2B						

(2) Reel dimensions



Dimensions in inches (mm)

	A	B	C	W (min)	W (max)
Series	7.09 ± ⁺⁰ _{-0.118} (Ø180 ± ⁺⁰ ₋₃)	2.36 ± ^{+0.004} ₀ (Ø60 ± ^{+0.1} ₀)	0.512 ± 0.008 (13.0 ± 0.2)	0.354 ± 0.012 (9.0 ± 0.3)	0.449 ± 0.039 (11.4 ± 1.0)