

The **OHB660CB** is a GaAlAs LED mounted in a T0-18 metal can package is ideal for use with plastic fiber optic cables. As light loss is minimal at a wavelength of 660nm.

### FEATURES

- Wide beam angle
- High-speed response
- Low profile package

### APPLICATIONS

- Fiber optic communications



### ELECTRO-OPTICAL CHARACTERISTICS

( Ta=25℃ )

Item	Symbol	Cond.	Min.	Typ.	Max.	Unit
Forward voltage	VF	IF=20mA		1.9	2.4	V
Reverse current	IR	VR=5v			10	μA
Radiant intensity	Po	IF=20mA		3.5		mW/sr
Peak emission wavelength	λp	IF=20mA		660		nm
Spectral bandwidth 50%	Δ λ	IF=20mA		50		nm
Half angle	Δ θ			± 32		deg.

### MAXIMUM RATINGS

( Ta=25℃ )

Item	Symbol	Rating	Unit
Reverse voltage	VR	5	V
Forward current	IF	50	mA
Pulse forward current	IFP	1	A
Power dissipation	Pd	120	mW
Operating temp.	Topr	-25~+100	℃
Storage temp.	Tstg	-30~+100	℃
Soldering temp. <sup>(1)</sup>	Tsol	260	℃

(1)For MAX.5seconds at the position of 2mm from the package

Copyright © Each Manufacturing Company.

All Datasheets cannot be modified without permission.

This datasheet has been download from :

[www.AllDataSheet.com](http://www.AllDataSheet.com)

100% Free DataSheet Search Site.

Free Download.

No Register.

Fast Search System.

[www.AllDataSheet.com](http://www.AllDataSheet.com)