

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: [0025021010](#)
Status: **Active**
Description: 2.54mm (.100") Pitch C-Grid® Header, Dual Row, Shrouded, with PC Slot and Guide Ear, 10 Circuits, 0.76µm (30µ") Gold (Au) Selective Plating

Documents:

3D Model	Product Specification PS-70204 (PDF)
Packaging Specification (PDF)	RoHS Certificate of Compliance (PDF)
Drawing (PDF)	

Agency Certification

CSA	LR19980
UL	E29179

General


Product Family	PCB Headers
Series	70204
Application	Board-to-Board
Product Name	C-Grid®

Physical

Breakaway	No
Circuits (Loaded)	10
Circuits (maximum)	10
Color - Resin	Black
Durability (mating cycles max)	50
Flammability	94V-0
Glow-Wire Compliant	No
Guide to Mating Part	Yes
Lock to Mating Part	None
Material - Metal	Brass, Phosphor Bronze
Material - Plating Mating	Gold
Material - Plating Termination	Tin
Material - Resin	Nylon
Number of Rows	2
Orientation	Vertical
PC Tail Length (in)	0.110 In
PC Tail Length (mm)	2.79 mm
PCB Locator	No
PCB Retention	None
Packaging Type	Tray
Pitch - Mating Interface (in)	0.100 In
Pitch - Mating Interface (mm)	2.54 mm
Plating min: Mating (µin)	30
Plating min: Mating (µm)	0.75
Plating min: Termination (µin)	75
Plating min: Termination (µm)	1.91
Polarized to Mating Part	Yes
Polarized to PCB	No
Shrouded	Fully
Stackable	No
Temperature Range - Operating	-40°C to +105°C
Termination Interface: Style	Through Hole

Electrical

Current - Maximum per Contact	3A
-------------------------------	----



EU RoHS

**ELV and RoHS
Compliant**
**REACH SVHC
Contains SVHC: No**
**Halogen-Free
Status**

China RoHS



**Need more information on product
environmental compliance?**

Email productcompliance@molex.com
For a multiple part number RoHS Certificate of
Compliance, [click here](#)

Please visit the [Contact Us](#) section for any
non-product compliance questions.

Search Parts in this Series
[70204Series](#)

Mates With
[71973](#)


Voltage - Maximum	250V
Solder Process Data	
Duration at Max. Process Temperature (seconds)	5
Lead-free Process Capability	Wave Capable (TH only)
Max. Cycles at Max. Process Temperature	1
Process Temperature max. C	245
Material Info	
Old Part Number	70204-0324
Reference - Drawing Numbers	
Product Specification	PS-70204
Sales Drawing	SDA-70204-0321-0384

This document was generated on 03/31/2010

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION


13		12	11		10		9	
CKT. SIZE	PART NUMBER	ENG. NUMBER SDA-70204-	DIM. "A"		DIM. "B"		DIM. "C"	
			MM	IN.	MM	IN.	MM	IN.
08	25-02-1008	0323	7,62	.300	17,78	.700	20,32	.800
10	25-02-1010	0324	10,16	.400	20,32	.800	22,86	.900
12	25-02-1012	0325	12,70	.500	22,86	.900	25,40	1.000
14	25-02-1014	0326	15,24	.600	25,40	1.000	32,51	1.100
16	25-02-1016	0327	17,78	.700	27,94	1.100	30,48	1.200
18	25-02-1018	0328	20,32	.800	30,48	1.200	33,02	1.300
20	25-02-1020	0329	22,86	.900	33,02	1.300	35,56	1.400
22	25-02-1022	0330	25,40	1.000	35,56	1.400	38,10	1.500
24	25-02-1024	0331	27,94	1.100	38,10	1.500	40,64	1.600
26	25-02-1026	0332	30,48	1.200	40,64	1.600	43,10	1.700
28	25-02-1028	0333	33,02	1.300	43,10	1.700	45,72	1.800
30	25-02-1030	0334	35,56	1.400	45,72	1.800	48,26	1.900
32	25-02-1032	0335	38,10	1.500	48,26	1.900	50,80	2.000
34	25-02-1034	0336	40,64	1.600	50,80	2.000	53,34	2.100
36	25-02-1036	0337	43,10	1.700	53,34	2.100	55,88	2.200
38	25-02-1038	0338	45,72	1.800	55,88	2.200	58,42	2.300
40	25-02-1040	0339	48,26	1.900	58,42	2.300	60,96	2.400

8	7	6	5	4	3	2	1
CKT. SIZE	PART NUMBER	ENG. NUMBER SDA-70204-	DIM. "A" MM IN.	DIM. "B" MM IN.	DIM. "C" MM IN.		
J	42	25-02-1042	0340	50.80 2.000 60.96 2.400 63.50 2.500			
	44	25-02-1044	0341	53.34 2.100 63.50 2.500 66.04 2.600			
	46	25-02-1046	0342	55.88 2.200 66.04 2.600 68.58 2.700			
	48	25-02-1048	0343	58.42 2.300 68.58 2.700 71.12 2.800			
	50	25-02-1050	0344	60.96 2.400 71.12 2.800 73.66 2.900			
	52	25-02-1052	0345	63.50 2.500 73.66 2.900 76.20 3.000			
	54	25-02-1054	0346	66.04 2.600 76.20 3.000 78.74 3.100			
	56	25-02-1056	0347	68.58 2.700 78.74 3.100 81.28 3.200			
	58	25-02-1058	0348	71.12 2.800 81.28 3.200 83.82 3.300			
	60	25-02-1060	0349	73.66 2.900 83.82 3.300 86.36 3.400			
	62	25-02-1062	0350	76.20 3.000 86.36 3.400 88.90 3.500			
	64	25-02-1064	0351	78.74 3.100 88.90 3.500 91.44 3.600			
	66	25-02-1066	0352	81.28 3.200 91.44 3.600 93.98 3.700			
	68	25-02-1068	0353	83.82 3.300 93.98 3.700 96.52 3.800			
	70	25-02-1070	0354	86.36 3.400 96.52 3.800 99.06 3.900			
	72	25-02-1072	0355	88.90 3.500 99.06 3.900 101.60 4.000			




DETAIL "V"

SCALE = 20:1



DETAIL "S"



SECTION W-W

NOTES:

- 1) WAFER MATERIAL: GLASS FILLED NYLON COLOR, BLACK.
- 2) PIN MATERIAL: PHOSPHOR BRONZE ALLOY
- 3) PIN PLATING:
TIP: .000030 MINIMUM GOLD IN SELECTED AREA
TAIL: .000075 MINIMUM TIN IN SELECTED AREA
OVER .000050 NICKEL OVER-ALL.
- *THE PRIMARY SHIPPING CARTON WILL BE LABELED 'COMPLIANT TO RoHS DIRECTIVE 2002/95/EC AND ELV ANNEX II OF DIRECTIVE 2000/53/EC'. CARTONS WITHOUT THIS LABEL MAY CONTAIN PRODUCT WITH LEAD.
- 4) PINS MUST MEET SOLDERABILITY SPEC. NO. I52.
- 5) PIN PUSH-OUT FORCE (1.81 KG.)/4 LBS MINIMUM
- 6) REFER TO P.S. NO. 70204.
- 7) STANDARD PACKAGING PER: PK-70873-0070.

RECOMMENDED P.C. BOARD HOLE LAYOUT

REMOVAL	DESCRIPTION	DATE
0356-0384	REMOVE	2006/08/07
UCP2007-0113	UCP2007-0113	2006/08/16
DRW:ANDRORGAN	DRW:ANDRORGAN	2006/08/16
CHKD:MS BARRA	CHKD:MS BARRA	2006/08/16
APPR:SMILLER	APPR:SMILLER	2006/08/16

QUALITY SYMBOLS	GENERAL TOLERANCES (UNLESS SPECIFIED)	DIMENSION STYLE	SCALE	DESIGN UNITS	THIRD ANGLE PROJECTION
▽=0	mm INCH	MM/IN	4:1	INCH	
▽=0	4 PLACES ± --- ± ---	DRAWN BY DATE	JAS 1986/05/20	CHECKED BY DATE	EIK 1986/05/20
	3 PLACES ± 0.25 ± .010	APPROVED BY DATE	WAZ 1986/05/20	MATERIAL NO.	SDA-70204-0321-0384
	2 PLACES ± --- ± ---	SIZE	SEE TABLE	SHEET NO.	1 OF 1
	1 PLACE ± --- ± ---				
	ANGULAR ±1/2°				
	DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS				

SHROUDED HEADER DUAL ROW W/PCB SLOTS & GUIDE EARS .100 GRID .025 SQ PIN

MOLEX INCORPORATED