

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:

0473621010

Status:

Active

Overview:

serial_ata_127_host_receptacles

Description:

1.27mm (.050") Pitch Combo SATA Cable Connector, Straight Type, with Arris on top surface, with bumps, Gold(Au) Flash Plating, 22 Circuits, Lead Free

Documents:

3D Model

Drawing (PDF)


Product Specification PS-47362-001 (PDF)

RoHS Certificate of Compliance (PDF)

General	
Product Family	I/O Connectors
Series	47362
Application	Wire-to-Board
Comments	Straight Type
Component Type	Receptacle
Overview	serial_ata_127_host_receptacles
Product Name	Serial ATA
Type	N/A

Physical	
Boot Color	N/A
Circuits (Loaded)	22
Circuits (maximum)	22
Circuits Detail	Signal 7, Power 15
Color - Resin	Black
Durability (mating cycles max)	50
Gender	Receptacle
Keying to Mating Part	Yes
Lock to Mating Part	Yes
Material - Metal	Copper Alloy
Material - Plating Mating	Gold
Material - Plating Termination	Tin
Number of Rows	1
Orientation	Straight
PCB Locator	No
PCB Retention	None
Packaging Type	Tray
Panel Mount	No
Pitch - Mating Interface (in)	0.050 In
Pitch - Mating Interface (mm)	1.27 mm
Pitch - Term. Interface (in)	0.050 In
Pitch - Term. Interface (mm)	1.27 mm
Plating min: Mating (µin)	2
Plating min: Mating (µm)	0.05
Plating min: Termination (µin)	50
Plating min: Termination (µm)	1.27
Polarized to Mating Part	Yes
Polarized to PCB	Yes
Ports	2
Temperature Range - Operating	-35°C to +85°C
Termination Interface: Style	Solder or Weld
Waterproof / Dustproof	No
Wire Size AWG	N/A

Electrical



EU RoHS

ELV and RoHS

Compliant

REACH SVHC

Not Reviewed

Halogen-Free

Status

Not Reviewed

China RoHS



Need more information on product environmental compliance?

Email productcompliance@molex.com
For a multiple part number RoHS Certificate of Compliance, [click here](#)

Please visit the [Contact Us](#) section for any non-product compliance questions.

Search Parts in this Series

47362Series

Current - Maximum per Contact	1.5A
Voltage - Maximum	15V DC

Material Info



Reference - Drawing Numbers

Packaging Specification	PK-47362-001
Product Specification	PS-47362-001
Sales Drawing	SD-47362-100

This document was generated on 05/19/2010

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

10 9 8 7 6 5 4 3 2 1



NOTES:

1. MATERIAL:

HOUSING: THERMAL PLASTIC, GLASS FILLED, UL94V-0, COLOR: BLACK.
TERMINAL: COPPER ALLOY, THICKNESS=0.25MM.



2. TERMINAL PLATING:

CONTACT AREA: GOLD PLATED, SEE TABLE.
SOLDER AREA: PURE TIN, THICKNESS=1.27 MICRONS MINIMUM.
UNDER PLATE: NICKLE, THICKNESS=1.27 MICRONS MINIMUM.

3. PRODUCT SPECIFICATION: REFER TO PS-47362-001.

4. PACKAGING METHOD: REFER TO PK-47362-001.

5. PRODUCT COMPLIANT TO RoHS DIRECTIVE 2002/95/EC AND
ELV DIRECTIVE 2000/53/EC



ADD NEW OPTION EC NO: SH2009-0500 DRWN: XJ SONG 2009/04/16 CHKD: XJ SONG 2009/04/17 APPR: HWANG 2009/05/21 REV	DESCRIPTION	QUALITY SYMBOLS ▽=0 ▽=0	GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION STYLE MM ONLY		SCALE 4:1	DESIGN UNITS METRIC	THIRD ANGLE PROJECTION				
				mm	INCH	DRAWN BY BCHEN26	DATE 2005/12/05	TITLE COMBO SATA RECEPTACLE CABLE END					
			4 PLACES	± ---	± ---	CHECKED BY DIXON	DATE 2005/12/05						
			3 PLACES	± ---	± ---	APPROVED BY GRATE		DATE 2005/12/05	MOLEX INCORPORATED				
			2 PLACES	± 0.2	± ---	MATERIAL NO. SEE SHEET 4		DOCUMENT NO. SD-47362-100					
			1 PLACE	± 0.25	± ---	DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS							
			ANGULAR ± 3 °										

9 8 7 6 5 4 3 2 1

10 9 8 7 6 5 4 3 2 1

F

E

D

C

B

A

F


E

D



C

B

A




COVER



0,45 ±0,05
TYP. (22X)


⌀ 0,15 B





ARRIS

RIGHT ANGLE(90 DEGREE) TYPE

OTHER DIMENSIONS REFER TO STRAIGHT TYPE








SECTION Z-Z



DETAIL1

SEE SHEET1 EC NO: SH2009-0500 2009/04/16 DRWN:XJ.SONG 2009/04/17 CHKD:XJ.SONG 2009/05/21 APPR:HWANG	DESCRIPTION REV	QUALITY SYMBOLS ▽=0 ▽C=0	GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION STYLE MM ONLY		SCALE 4:1	DESIGN UNITS METRIC	 THIRD ANGLE PROJECTION	
					DRAWN BY BCHEN26	DATE 2005/12/05	TITLE COMBO SATA RECEPTACLE CABLE END			
			4 PLACES	± ---	± ---	CHECKED BY DIXON				DATE 2005/12/05
			3 PLACES	± ---	± ---	APPROVED BY GRATE		DATE 2005/12/05		 MOLEX INCORPORATED
			2 PLACES	± 0.2	± ---					
			1 PLACE	± 0.25	± ---	DOCUMENT NO. SD-47362-100		SHEET NO. 2 OF 4		
			ANGULAR ± 3 °		MATERIAL NO. SEE SHEET4					
			DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		SIZE A3		THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION			



RIGHT ANGLE(270 DEGREE) TYPE
OTHER DIMENSIONS REFER TO RIGHT ANGLE(90 DEGREE) TYPE

SEE SHEET1 EC NO: SH2009-0500 DRWN:X JSONG CHKD:X JSONG APPR:HWANG	DESCRIPTION	QUALITY SYMBOLS ▽=0 ▽=0	GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION STYLE MM ONLY		SCALE 4:1	DESIGN UNITS METRIC	THIRD ANGLE PROJECTION			
					DRAWN BY BCHEN26	DATE 2005/12/05	TITLE COMBO SATA RECEPTACLE CABLE END					
					CHECKED BY DIXON	DATE 2005/12/05						
					APPROVED BY GRATE	DATE 2005/12/05	MOLEX INCORPORATED					
					ANGULAR ± 3 °							MATERIAL NO.
					DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		SEE SHEET4		DOCUMENT NO. SD-47362-100			SHEET NO. 3 OF 4
							SIZE A3		THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION			

	10	9	8	7	6	5	4	3	2	1		
	P/N	PLATE TYPE	REMARK	STRAIGHT OR R/A	P/N	PLATE TYPE	REMARK	STRAIGHT OR R/A				
F	47362-1000	GOLD FLASH			47362-3000	GOLD FLASH						
	47362-1001	GOLD PLATED 0.76 MICRONS MIN.	WITH ARRIS ON BOTH SURFACE		47362-3001	GOLD PLATED 0.76 MICRONS MIN.	WITH ARRIS ON BOTH SURFACE					
	47362-1002	GOLD PLATED 0.38 MICRONS MIN.	WITH BUMPS		47362-3002	GOLD PLATED 0.38 MICRONS MIN.	WITH BUMPS,WITH COVER					
	47362-1010	GOLD FLASH			47362-3010	GOLD FLASH						
	47362-1011	GOLD PLATED 0.76 MICRONS MIN.	WITH ARRIS ON TOP SURFACE		47362-3011	GOLD PLATED 0.76 MICRONS MIN.	WITH ARRIS ON TOP SURFACE					
	47362-1012	GOLD PLATED 0.38 MICRONS MIN.	WITH BUMPS		47362-3012	GOLD PLATED 0.38 MICRONS MIN.	WITH BUMPS,WITH COVER					
	47362-1020	GOLD FLASH			47362-3020	GOLD FLASH						
	47362-1021	GOLD PLATED 0.76 MICRONS MIN.	WITH ARRIS ON BOTTOM SURFACE		47362-3021	GOLD PLATED 0.76 MICRONS MIN.	WITH ARRIS ON BOTTOM SURFACE					
	47362-1022	GOLD PLATED 0.38 MICRONS MIN.	WITH BUMPS		47362-3022	GOLD PLATED 0.38 MICRONS MIN.	WITH BUMPS,WITH COVER					
	47362-1030	GOLD FLASH			47362-3030	GOLD FLASH						
	47362-1031	GOLD PLATED 0.76 MICRONS MIN.	WITHOUT ARRIS		47362-3031	GOLD PLATED 0.76 MICRONS MIN.	WITHOUT ARRIS					
	47362-1032	GOLD PLATED 0.38 MICRONS MIN.	WITH BUMPS		47362-3032	GOLD PLATED 0.38 MICRONS MIN.	WITH BUMPS,WITH COVER					
D	47362-2000	GOLD FLASH										
	47362-2001	GOLD PLATED 0.76 MICRONS MIN.	WITH ARRIS ON BOTH SURFACE									
	47362-2002	GOLD PLATED 0.38 MICRONS MIN.	WITH BUMPS,WITH COVER									
	47362-2010	GOLD FLASH										
	47362-2011	GOLD PLATED 0.76 MICRONS MIN.	WITH ARRIS ON TOP SURFACE									
	47362-2012	GOLD PLATED 0.38 MICRONS MIN.	WITH BUMPS,WITH COVER									
	47362-2020	GOLD FLASH										
	47362-2021	GOLD PLATED 0.76 MICRONS MIN.	WITH ARRIS ON BOTTOM SURFACE									
	47362-2022	GOLD PLATED 0.38 MICRONS MIN.	WITH BUMPS,WITH COVER									
	47362-2030	GOLD FLASH										
	47362-2031	GOLD PLATED 0.76 MICRONS MIN.	WITHOUT ARRIS									
	47362-2032	GOLD PLATED 0.38 MICRONS MIN.	WITH BUMPS,WITH COVER									
C	47362-1003	GOLD PLATED 0.38 MICRONS MIN.	WITH ARRIS ON BOTH SURFACE WITHOUT BUMPS	STRAIGHT TYPE								
	47362-1082	GOLD PLATED 0.38 MICRONS MIN.	WITH ARRIS ON BOTH SURFACE WITH BUMPS	STRAIGHT TYPE								
B												
A												
fb_frame_A3_P_AM_T Rev. E 2006/04/15												