




ITT

Cannon Universal Contact Series




Engineered for life

Universal Contact

Universal Contact is an independent SMT contact which provides an electrical connection between a device and a PCB. The contact is manufactured as a single piece stamped product, incorporating pre-load and anti-lift features. The Universal Contact has been designed to replace traditional interfaces where the contact is custom designed into the component. It can be used to connect a number of device components in any direction and configuration using the same interface.

Features & Benefits of the Design

- Range of heights available:
 - 1.3mm contact with the minimum pitch of 1.35mm
 - 1.8mm contact with the minimum pitch of 1.25mm
 - 2.5mm contact the minimum pitch is 1.35mm
 - 3.5 & 4.0mm minimum pitch is 1.45mm
- Solderwell that prevents solder wicking up the contact
- "Side wings" protect the active parts of the contact which prevent contact from overstressing and potential damage
- Domed contact point allows good hertz stress and low contact resistance
- The X-Y-Z movement allows robust connection between the contact and component assembly during shock and vibration
- Compliant with WEEE and RoHS directives.



Additional Advantages of using Universal Contacts

- Qualification time reduction - same contact for many components
- Allows standard interface across applications and platforms
- Freedom to position at an angle - not fixed by mating component

Applications

Handset

- Solderless component interconnect
- I/O connector / Board to board interconnect

- Battery contact / Antenna contact
- Grounding contact / SIM contact

Laptops & Computers

- Memory Stick

Home Electronic Devices / White Goods

- Smoke detectors / Security alarm systems
- Home appliances

Automotive - Keyfob

Medical - CT scan equipment

Industrial - Circuit breaker for GPS beacon

Materials & Finishes

Base material	Beryllium Copper
Plating	Selective Au in contact area 1 µm min over Au stripe, 0.05 - 0.1 µm over Ni 1.0 - 3.0 µm

Electrical

Contact resistance	Max 20 mΩ
Max current rating	2.0 amps nominal 3.0 amps peak

Environmental

Operating temperature	-40°C and +85°C
Humidity	Operable in 90% relative humidity (temp + 40°C)

Solder systems Infrared and hot air reflow

Vibration In accordance with IEC 68-2-36

Shock In accordance with IEC 68-2-27, 30 g

Mechanical


See selection table on the right for contact forces at specific mating heights

Maximum mating cycle based on mating PCB plated with 0.05µ Au over 2.0µ m Ni = 3,000 cycles. (Wear resistance is subject to mating component surface finish and plating type, increased mating component plating spec = increased mating cycles.)


Packaging

Packaged in 12mm wide tape & reel packaging to EIA-481 standards


MATING HEIGHT	1.3mm	1.8mm	2.5mm	3.5mm	4.0mm
FORCE (N) AT COMPRESSED HEIGHT					
0.90	0.58				
1.00	0.51	0.87			
1.10	0.44	0.80			
1.20	0.37	0.74			
1.30	Pre-load	0.68			
1.40		0.62			
1.50		0.56	0.58		
1.60		0.49	0.55		
1.70		0.43	0.52		
1.80		Pre-load	0.49		
1.90			0.46		
2.00			0.42	0.94	
2.10			0.39	0.91	
2.20			0.36	0.87	
2.30			0.33	0.83	
2.40			0.30	0.80	
2.50			Pre-load	0.76	1.30
2.60				0.73	1.27
2.70				0.69	1.24
2.80				0.65	1.22
2.90				0.62	1.19
3.00				0.58	1.16
3.10				0.55	1.13
3.20				0.51	1.11
3.30				0.47	1.08
3.40				0.44	1.05
3.50				Pre-load	1.02
3.60					1.00
3.70					0.97
3.80					0.94
3.90					0.91
4.00					Pre-load
Spring Rate N/mm	0.68	0.62	0.32	0.36	0.28




1.3mm
120220-0210
 packaging: 9,500 per reel




1.8mm
120220-0202
 packaging: 6,800 per reel




2.5mm
120220-0161
 packaging: 6,000 per reel



3.5mm
120220-0204
 packaging: 3,600 per reel



4mm
120220-0206
 packaging: 3,200 per reel



2 way - 2.5mm height,
1.5 pitch
120220-0162



ITT



ITT

Customer Support Locations

AMERICAS

100 New Wood Road
Watertown, CT 06796
Tel: 860.945.0206
Toll Free: 800.683.7666
Fax: 860.645.0303

ASIA

Unit 901 & 912, West Tower,
Shun Tak Center
168-200 Connaught Road
Central, Hong Kong
Tel: +852.2732.2720
Fax: +852.2732.2919

EUROPE

Jays Close, Viabes Estate
Basingstoke, Hants, RG22 4BA
Tel: +44.1256.311200
Fax: +44.1256.323356