

Silicon NPN Power Transistors

2SD1456

DESCRIPTION


- With TO-3PN package
- High voltage,high speed
- Built-in damper diode

APPLICATIONS

- For TV horizontal deflection output applications

PINNING

PIN	DESCRIPTION
1	Base
2	Collector;connected to mounting base
3	Emitter



Absolute maximum ratings (Ta=25°C)

SYMBOL	PARAMETER	CONDITIONS	VALUE	UNIT
V_{CBO}	Collector-base voltage	Open emitter	1500	V
V_{EBO}	Emitter-base voltage	Open collector	6	V
I_C	Collector current (DC)		6	A
P_C	Collector power dissipation	$T_C=25^{\circ}C$	50	W
T_j	Junction temperature		150	$^{\circ}C$
T_{stg}	Storage temperature		-45~150	$^{\circ}C$

Silicon NPN Power Transistors**2SD1456****CHARACTERISTICS**T_j=25°C unless otherwise specified

SYMBOL	PARAMETER	CONDITIONS	MIN	TYP.	MAX	UNIT
V _{(BR)EBO}	Emitter-base breakdown voltage	I _E =200mA; I _C =0	6			V
V _{CEsat}	Collector-emitter saturation voltage	I _C =5A; I _B =1A			5.0	V
V _{BEsat}	Base-emitter saturation voltage	I _C =5A; I _B =1A			1.5	V
I _{CBO}	Collector cut-off current	V _{CB} =1500V; I _E =0			0.5	mA
h _{FE}	DC current gain	I _C =1A ; V _{CE} =5V	6			
V _F	Diode forward voltage	I _F =6A			2.2	V

固电半导体
INCHANGE SEMICONDUCTOR

Silicon NPN Power Transistors

2SD1456

PACKAGE OUTLINE

