

**M29150A/B****LINEAR INTEGRATED CIRCUIT****1.5A, VERY LOW DROP
VOLTAGE REGULATORS****DESCRIPTION**

As the UTC linear integrated LDO, the UTC **M29150A/B** shows a high current, high accuracy, low-dropout voltage. The features are: 400mV dropout voltage, very low ground current. Cause the series have been designed for high current loads, so they are also used in lower current, extremely low dropout-critical systems (in which their tiny dropout voltage and ground current values are important attributes).

FEATURES

- * Very low dropout voltage : typ. 0.4 @ $I_{OUT}=1.5A$
- * Output current guaranteed 1.5A
- * Fixed and adjustable output voltage
- * Thermal limit and Internal current
- * Logic controlled electronic shutdown available
- * Over voltage protection


ORDERING INFORMATION

Ordering Number		Package	Packing
Lead Free	Halogen Free		
M29150AL-xx-TN4-R	M29150AG-xx-TN4-R	TO-252-4	Tape Reel
M29150BL-xx-TN4-R	M29150BG-xx-TN4-R	TO-252-4	Tape Reel
M29150AL-xx-TN5-R	M29150AG-xx-TN5-R	TO-252-5	Tape Reel
M29150BL-xx-TN5-R	M29150BG-xx-TN5-R	TO-252-5	Tape Reel


M29150XL-xx-TN4-R

- (1) Packing Type
- (2) Package Type
- (3) Output Voltage Code
- (4) Lead Plating
- (5) Over Voltage Protection

- (1) R: Tape Reel
- (2) TN4: TO-252-4, TN5: TO-252-5
- (3) xx: Refer to Marking Information
- (4) G: Halogen Free, L: Lead Free
- (5) X: Refer to Marking Information



TO-252-5




TO-252-4

MARKING INFORMATION

PACKAGE	VOLTAGE CODE	MARKING
TO-252-4	50 :5.0V	
TO-252-5	AD :ADJ	

PIN CONFIGURATION




PIN DESCRIPTIONS


PIN NO.	PIN NAME	PIN FUNCTION
1	INH	Inhibit Function Input
2	V _{IN}	Input voltage
3	GND	GND
4	V _{OUT}	Output Voltage
5	ADJ/NC	Adjustable Version Input /Not connected for fixed version

■ BLOCK DIAGRAM

Adjustable Version



Fixed Version



■ ABSOLUTE MAXIMUM RATINGS

PARAMETER	SYMBOL	RATINGS	UNITS
DC Input Voltage	V_{IN}	30	V
DC Output Voltage	V_{OUT}	-0.3 ~ +20	V
Inhibit Input Voltage	V_{INH}	-0.3 ~ +20	V
Over Voltage Protection	M29150A	14	V
	M29150B	35	V
Output current	I_{OUT}	Internally Limited	mA
Power Dissipation	P_D	Internally Limited	mW
Junction Temperature	T_J	+150	°C
Operating Temperature	T_{OPR}	-40 ~ +125	°C
Storage Temperature	T_{STG}	-55 ~ +150	°C

Notes: 1. Absolute maximum ratings are those values beyond which the device could be permanently damaged.
Absolute maximum ratings are stress ratings only and functional device operation is not implied.

■ THERMAL DATA

PARAMETER	SYMBOL	RATINGS	UNIT
Junction to Ambient	θ_{JA}	100	°C/W
Junction to Case	θ_{JC}	8	°C/W

■ ELECTRICAL CHARACTERISTICS

($I_{OUT}=10mA$, $T_J=25^\circ C$, $V_{INH}=2V$ (Note 2), $C_I=0.33\mu F$, $C_O=10\mu F$, unless otherwise specified)

M29150-5.0V ($V_{IN}=7.0V$)

PARAMETER	SYMBOL	CONDITIONS	MIN	TYP	MAX	UNIT
Output Voltage	V_{OUT}	$V_{IN}=6V \sim 10.5V$, $I_{OUT}=10mA \sim 1.5A$ M29150A	4.9	5.0	5.1	V
		$V_{IN}=6V \sim 10.5V$, $I_{OUT}=10mA \sim 1.5A$ $V_{IN}=30V$, $I_{OUT}=10mA \sim 100mA$ M29150B	4.95	5.0	5.05	V
Load Regulation	$\frac{\Delta V_{OUT}}{V_{OUT}}$	$I_{OUT}=10mA \sim 1.5A$		0.2	1.0	%
Line Regulation	$\frac{\Delta V_{OUT}}{V_{OUT}}$	$V_{IN}=6V \sim 13V$ M29150A		0.06	0.5	%
		$V_{IN}=6V \sim 30V$ M29150B				
Supply Voltage Rejection	SVR	$f=120Hz$, $V_{IN}=7 \pm 1V$, $I_{OUT}=0.75A$ (Note 1)	49	64		dB
Dropout Voltage	V_D	$I_{OUT}=250mA$, $T_J=-40 \sim 125^\circ C$ (Note 3)		0.1		V
		$I_{OUT}=0.75A$, $T_J=-40 \sim 125^\circ C$ (Note 3)		0.2		V
		$I_{OUT}=1.5A$, $T_J=-40 \sim 125^\circ C$ (Note 3)		0.4	0.7	V
Quiescent Current	I_Q	$I_{OUT}=0.75A$, $T_J=-40 \sim 125^\circ C$		15	40	mA
		$I_{OUT}=1.5A$, $T_J=-40 \sim 125^\circ C$		30	80	mA
		$V_{IN}=13V$, $V_{INH}=GND$, $T_J=-40 \sim 125^\circ C$ M29150A		0.13	0.18	mA
		$V_{IN}=30V$, $V_{INH}=GND$, $T_J=-40 \sim 125^\circ C$ M29150B				
Short Circuit Current	I_{SC}	$V_{IN}-V_{OUT}=5.5V$		2.2		A
Control Input Logic Low	V_{IL}	OFF MODE (Note 2), $T_J=-40 \sim 125^\circ C$			0.8	V
Control Input Logic High	V_{IH}	ON MODE (Note 2), $T_J=-40 \sim 125^\circ C$	2			V
Control Input Current	I_{INH}	$V_{INH}=13V$, $T_J=-40 \sim 125^\circ C$		5	10	μA
Output Noise Voltage	eN	$B_p=10Hz \sim 100KHz$, $I_{OUT}=100mA$		200		μV_{RMS}
Thermal Shutdown	T_{SHDN}			150		°C

■ ELECTRICAL CHARACTERISTICS(Cont.)

M29150-ADJ ($V_{IN}=3.23V$)


PARAMETER	SYMBOL	CONDITIONS	MIN	TYP	MAX	UNIT
Minimum Operating Input Voltage	V_{IN}	$I_{OUT}=10mA\sim1.5A$, $T_J=-40\sim125^{\circ}C$	2.5			V
Load Regulation	ΔV_{OUT}	$I_{OUT}=10mA\sim1.5A$		0.2	1.0	%
Line Regulation	ΔV_{OUT}	$V_{IN}=2.5V\sim13V$, $I_{OUT}=10mA$		0.06	0.5	%
		$V_{IN}=2.5V\sim30V$, $I_{OUT}=10mA$				
Reference Voltage	V_{REF}	$I_{OUT}=10mA\sim1.5A$, $V_{IN}=2.5\sim4.5V$ $T_J=-40\sim125^{\circ}C$ (Note 4)	-1%	1.23	+1%	V
			-2%		+2%	
Supply Voltage Rejection	SVR	$f=120Hz$, $V_{IN}=3.23\pm1V$, $I_{OUT}=0.75A$ (Note 1)	45	75		dB
Quiescent Current	I_Q	$I_{OUT}=0.75A$, $T_J=-40\sim125^{\circ}C$		15	40	mA
		$I_{OUT}=1.5A$, $T_J=-40\sim125^{\circ}C$		30	80	mA
		$V_{IN}=13V$, $V_{INH}=GND$, $T_J=-40\sim125^{\circ}C$		0.13	0.18	mA
		$V_{IN}=30V$, $V_{INH}=GND$, $T_J=-40\sim125^{\circ}C$				
Adjust Pin Current	I_{ADJ}	$T_J=-40\sim125^{\circ}C$ (Note 1)			1	μA
Short Circuit Current	I_{SC}	$V_{IN}-V_{OUT}=5.5V$		2.2		A
Control Input Logic Low	V_{IL}	OFF MODE (Note 2), $T_J=-40\sim125^{\circ}C$			0.8	V
Control Input Logic High	V_{IH}	ON MODE (Note 2), $T_J=-40\sim125^{\circ}C$	2			V
Control Input Current	I_{INH}	$V_{INH}=13V$, $T_J=-40\sim125^{\circ}C$		5	10	μA
Output Noise Voltage	eN	$B_P=10Hz\sim100KHz$, $I_{OUT}=100mA$		50		μV_{RMS}
Thermal Shutdown	T_{SHDN}			150		$^{\circ}C$

Note: 1. Guaranteed by design.

2. Only for version with Inhibit function.







3. Dropout voltage is defined as the input-to-output differential when the output voltage drops to 99% of its nominal value with $V_{OUT}+1V$ applied to V_{IN} .4. Reference voltage is measured between output and GND pin, with ADJ PIN tied to V_{OUT}

■ TYPICAL APPLICATION CIRCUITS









Note: Only for version with inhibit function.



■ TYPICAL CHARACTERISTICS



■ TYPICAL CHARACTERISTICS(Cont.)



■ TYPICAL CHARACTERISTICS(Cont.)



UTC assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all UTC products described or contained herein. UTC products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. The information presented in this document does not form part of any quotation or contract, is believed to be accurate and reliable and may be changed without notice.