

PD10NG-XXXXZ2:1H30 3KV ISOLATED 2W REGULATED DUAL OUTPUT SIP8

Electrical Specifications

(Typical at + 25°C , nominal input voltage, rated output current unless otherwise specified)

Input Specifions

Voltage range

4.5-9, 9-18, 18-36 and 36-72 VDC Wide Input

Filter

Capacitor type

Isolation Specifications

Rated voltage

3000 VDC

Resistance

>1 GΩ

Capacitance

72PF

Output Specifications

Voltage accuracy

+/- 2 %, typ.

Ripple and noise (at 20 MHz BW)

100 mV p-p, max.

Short circuit protection

Continuous, auto restart

Line voltage regulation

+/- 0.2 % typ.

Load voltage regulation

+/- 0.5 % typ. load = 10 ~ 100%

Temperature coefficient

+/- 0.02 % / °C

General Specifications

Efficiency

Continuous, auto restart

Switching frequency

75 KHz, typ.

Environmental Specifications

Operating temperature (ambient)

- 40 °C to + 80 °C

Storage temperature

- 55 °C to + 125 °C

Humidity

Up to 90 %, non condensing

Cooling

Free air convection

Physical Characteristics

Dimensions SIP

21.80 x 9.20 x 11.10 mm


Case material

Non conductive black plastic


Samples of Partnumbers

PART NO.	INPUT VOLTAGE (VDC)	INPUT CURRENT NO LOAD (mA)	INPUT CURRENT FULL LOAD (mA)	OUTPUT VOLTAGE (VDC)	OUTPUT CURRENT (max.mA)	EFFICIENCY FULL LOAD (% TYP.)
PD10NG-053R3Z2:1H30	4.5 - 9	41	487	+/- 3.3	± 303	68
PD10NG-0505Z2:1H30	4.5 - 9	37	473	+/- 5	± 200	70
PD10NG-0509Z2:1H30	4.5 - 9	37	467	+/- 9	± 111	71
PD10NG-0512Z2:1H30	4.5 - 9	35	442	+/- 12	± 83	75
PD10NG-0515Z2:1H30	4.5 - 9	35	442	+/- 15	± 67	75
PD10NG-0524Z2:1H30	4.5 - 9	35	442	+/- 24	± 42	75
PD10NG-123R3Z2:1H30	9 - 18	24	237	+/- 3.3	± 303	70
PD10NG-1205Z2:1H30	9 - 18	23	227	+/- 5	± 200	73
PD10NG-1209Z2:1H30	9 - 18	22	213	+/- 9	± 111	76
PD10NG-1212Z2:1H30	9 - 18	22	213	+/- 12	± 83	78
PD10NG-1215Z2:1H30	9 - 18	22	213	+/- 15	± 67	78
PD10NG-1224Z2:1H30	9 - 18	22	213	+/- 24	± 42	78
PD10NG-243R3Z2:1H30	18 - 36	12	117	+/- 3.3	±303	71
PD10NG-2405Z2:1H30	18 - 36	12	109	+/- 5	± 200	76
PD10NG-2409Z2:1H30	18 - 36	12	108	+/- 9	±111	77
PD10NG-2412Z2:1H30	18 - 36	12	109	+/- 12	± 83	76
PD10NG-2415Z2:1H30	18 - 36	12	107	+/- 15	± 67	77
PD10NG-2424Z2:1H30	18 - 36	11	106	+/- 24	± 42	78
PD10NG-483R3Z2:1H30	36 - 72	8	58	+/- 3.3	± 303	72
PD10NG-4805Z2:1H30	36 - 72	6	54	+/- 5	± 200	77
PD10NG-4809Z2:1H30	36 - 72	7	53	+/- 9	± 111	78
PD10NG-4812Z2:1H30	36 - 72	6	52	+/- 12	± 83	80
PD10NG-4815Z2:1H30	36 - 72	6	52	+/- 15	± 67	80
PD10NG-4824Z2:1H30	36 - 72	6	52	+/- 24	±42	80

Dimensions




Derating Graph and Pinning



External capacitance:

These converters will work with without external capacitors but they are necessary in order to guarantee the full line load range. All parts have been tested using the following recommended values.




Pin 3 (CTRL)

Control pin (ON/OFF)

Output starts at low or open and stops when high. Voltage applied via a limiting resistor and switching diode. The converter is in a low power mode during the high level phase.

Connection example



Pin 5 (NE)

This pin is used internally and must have have no external connection.

Application Notes

Pin 3: The outside control connection. This pin provides the converter output ON/OFF, and the control common is referred to negative input.

Pin 5: This pin belongs to the secondary side. It just avoids someone to reverses the primary and secondary.

Specification can be changed without notice.

Copyright PEAK electronics GmbH