



PRESS FIT AUTOMOTIVE RECTIFIER

LPB251 THRU LPB256
LPBS251 THRU LPBS256

VOLTAGE RANGE 100 to 600 Volts

CURRENT 25.0 Amperes


TECHNICAL SPECIFICATION:

FEATURES

- Low Leakage
- Low forward voltage drop
- High current capability
- High forward surge current capacity

MECHANICAL DATA

- Technology: Cell with Vacuum soldered
- Case: Copper case
- Polarity: As marked of case bottom
- Lead: Plated lead, solderable per MIL-STD-202E method 208C
- Mounting: Press Fit
- Weight: 0.17 ounces, 4.84 grams (LPB)
- Weight: 0.14 ounces, 3.96 grams (LPBS)



MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

- Ratings at 25°C ambient temperature unless otherwise specified
- Single Phase, half wave, 60HZ, resistive or inductive load
- For capacitive load derate current by 20%

	SYMBOLS	LPB251 LPBS251	LPB252 LPBS252	LPB254 LPBS254	LPB256 LPBS256	UNIT
Maximum Repetitive Peak Reverse Voltage	V _{RRM}	100	200	400	600	Volts
Maximum RMS Voltage	V _{RMS}	70	140	280	420	Volts
Maximum DC Blocking Voltage	V _{DC}	100	200	400	600	Volts
Maximum Average Forward Rectified Current, At Tc=105°C	I _(AV)	25				Amps
Peak Forward Surge Current 3.3mS single half sine wave superimposed on Rated load (JEDEC method)	I _{FSM}	400				Amps
Rating for fusing (t<8.3ms)	I ² t	664				A ² S
Maximum instantaneous Forward Voltage at 80A	V _F	1.10				Volts
Maximum DC Reverse Current at Rated TA=25°C DC Blocking Voltage TA=100°C	I _R	5.0				UA
		250				
Typical Thermal Resistance	R _{θJC}	1.0				°C/W
Operating and Storage Temperature Range	T _J ,T _{STG}	(-65 to +175)				°C
Polarity and voltage demotion color band (button)		Yellow	Silver	Orange	Green	

Notes:

1. Enough heatsink must be considered in application.



PRESS FIT AUTOMOTIVE RECTIFIER


LPB251 THRU LPB256
LPBS251 THRU LPBS256

VOLTAGE RANGE 100 to 600 Volts
CURRENT 25.0 Amperes


RATINGS AND CHARACTERISTIC CURVES

LPB251 THRU LPB256
LPBS2505 THRU LPBS256


F1G.1 TYPICAL FORWARD CURRENT
DERATING CURVE



F1G.2 MAXIMUM NON-REPETITIVE PEAK
FORWARD SURGE CURRENT



F1G.3 TYPICAL INSTANTANEOUS
FORWARD CHARACTERISTICS



F1G.4 FORWARD POWER DISSIPATION

