


LL103A...LL103C

SILICON SCHOTTKY BARRIER DIODES

for general purpose applications

The LL103A, B, C is a metal on Silicon Schottky barrier device which is protected by a PN junction guard ring. The low forward voltage drop and fast switching make it ideal for protection of MOS devices, steering, biasing and coupling diodes for fast switching and low logic level applications. Other uses are for click suppression, efficient full wave bridges in telephone subsets, and as blocking diodes in rechargeable low voltage battery systems.


This diode is also available in DO-35 case with type designation SD103A, B, C.



Glass case MiniMELF
Dimensions in mm

Absolute Maximum Ratings (T_a = 25°C)

		Symbol	Value	Unit
Peak Reverse Voltage	LL103A	V _{RRM}	40	V
	LL103B	V _{RRM}	30	V
	LL103C	V _{RRM}	20	V
Power Dissipation (Infinite Heatsink) T _c = 3/8 from body Derates at 4 mW/°C to 0 at 125 °C		P _{tot}	400 ¹⁾	mW
Single Cycle Surge 60Hz sinewave		I _{FSM}	15	A
Junction Temperature		T _j	125	°C
Storage Temperature Range		T _s	-55 to +175	°C
¹⁾ Valid provided that electrodes are kept at ambient temperature.				



SEMTECH ELECTRONICS LTD.
(Subsidiary of Sino-Tech International Holdings Limited, a company
listed on the Hong Kong Stock Exchange, Stock Code: 724)



ISO/TS 16949 : 2002
Certificate No. 05103



ISO 14001:2004
Certificate No. 7116




ISO 9001:2000
Certificate No. 0506098

Dated : 07/12/2002

LL103A...LL103C


Characteristics at $T_{amb} = 25^{\circ}\text{C}$

	Symbol	Min.	Typ.	Max.	Unit
Forward Voltage					
at $I_F = 20\text{mA}$	V_F	-	-	0.37	V
at $I_F = 200\text{mA}$	V_F	-	-	0.6	V
Leakage Current					
at $V_R = 30\text{V}$ LL103A	I_R	-	-	5	μA
at $V_R = 20\text{V}$ LL103B	I_R	-	-	5	μA
at $V_R = 10\text{V}$ LL103C	I_R	-	-	5	μA
Junction Capacitance					
at $V_R = 0\text{V}$, $f = 1\text{MHz}$	C_{tot}	-	50	-	pF
Reverse Recovery Time					
at $I_F = I_R = 5\text{mA}$ to 200mA , recover to $0.1 I_R$	t_{rr}	-	10	-	ns




SEMTECH ELECTRONICS LTD.

(Subsidiary of Sino-Tech International Holdings Limited, a company
listed on the Hong Kong Stock Exchange, Stock Code: 724)




Dated : 07/12/2002

Typical variation of fwd. current vs.fwd.voltage for primary conduction through the Schottky barrier




Typical high current forward conduction curve



$t_p=300\mu s$, duty cycle=2%



Typical non repetitive forward surge current versus pulse width
Rectangular pulse



Typical variation of reverse current at various temperatures



SEMTECH ELECTRONICS LTD.

(Subsidiary of Sino-Tech International Holdings Limited, a company listed on the Hong Kong Stock Exchange, Stock Code: 724)



ISO/TS 16949 : 2002
Certificate No. 05103






ISO 14001:2004
Certificate No. 7116



ISO 9001:2000
Certificate No. 0506098

Dated : 07/12/2002



SEMTECH ELECTRONICS LTD.
(Subsidiary of Sino-Tech International Holdings Limited, a company
listed on the Hong Kong Stock Exchange, Stock Code: 724)



Dated : 07/12/2002