

LL101A...LL101C


SILICON SCHOTTKY BARRIER DIODES

for general purpose applications

The LL101 Series is a metal on silicon Schottky barrier device which is protected by a PN junction guard ring. The low forward voltage drop and fast switching make it ideal for protection of MOS devices, steering, biasing and coupling diodes for fast switching and low logic level applications.

This diode is also available in DO-35 case with type designation

SD101A, B, C.




Glass case MiniMELF
Dimensions in mm

Absolute Maximum Ratings (T_a = 25°C)

	Symbol	Value	Unit
Peak Reverse Voltage	LL101A V _{RRM}	60	V
	LL101B V _{RRM}	50	V
	LL101C V _{RRM}	40	V
Power Dissipation (Infinite Heatsink)	P _{tot}	400 ¹⁾	mW
Max. Single Cycle Surge 10µs Squarewave	I _{FSM}	2	A
Junction Temperature	T _j	200	°C
Storage Temperature Range	T _s	-55 to +200	°C

¹⁾ Valid provided that electrodes are kept at ambient temperature.



SEMTECH ELECTRONICS LTD.
(Subsidiary of Sino-Tech International Holdings Limited, a company
listed on the Hong Kong Stock Exchange, Stock Code: 724)




Dated : 07/12/2002

LL101A...LL101C


Characteristics at $T_{amb} = 25^{\circ}\text{C}$

		Symbol	Min.	Typ.	Max.	Unit
Reverse Breakdown Voltage at $I_R = 10\mu\text{A}$	LL101A	$V_{(BR)R}$	60	-	-	V
	LL101B	$V_{(BR)R}$	50	-	-	V
	LL101C	$V_{(BR)R}$	40	-	-	V
Forward Voltage Drop at $I_F = 1\text{mA}$ at $I_F = 15\text{mA}$	LL101A	V_F	-	-	0.41	V
	LL101B	V_F	-	-	0.4	V
	LL101C	V_F	-	-	0.39	V
	LL101A	V_F	-	-	1	V
	LL101B	V_F	-	-	0.95	V
	LL101C	V_F	-	-	0.9	V
Leakage Current at $V_R = 50\text{V}$ at $V_R = 40\text{V}$ at $V_R = 30\text{V}$	LL101A	I_R	-	-	200	nA
	LL101B	I_R	-	-	200	nA
	LL101C	I_R	-	-	200	nA
Junction Capacitance at $V_R = 0\text{V}$, $f = 1\text{MHz}$	LL101A	C_{tot}	-	-	2.0	pF
	LL101B	C_{tot}	-	-	2.1	pF
	LL101C	C_{tot}	-	-	2.2	pF
Reverse Recovery Time at $I_F = I_R = 5\text{mA}$, recover to $0.1 I_R$		t_{rr}	-	-	1	ns



SEMTECH ELECTRONICS LTD.


(Subsidiary of Sino-Tech International Holdings Limited, a company
listed on the Hong Kong Stock Exchange, Stock Code: 724)




Dated : 07/12/2002

LL101A...LL101C


Typical variation of fwd. current vs. fwd. voltage for primary conduction through the Schottky barrier





Typical forward conduction curve of combination Schottky barrier and PN junction guard ring



Typical variation of reverse current at various temperatures



Typical capacitance curve as a function of reverse voltage



SEMTECH ELECTRONICS LTD.

(Subsidiary of Sino-Tech International Holdings Limited, a company listed on the Hong Kong Stock Exchange, Stock Code: 724)



ISO/TS 16949 : 2002
Certificate No. 05103



ISO 14001:2004
Certificate No. 7116



ISO 9001:2000
Certificate No. 0506098

Dated : 07/12/2002