



LIGITEK



Lead-Free Parts


FLASH ROUND TYPE LED LAMPS

LFHRF3363-PF

SERIES

Page 1/2

Package Dimension



Features

- Built-in IC chip flashes lamps on and off to attract attention
- Pulse rate 2.4Hz
- T-1 size
- 1 inch leads
- Large full flood radiating area
- IC compatible

Description

The LFHRF3363-PF series is a solid state lamp with a red diffused plastic lens. The built-in IC flashes the lamp on/off and can be driven directly by standard TTL and CMOS circuit eliminating the need for external switching circuitry.

Note: 1. All dimension are in millimeter tolerance is $\pm 0.25\text{mm}$ unless otherwise noted.
2. Specifications are subject to change without notice.

• Part Selection And Application Information (Ratings At 25°C Ambient)

PART NO	MATERIAL	COLOR		Dominant wave length λ_{Dnm}	Spectral halfwidth $\Delta \lambda \text{ nm}$	Pulse rate(Hz) volt=5v		Luminous intensity volt=5v(mcd)		Operating voltage	
		Emitted	Lens			Min.	Max.	Min.	Typ.	Min.	Max.
LFHRF3363-PF	AlGaInP	Red	Water Clear	630	20	2.0	3.0	120	220	3.0	12

• Absolute Maximum Rating (Ta=25°C)

PARAMETER	RED		GREEN		YELLOW			ORANGE		UNIT	REMARK
	HRF										
Peak Current (1/4) Duty cycle	60									mA	
Operating Voltage	15									V	
Reverse Voltage	0.4									V	
Operating Temperature	0°C TO +85°C										
Storage Temperature	-20°C TO +85°C										

**Soldering Condition(Pb-Free)****1.Iron:**

Soldering Iron:30W Max

Temperature 350 ° C Max

Soldering Time:3 Seconds Max(One Time)

Distance:2mm Min(From solder joint to body)

2.Wave Soldering Profile

Dip Soldering

Preheat: 120° C Max

Preheat time: 60seconds Max

Ramp-up

2° C/sec(max)

Ramp-Down:-5° C/sec(max)

Solder Bath:260° C Max

Dipping Time:3 seconds Max

Distance:2mm Min(From solder joint to body)

