



LIGITEK

LIGITEK ELECTRONICS CO.,LTD.

Property of Ligitek Only

---

ROUND TYPE LED LAMPS



Lead-Free Parts

**LDBK2043-W77**

**DATA SHEET**

DOC. NO : QW0905-LDBK2043-W77


REV. : A

DATE : 26 - Feb. - 2009






## Package Dimensions



Note : 1.All dimension are in millimeter tolerance is  $\pm 0.25\text{mm}$  unless otherwise noted.  
2.Specifications are subject to change without notice.

## Directivity Radiation





## Absolute Maximum Ratings at Ta=25

| Parameter                               | Symbol | Ratings    | UNIT |
|-----------------------------------------|--------|------------|------|
|                                         |        | DBK        |      |
| Forward Current                         | IF     | 30         | mA   |
| Peak Forward Current<br>Duty 1/10@10KHz | IFP    | 100        | mA   |
| Power Dissipation                       | PD     | 120        | mW   |
| Reverse Current @5V                     | Ir     | 50         | μ A  |
| Electrostatic Discharge( * )            | ESD    | 500        | V    |
| Operating Temperature                   | Topr   | -20 ~ +80  |      |
| Storage Temperature                     | Tstg   | -30 ~ +100 |      |

★ Static Electricity or power surge will damage the LED. Use of a conductive wrist band or anti-electrosatic glove is recommended when handing these LED. All devices, equipment and machinery must be properly grounded.

## Typical Electrical &amp; Optical Characteristics (Ta=25 )

| PART NO      | MATERIAL  | COLOR   |             | Dominant wave length<br>λ Dnm | Spectral halfwidth<br>λ nm | Forward voltage<br>@20mA(V) |      | Luminous intensity<br>@20mA(mcd) |      | Viewing angle<br>2 θ 1/2<br>(deg) |
|--------------|-----------|---------|-------------|-------------------------------|----------------------------|-----------------------------|------|----------------------------------|------|-----------------------------------|
|              |           | Emitted | Lens        |                               |                            | Typ.                        | Max. | Min.                             | Typ. |                                   |
| LDBK2043-W77 | InGaN/GaN | Blue    | Water Clear | 470                           | 30                         | 3.5                         | 4.0  | 1100                             | 3400 | 30                                |

Note : 1.The forward voltage data did not including ±0.1V testing tolerance.

2. The luminous intensity data did not including ±15% testing tolerance.



## Typical Electro-Optical Characteristics Curve

### DBK CHIP

Fig.1 Forward current vs. Forward Voltage




Fig.2 Relative Intensity vs. Forward Current




Fig.3 Forward Voltage vs. Temperature




Fig.4 Relative Intensity vs. Temperature





Fig.5 Relative Intensity vs. Wavelength



**Soldering Condition(Pb-Free)****1.Iron:**

Soldering Iron:30W Max

Temperature 350° C Max

Soldering Time:3 Seconds Max(One Time)

Distance:2mm Min(From solder joint to case)

**2.Wave Soldering Profile**

Dip Soldering

Preheat: 120° C Max

Preheat time: 60seconds Max

Ramp-up


2° C/sec(max)

Ramp-Down:-5° C/sec(max)

Solder Bath:260° C Max

Dipping Time:3 seconds Max

Distance:2mm Min(From solder joint to case)



Note: 1.Wave solder should not be made more than one time.  
2.You can just only select one of the soldering conditions as above.

**Reliability Test:**

| Test Item                           | Test Condition                                                         | Description                                                                                                                                                             | Reference Standard                                                             |
|-------------------------------------|------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------|
| Operating Life Test                 | 1.Under Room Temperature<br>2.If=20mA<br>3.t=1000 hrs (-24hrs, +72hrs) | This test is conducted for the purpose of determining the resistance of a part in electrical and thermal stressed.                                                      | MIL-STD-750: 1026<br>MIL-STD-883: 1005<br>JIS C 7021: B-1                      |
| High Temperature Storage Test       | 1.Ta=105 ±5<br>2.t=1000 hrs (-24hrs, +72hrs)                           | The purpose of this is the resistance of the device which is laid under condition of high temperature for hours.                                                        | MIL-STD-883:1008<br>JIS C 7021: B-10                                           |
| Low Temperature Storage Test        | 1.Ta=-40 ±5<br>2.t=1000 hrs (-24hrs, +72hrs)                           | The purpose of this is the resistance of the device which is laid under condition of low temperature for hours.                                                         | JIS C 7021: B-12                                                               |
| High Temperature High Humidity Test | 1.Ta=65 ±5<br>2.RH=90%~95%<br>3.t=240hrs ±2hrs                         | The purpose of this test is the resistance of the device under tropical for hours.                                                                                      | MIL-STD-202:103B<br>JIS C 7021: B-11                                           |
| Thermal Shock Test                  | 1.Ta=105 ±5 & -40 ±5<br>(10min) (10min)<br>2.total 10 cycles           | The purpose of this is the resistance of the device to sudden extreme changes in high and low temperature.                                                              | MIL-STD-202: 107D<br>MIL-STD-750: 1051<br>MIL-STD-883: 1011                    |
| Solder Resistance Test              | 1.T.Sol=260 ±5<br>2.Dwell time= 10 ±1sec.                              | This test intended to determine the thermal characteristic resistance of the device to sudden exposures at extreme changes in temperature when soldering the lead wire. | MIL-STD-202: 210A<br>MIL-STD-750: 2031<br>JIS C 7021: A-1                      |
| Solderability Test                  | 1.T.Sol=230 ±5<br>2.Dwell time=5 ±1sec                                 | This test intended to see soldering well performed or not.                                                                                                              | MIL-STD-202: 208D<br>MIL-STD-750: 2026<br>MIL-STD-883: 2003<br>JIS C 7021: A-2 |