





features

- Excellent for high frequency applications
- Low DC resistance and high Q
- Suitable for reflow and wave soldering
- Low tolerance $\pm 2\%$ available
- Small size allows for high density mounting (1E, 1J, 2A, 2B)
- Marking: Yellow marking on blue protective coating (1E, 1J, 2A, 2B)
- Products with lead-free terminations meet EU RoHS and China RoHS requirements

dimensions and construction



Type (Inch Size Code)	Dimensions inches (mm)				
	L	W	c	d	t
1E (0402)	.039 $\pm$.004 (1.0 $\pm$ 0.1)	.02 $\pm$.002 (0.5 $\pm$ 0.05)	.006 $\pm$.004 (0.15 $\pm$ 0.1)	.01 $\pm$.004 (0.25 $\pm$ 0.1)	.014 $\pm$.002 (0.35 $\pm$ 0.05)
1J (0603)	.063 $\pm$.008 (1.6 $\pm$ 0.2)	.031 $\pm$.004 (0.8 $\pm$ 0.1)	.012 $\pm$.004 (0.3 $\pm$ 0.1)	.012 $\pm$.004 (0.3 $\pm$ 0.1)	.02 $\pm$.004 (0.5 $\pm$ 0.1)
2A (0805)	.079 $\pm$.008 (2.0 $\pm$ 0.2)	.049 $\pm$.008 (1.25 $\pm$ 0.2)	.016 $\pm$.008 (0.4 $\pm$ 0.2)	.012 $\pm$.004 (0.3 $\pm$ 0.2)	.02 $\pm$.004 (0.5 $\pm$ 0.1)
2B (1206)	.126 $\pm$.008 (3.2 $\pm$ 0.2)	.063 $\pm$.008 (1.6 $\pm$ 0.2)	.02 $\pm$.008 (0.5 $\pm$ 0.2)	.016 $\pm$.008 (0.4 $\pm$ 0.2)	.024 $\pm$.004 (0.6 $\pm$ 0.1)

Inductance Marking

Part 1J (nH)	Marking
1.0	L1
1.2	L2
1.5	L3
1.8	L4
2.2	22
2.7	27
3.3	33
3.9	39
4.7	47
5.6	56
6.8	68
8.2	82

Part 1J (nH)	Marking
10	10
12	12
15	15
18	H1
22	H2
27	H3
33	H4
39	H5
47	H6
56	H7
68	H8
82	H9

Part Marking	Value (nH) 2.2 - 8.2	Value (nH) 10 and higher
2A	Ex. = 2.2 = 2.2nH	Ex. = 15 = 15nH
2B	Ex. = 2N2 = 2.2nH	Ex. = 15N = 15nH

No marking on 1E (0402)

ordering information

New Part #	KL73	2A	T	TE	4N7	G
	Type	Size Code	Termination Material	Packaging	Nominal Inductance	Tolerance
		1E: 0402 1J: 0603 2A: 0805 2B: 1206	T: Sn	TP: 7" paper 2mm pitch (1E only - 10,000 pieces/reel) TE: 7" embossed plastic 4mm pitch (1J, 2A, 2B - 4,000 pieces/reel)	4N7: 4.7nH 47N: 47nH	B: ± 0.1 nH C: ± 0.2 nH G: $\pm 2\%$ J: $\pm 5\%$

For further information on packaging, please refer to Appendix A.

applications and ratings

Part Designation	Inductance (nH)	Inductance Tolerance	Quality Factor Minimum	Self Resonant Frequency Minimum (MHz)	DC Resistance Maximum (Ω)	Allowable DC Current Maximum (mA)	Measured Frequency (MHz)	
KL731ETTPN56B	0.56	B: ±0.1nH	7	14000	0.10	700	500	
KL731ETTPN68B	0.68							
KL731ETTPN82B	0.82							
KL731ETTP1N0*	1.0	B: ±0.1nH C: ±0.2nH	10	12000	0.15	650		
KL731ETTP1N2*	1.2			10000	0.20			600
KL731ETTP1N5*	1.5							
KL731ETTP1N8*	1.8			8000	0.25	550		
KL731ETTP2N2*	2.2							
KL731ETTP2N7*	2.7							
KL731ETTP3N3*	3.3			6000	0.30	500		
KL731ETTP3N9*	3.9							
KL731ETTP4N7*	4.7							
KL731ETTP5N6*	5.6			5000	0.50	450		
KL731ETTP6N8*	6.8							
KL731ETTP8N2*	8.2							
KL731ETTP10N*	10	G: ±2% J: ±5%	7	4000	1.00	350		
KL731ETTP6N8*	6.8							
KL731ETTP8N2*	8.2							
KL731ETTP10N*	10			2500	1.50	300		
KL731ETTP12N*	12							
KL731ETTP15N*	15							
KL731ETTP18N*	18			2000	2.00	250		
KL731ETTP22N*	22							
KL731ETTP27N*	27							
KL731ETTP33N*	33	7	1500	3.00	200			
KL731ETTP22N*	22							
KL731ETTP27N*	27							
KL731ETTP33N*	33	G: ±2% J: ±5%	20	1000	5.00	150		
KL731JTTE1N0*	1.0							
KL731JTTE1N2*	1.2							
KL731JTTE1N5*	1.5			25	13000	0.10	650	
KL731JTTE1N8*	1.8							
KL731JTTE2N2*	2.2							
KL731JTTE2N7*	2.7							
KL731JTTE3N3*	3.3							
KL731JTTE3N9*	3.9							
KL731JTTE4N7*	4.7			25	10000	0.15	450	
KL731JTTE5N6*	5.6							
KL731JTTE6N8*	6.8							
KL731JTTE8N2*	8.2							
KL731JTTE10N*	10							
KL731JTTE12N*	12							
KL731JTTE15N*	15	10	2500	0.25	350			
KL731JTTE18N*	18							
KL731JTTE22N*	22							
KL731JTTE27N*	27							
KL731JTTE33N*	33							
KL731JTTE39N*	39							
KL731JTTE47N*	47	10	5000	0.50	250			
KL731JTTE56N*	56							
KL731JTTE68N*	68							

* Add tolerance character (B, C, G, J)

For complete environmental specifications, please refer to pages 216.

applications and ratings (continued)

Part Designation	Inductance (nH)	Inductance Tolerance	Quality Factor Minimum	Self Resonant Frequency Minimum (MHz)	DC Resistance Maximum (Ω)	Allowable DC Current Maximum (mA)	Measured Frequency (MHz)			
KL732ATTE1N0*	1.0	C: ±0.2nH	20	13000	0.25	900	500			
KL732ATTE1N2*	1.2									
KL732ATTE1N5*	1.5			10000						
KL732ATTE1N8*	1.8			9000						
KL732ATTE2N2*	2.2		25		8000	800				
KL732ATTE2N7*	2.7				6000					
KL732ATTE3N3*	3.3				5000	0.50		700		
KL732ATTE3N9*	3.9				4500					
KL732ATTE4N7*	4.7				4000					
KL732ATTE5N6*	5.6				3000			500		
KL732ATTE6N8*	6.8	G: ±2% J: ±5%		20		1.00	400	200		
KL732ATTE8N2*	8.2						2500			
KL732ATTE10N*	10					2000				
KL732ATTE12N*	12					1500	300			
KL732ATTE15N*	15		15		1.50	250	200			
KL732ATTE18N*	18					1000				
KL732ATTE22N*	22				800					
KL732ATTE27N*	27				700	4.00			150	
KL732ATTE33N*	33		10		600	5.00				
KL732ATTE39N*	39									
KL732ATTE47N*	47									
KL732ATTE56N*	56									
KL732ATTE68N*	68									
KL732ATTE82N*	82									
KL732BTTE2N2*	2.2	C: ±0.2nH	25	9000	0.25	1000	500			
KL732BTTE2N7*	2.7							7000		
KL732BTTE3N3*	3.3					6000				
KL732BTTE3N9*	3.9		35		5000	900		800		
KL732BTTE4N7*	4.7				4500					
KL732BTTE5N6*	5.6			4000	0.50					
KL732BTTE6N8*	6.8			3500						
KL732BTTE8N2*	8.2			3000						
KL732BTTE10N*	10	40		2500						
KL732BTTE12N*	12			2000	1.00	500				
KL732BTTE15N*	15			1500						
KL732BTTE18N*	18									
KL732BTTE22N*	22		G: ±2% J: ±5%	25	1000	2.00	400	200		
KL732BTTE27N*	27									
KL732BTTE33N*	33									
KL732BTTE39N*	39									
KL732BTTE47N*	47	15		500	400	200				
KL732BTTE56N*	56									
KL732BTTE68N*	68									
KL732BTTE82N*	82									
KL732BTTE100*	100								400	

* Add tolerance character (B, C, G, J)

For complete environmental specifications, please refer to pages 216.

Specifications given herein may be changed at any time without prior notice. Please confirm technical specifications before you order and/or use.

1/10/06

environmental applications

Performance Characteristics

Parameter	Requirements Maximum Limit	Δ L/L Typical	Test Method
Resistance to Soldering Heat	Without distinct damage in appearance and construction Δ L/L: $\pm 2\%$, Δ Q/Q: $\pm 20\%$	Δ L/L: $\pm 0.5\%$ Δ Q/Q: $\pm 1.5\%$	260°C $\pm$ 5°C, 10s $\pm$ 1s
Rapid Change of Temperature	Without distinct damage in appearance and construction Δ L/L: $\pm 2\%$, Δ Q/Q: $\pm 20\%$	Δ L/L: $\pm 0.5\%$ Δ Q/Q: $\pm 1.6\%$	-40°C (30min.)/ +125°C (30min.) 100 cycles
Low Temperature Exposure	Without distinct damage in appearance and construction Δ L/L: $\pm 2\%$, Δ Q/Q: $\pm 20\%$	Δ L/L: $\pm 0.7\%$ Δ Q/Q: $\pm 1.2\%$	-40°C $\pm$ 3°C, 1000h
High Temperature Exposure	Without distinct damage in appearance and construction Δ L/L: $\pm 2\%$, Δ Q/Q: $\pm 20\%$	Δ L/L: $\pm 0.4\%$ Δ Q/Q: $\pm 1.3\%$	125°C $\pm$ 2°C, 1000h
Moisture Exposure	Without distinct damage in appearance and construction Insulation resistance: 50M Ω or more Δ L/L: $\pm 2\%$, Δ Q/Q: $\pm 20\%$	Δ L/L: $\pm 0.4\%$ Δ Q/Q: $\pm 1.4\%$	40°C $\pm$ 2°C, 90%~95%RH, 1000h
Resistance to Solvent	Without distinct damage in appearance, construction and marking Δ L/L: $\pm 2\%$, Δ Q/Q: $\pm 20\%$	Δ L/L: $\pm 0.6\%$ Δ Q/Q: $\pm 1.2\%$	Immerse the inductors for 30s $\pm$ 5s in the reagent (20°C ~ 25°C) of JIS K8839 (1995)