

RATING AND CHARACTERISTICS - 14mm

Part Number	Maximum Allowable Voltage		Varistor Voltage		Maximum Clamping Voltage	Withstanding Surge Current 8/20 S		Rated Wattage	Energy 10/1000 s	UL	CSA
	Acrms (V)	DC (V)	DC (V)	Tolerance Range	V 50A (V)	1 Time (A)	2 Times (A)	(W)	(J)		
JVR14U201K87□△△	130	170	200	± 10%	340	6500	6000	0.6	84	✓	✓
JVR14U221K87□△△	140	180	220		360				93	✓	✓
JVR14U241K87□△△	150	200	240		395				101	✓	✓

RATING AND CHARACTERISTICS - 20mm

Part Number	Maximum Allowable Voltage		Varistor Voltage		Maximum Clamping Voltage	Withstanding Surge Current 8/20 S		Rated Wattage	Energy 10/1000 s	UL	CSA
	Acrms (V)	DC (V)	DC (V)	Tolerance Range	V 100A (V)	1 Time (A)	2 Times (A)	(W)	(J)		
JVR20U201K11□△△	130	170	200	± 10%	340	12500	10000	1.0	168	✓	✓
JVR20U221K11□△△	140	180	220		360				186	✓	✓
JVR20U241K11□△△	150	200	240		395				202	✓	✓

□ = Lead Style (Y=Vertical kink, P=Straight)
 △△ = Lead Length & Packaging

PULSE RATING & VI CURVES

