

PJSOT05C-02/PJSOT24C-02

STANDARD CAPACITANCE TVS ARRAY

VOLTAGE 5 / 24 Volts **POWER** 140 Watts

FEATURES

- 140 Watts Peak Pulse Power per Line ($t_p=8/20$ ms)
- Low Clamping Voltage
- Available in Multiple Voltage Types Ranging from 5V
- In compliance with EU RoHS 2002/95/EC directives
- IEC61000-4-2 ESD 15kV air, 8kV Contact compliance

MECHANICAL DATA

- Case: SOT-23
- Terminals : Solderable per MIL-STD-750, Method 2026
- Approx. Weight: 0.0003 ounce, 0.0084 gram





Fig.25

SOT-23 Unit: inch (mm)



DEVICE CHARACTERISTICS

Ratings at 25°C unless otherwise specified.

PARAMETER	SYMBOL	VALUE	UNITS
Peak Pulse Power ($t_p=8/20$ μ s)	P_{PP}	140	Watts
Operating Temperature	T_J	-50 to 150	°C
Storage Temperature	T_{STG}	-50 to 150	°C
Forward Voltage@ 100mA,300 μ s-Square Wave	V_F	1.5	Volts

Part Number	Reverse Stand-off Voltage	Minum Breakdown Voltage	Max Clamping Voltage @ 8/20 μ sec	Peak Pulse Current 8/20 μ sec	Maximum Leakage Current	Off-State Capacitance, 1MHz Zero dc Bias	Marking Code
	V_{RWM} Max. V	@1mA V_{BR} V	V_{CL} @ I_{PP} V	I_{PP} Max. A	@ V_{RWM} I_D μ A	Cd Max. pF	
PJSOT05C-02	5	6	11.2	13	20	120	2BC
PJSOT24C-02	24	26.7	47.2	3	20	30	6BC

PAN JIT RESERVES THE RIGHT TO CHANGE THE SPECIFICATION ANY TIME WITHOUT NOTICE IN ORDER TO IMPROVE THE DESIGN AND SUPPLY THE BEST POSSIBLE PRODUCT.

PJSOT05C-02/PJSOT24C-02




FIG.1- TYPICAL CAPACITANCE UNDER BIAS




FIG.2- TYPICAL CAPACITANCE UNDER BIAS




FIG.3- TYPICAL CLAMPING VOLTAGE




FIG.4- TYPICAL CLAMPING VOLTAGE




FIG.5- TYPICAL LEAKAGE CURRENT vs JUNCTION TEMPERATURE





FIG.6- TYPICAL LEAKAGE CURRENT vs JUNCTION TEMPERATURE

PJSOT05C-02/PJSOT24C-02

MOUNTING PAD LAYOUT



ORDER INFORMATION

- Packing information
 - T/R - 12K per 13" plastic Reel
 - T/R - 3K per 7" plastic Reel

LEGAL STATEMENT

Copyright PanJit International, Inc 2010

The information presented in this document is believed to be accurate and reliable. The specifications and information herein are subject to change without notice. Pan Jit makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose. Pan Jit products are not authorized for use in life support devices or systems. Pan Jit does not convey any license under its patent rights or rights of others.