

TOSHIBA CMOS Digital Integrated Circuit Silicon Monolithic

# TC74HC597AP, TC74HC597AF

## 8-Bit Latch/Shift Register

The TC74HC597A is a high speed CMOS 8-BIT PARALLEL-IN/SERIAL-IN SERIAL-OUT LATCH/SHIFT REGISTER fabricated with silicon gate C<sup>2</sup>MOS technology.

It achieves the high speed operation similar to equivalent LSTTL while maintaining the CMOS low power dissipation.

It consists of an 8-bit data register feeding an 8-bit shift register. The parallel data on the A to H inputs is stored in the input register on the positive going transition of RCK.

When the  $\overline{\text{SLOAD}}$  input is held low, the input register data is passed into the shift registers. When  $\overline{\text{SLOAD}}$  input is held high, the serial data input (SI) is enabled and the eight flip-flops perform serial shifting on the positive transition of SCK.



A direct clear input ( $\overline{\text{SCLR}}$ ) sets the 8-bit shift register to zero.

All inputs are equipped with protection circuits against static discharge or transient excess voltage.

## Features

- High speed:  $f_{\text{max}} = 60 \text{ MHz}$  (typ.) at  $V_{\text{CC}} = 5 \text{ V}$
- Low power dissipation:  $I_{\text{CC}} = 4 \mu\text{A}$  (max) at  $T_a = 25^\circ\text{C}$
- High noise immunity:  $V_{\text{NIH}} = V_{\text{NIL}} = 28\% V_{\text{CC}}$
- Output drive capability: 10 LSTTL loads
- Symmetrical output impedance:  $|I_{\text{OH}}| = I_{\text{OL}} = 4 \text{ mA}$  (min)
- Balanced propagation delays:  $t_{\text{PLH}} \approx t_{\text{PHL}}$
- Wide operating voltage range:  $V_{\text{CC}} (\text{opr}) = 2 \text{ to } 6 \text{ V}$
- Pin and function compatible with 74LS597


## Pin Assignment



### Weight

DIP16-P-300-2.54A	: 1.00 g (typ.)
SOP16-P-300-1.27A	: 0.18 g (typ.)

IEC Logic Symbol




Truth Table


Inputs					Function
SI	SCK	$\overline{\text{SCLR}}$	$\overline{\text{SLOAD}}$	RCK	
X	X	L	H	X	S.R. is cleared to "L"
X	X	H	L	X	Input register data is stored into S.R.
L		H	H	X	First stage of S.R. become "L". Other stages store the data of previous stage, respectively.
H		H	H	X	First stage of S.R. become "H". Other stages store the data of previous stage, respectively.
X		H	H	X	State of S.R. is not changed.
X	X	X	X		Input data on A to H line is stored into input register.
X	X	X	X		Storage register stage is not changed.

X: Don't care

Timing Chart



## System Diagram



## Absolute Maximum Ratings (Note 1)

Characteristics	Symbol	Rating	Unit
Supply voltage range	$V_{CC}$	-0.5 to 7.0	V
DC input voltage	$V_{IN}$	-0.5 to $V_{CC} + 0.5$	V
DC output voltage	$V_{OUT}$	-0.5 to $V_{CC} + 0.5$	V
Input diode current	$I_{IK}$	$\pm 20$	mA
Output diode current	$I_{OK}$	$\pm 20$	mA
DC output current	$I_{OUT}$	$\pm 25$	mA
DC $V_{CC}$ /ground current	$I_{CC}$	$\pm 50$	mA
Power dissipation	$P_D$	500 (DIP) (Note 2)/180 (SOP)	mW
Storage temperature	$T_{stg}$	-65 to 150	°C

Note 1: Exceeding any of the absolute maximum ratings, even briefly, lead to deterioration in IC performance or even destruction.

Using continuously under heavy loads (e.g. the application of high temperature/current/voltage and the significant change in temperature, etc.) may cause this product to decrease in the reliability significantly even if the operating conditions (i.e. operating temperature/current/voltage, etc.) are within the absolute maximum ratings and the operating ranges.

Please design the appropriate reliability upon reviewing the Toshiba Semiconductor Reliability Handbook ("Handling Precautions"/"Derating Concept and Methods") and individual reliability data (i.e. reliability test report and estimated failure rate, etc.).

Note 2: 500 mW in the range of  $T_a = -40$  to  $65^\circ\text{C}$ . From  $T_a = 65$  to  $85^\circ\text{C}$  a derating factor of  $-10$  mW/°C should be applied until 300 mW.

## Operating Ranges (Note)

Characteristics	Symbol	Rating	Unit
Supply voltage	$V_{CC}$	2 to 6	V
Input voltage	$V_{IN}$	0 to $V_{CC}$	V
Output voltage	$V_{OUT}$	0 to $V_{CC}$	V
Operating temperature	$T_{opr}$	-40 to 85	°C
Input rise and fall time	$t_r, t_f$	0 to 1000 ( $V_{CC} = 2.0$ V) 0 to 500 ( $V_{CC} = 4.5$ V) 0 to 400 ( $V_{CC} = 6.0$ V)	ns

Note: The operating ranges must be maintained to ensure the normal operation of the device. Unused inputs must be tied to either VCC or GND.

**Electrical Characteristics**
**DC Characteristics**

Characteristics	Symbol	Test Condition		Ta = 25°C			Ta = -40 to 85°C		Unit
				V <sub>CC</sub> (V)	Min	Typ.	Max	Min	Max
High-level input voltage	V <sub>IH</sub>	—		2.0 4.5 6.0	1.50 3.15 4.20	— — —	— — —	1.50 3.15 4.20	V
Low-level input voltage	V <sub>IL</sub>	—		2.0 4.5 6.0	— — —	— — —	0.50 1.35 1.80	— — —	V
High-level output voltage	V <sub>OH</sub>	V <sub>IN</sub> = V <sub>IH</sub> or V <sub>IL</sub>	I <sub>OH</sub> = -20 µA	2.0 4.5 6.0	1.9 4.4 5.9	2.0 4.5 6.0	— — —	1.9 4.4 5.9	V
			I <sub>OH</sub> = -4 mA	4.5 6.0	4.18 5.68	4.31 5.80	— —	4.13 5.63	
			I <sub>OH</sub> = -5.2 mA	4.5 6.0	4.18 5.68	4.31 5.80	— —	4.13 5.63	
			I <sub>OH</sub> = -5.2 mA	4.5 6.0	4.18 5.68	4.31 5.80	— —	4.13 5.63	
Low-level output voltage	V <sub>OL</sub>	V <sub>IN</sub> = V <sub>IH</sub> or V <sub>IL</sub>	I <sub>OL</sub> = 20 µA	2.0 4.5 6.0	— — —	0.0 0.0 0.0	0.1 0.1 0.1	— — —	V
			I <sub>OL</sub> = 4 mA	4.5 6.0	— —	0.17 0.18	0.26 0.26	— —	
			I <sub>OL</sub> = 5.2 mA	4.5 6.0	— —	0.17 0.18	0.26 0.26	— —	
			I <sub>OL</sub> = 5.2 mA	4.5 6.0	— —	0.17 0.18	0.26 0.26	— —	
Input leakage current	I <sub>IN</sub>	V <sub>IN</sub> = V <sub>CC</sub> or GND		6.0	—	—	±0.1	—	µA
Quiescent supply current	I <sub>CC</sub>	V <sub>IN</sub> = V <sub>CC</sub> or GND		6.0	—	—	4.0	—	µA

Timing Requirements (input:  $t_r = t_f = 6 \text{ ns}$ )

Characteristics	Symbol	Test Condition	Ta = 25°C		Ta = -40 to 85°C	Unit
			V <sub>CC</sub> (V)	Typ.	Limit	
Minimum pulse width (SCK, RCK)	$t_W$ (H) $t_W$ (L)	—	2.0	—	75	ns
			4.5	—	15	
			6.0	—	13	
Minimum pulse width ( $\overline{\text{SCLR}}$ )	$t_W$ (L)	—	2.0	—	75	ns
			4.5	—	15	
			6.0	—	13	
Minimum pulse width ( $\overline{\text{SLOAD}}$ )	$t_W$ (L)	—	2.0	—	75	ns
			4.5	—	15	
			6.0	—	13	
Minimum set-up time (RCK- $\overline{\text{SLOAD}}$ )	$t_s$	—	2.0	—	100	ns
			4.5	—	20	
			6.0	—	17	
Minimum set-up time (SI-SCK)	$t_s$	—	2.0	—	75	ns
			4.5	—	15	
			6.0	—	13	
Minimum set-up time (PI-RCK)	$t_s$	—	2.0	—	75	ns
			4.5	—	15	
			6.0	—	13	
Minimum hold time	$t_h$	—	2.0	—	0	ns
			4.5	—	0	
			6.0	—	0	
Minimum removal time ( $\overline{\text{SCLR}}$ , $\overline{\text{SLOAD}}$ )	$t_{\text{rem}}$	—	2.0	—	75	ns
			4.5	—	15	
			6.0	—	13	
Clock frequency	f	—	2.0	—	6	MHz
			4.5	—	30	
			6.0	—	35	

AC Characteristics ( $C_L = 15 \text{ pF}$ ,  $V_{CC} = 5 \text{ V}$ ,  $T_a = 25^\circ\text{C}$ , input:  $t_r = t_f = 6 \text{ ns}$ )

Characteristics	Symbol	Test Condition	Min	Typ.	Max	Unit
Output transition time	$t_{\text{TLH}}$	—	—	5	8	ns
	$t_{\text{THL}}$					
Propagation delay time (SCK-QH')	$t_{\text{PLH}}$	—	—	16	25	ns
	$t_{\text{PHL}}$					
Propagation delay time ( $\overline{\text{SCLR}}$ -QH')	$t_{\text{PHL}}$	—	—	20	32	ns
Propagation delay time ( $\overline{\text{SLOAD}}$ -QH')	$t_{\text{PLH}}$	—	—	18	30	ns
	$t_{\text{PHL}}$					
Propagation delay time (RCK-QH')	$t_{\text{PLH}}$ $t_{\text{PHL}}$	$\overline{\text{SLOAD}} = \text{"L"}$	—	25	37	ns
Clock frequency	$f_{\text{max}}$	—	30	59	—	MHz

**AC Characteristics ( $C_L = 50 \text{ pF}$ , input:  $t_r = t_f = 6 \text{ ns}$ )**

Characteristics	Symbol	Test Condition	$V_{CC}$ (V)	$T_a = 25^\circ\text{C}$			$T_a = -40 \text{ to } 85^\circ\text{C}$		Unit
				Min	Typ.	Max	Min	Max	
Output transition time	$t_{TLH}$ $t_{THL}$	—	2.0	—	32	75	—	95	ns
			4.5	—	8	15	—	19	
			6.0	—	7	13	—	16	
Propagation delay time (SCK-QH')	$t_{pLH}$ $t_{pHL}$	—	2.0	—	78	145	—	180	ns
			4.5	—	20	29	—	36	
			6.0	—	16	25	—	31	
Propagation delay time ( $\overline{\text{SCLR}}$ -QH')	$t_{pHL}$	—	2.0	—	90	175	—	220	ns
			4.5	—	24	35	—	44	
			6.0	—	20	30	—	37	
Propagation delay time ( $\overline{\text{SLOAD}}$ -QH')	$t_{pLH}$ $t_{pHL}$	—	2.0	—	80	175	—	220	ns
			4.5	—	22	35	—	44	
			6.0	—	18	30	—	37	
Propagation delay time (RCK-QH')	$t_{pLH}$ $t_{pHL}$	$\overline{\text{SLOAD}} = "L"$	2.0	—	112	210	—	265	ns
			4.5	—	30	42	—	53	
			6.0	—	24	36	—	45	
Maximum clock frequency	$f_{\text{max}}$	—	2.0	6	12	—	5	—	MHz
			4.5	30	48	—	24	—	
			6.0	35	50	—	28	—	
Input capacitance	$C_{IN}$	—	—	—	5	10	—	10	pF
Power dissipation capacitance	$C_{PD}$ (Note)	—	—	—	60	—	—	—	pF

Note:  $C_{PD}$  is defined as the value of the internal equivalent capacitance which is calculated from the operating current consumption without load.

Average operating current can be obtained by the equation:


$$I_{CC}(\text{opr}) = C_{PD} \cdot V_{CC} \cdot f_{IN} + I_{CC}$$



## Package Dimensions

DIP16-P-300-2.54A

Unit : mm




Weight: 1.00 g (typ.)

## Package Dimensions

SOP16-P-300-1.27A

Unit: mm



Weight: 0.18 g (typ.)

**RESTRICTIONS ON PRODUCT USE**

20070701-EN GENERAL

- The information contained herein is subject to change without notice.
- TOSHIBA is continually working to improve the quality and reliability of its products. Nevertheless, semiconductor devices in general can malfunction or fail due to their inherent electrical sensitivity and vulnerability to physical stress. It is the responsibility of the buyer, when utilizing TOSHIBA products, to comply with the standards of safety in making a safe design for the entire system, and to avoid situations in which a malfunction or failure of such TOSHIBA products could cause loss of human life, bodily injury or damage to property.  
In developing your designs, please ensure that TOSHIBA products are used within specified operating ranges as set forth in the most recent TOSHIBA products specifications. Also, please keep in mind the precautions and conditions set forth in the "Handling Guide for Semiconductor Devices," or "TOSHIBA Semiconductor Reliability Handbook" etc.
- The TOSHIBA products listed in this document are intended for usage in general electronics applications (computer, personal equipment, office equipment, measuring equipment, industrial robotics, domestic appliances, etc.). These TOSHIBA products are neither intended nor warranted for usage in equipment that requires extraordinarily high quality and/or reliability or a malfunction or failure of which may cause loss of human life or bodily injury ("Unintended Usage"). Unintended Usage include atomic energy control instruments, airplane or spaceship instruments, transportation instruments, traffic signal instruments, combustion control instruments, medical instruments, all types of safety devices, etc.. Unintended Usage of TOSHIBA products listed in this document shall be made at the customer's own risk.
- The products described in this document shall not be used or embedded to any downstream products of which manufacture, use and/or sale are prohibited under any applicable laws and regulations.
- The information contained herein is presented only as a guide for the applications of our products. No responsibility is assumed by TOSHIBA for any infringements of patents or other rights of the third parties which may result from its use. No license is granted by implication or otherwise under any patents or other rights of TOSHIBA or the third parties.
- Please contact your sales representative for product-by-product details in this document regarding RoHS compatibility. Please use these products in this document in compliance with all applicable laws and regulations that regulate the inclusion or use of controlled substances. Toshiba assumes no liability for damage or losses occurring as a result of noncompliance with applicable laws and regulations.